

TIP TOP CEMENT SC-BL

Safety Data Sheet

according to the WHS Regulations

Issue date:06/08/2014 Revision date:05/06/2024 Supersedes:27/03/2024 Version: 3.8

SDS No: 00156-0083



SECTION 1: Product identifier

1.1. GHS Product identifier

Product form : Mixture
Product name : TIP TOP CEMENT SC-BL
Product code : 020012, 506 0160, 506 0170, 506 0351, 506 0352, 506 4357, 506 4550, 506 4551, 506 4560, 510 1155, 510 1156, 510 1165, 510 1832, 510 1833, 510 1848, 510 1849, 510 3256, 510 3257, 510 3304, 510 3407, 510 3408, 510 3438, 510 3500, 510 3501, 510 3517, 510 3603, 510 3610, 510 3710, 514 1150, 514 1591, 514 3113, 514 4740, 515 9152, 515 9153, 515 9303, 515 9327, 515 9328, 515 9329, 515 9334, 515 9335, 515 9336, 515 9337, 515 9341, 515 9342, 515 9358, 515 9359, 515 9365, 515 9366, 515 9367, 515 9387, 515 9388, 515 9389, 515 9390, 515 9396, 515 9397, 515 9398, 515 9405, 515 9406, 515 9407, 516 9025, 516 9033, 516 9040, 516 9087, 599 2200

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Recommended use : Adhesive

1.4. Details of manufacturer or importer

Manufacturer

REMA TIP TOP AG
65 Gruber Strasse
Poing 85586
Germany
T +49 (0) 8121 / 707 - 100
info@tiptop.de

E-mail address of competent person responsible for the SDS: sds@gbk-ingelheim.de

Importer

REMA TIP TOP Australia Pty Ltd.
3/20 Worth Street
Chullora NSW 2190
Australia
T +61 2 8755 8400
www.rema-tiptop.com.au

1.5. Emergency phone number

Emergency number : +61-280735031, Infotrac/GBK GmbH-ID: 93591

SECTION 2: Hazard identification

2.1. Classification of the hazardous chemical

Classification according to the model Work Health and Safety Regulations (WHS Regulations)

Flammable liquids, Category 2	H225
Serious eye damage/eye irritation, Category 2A	H319
Specific target organ toxicity – Single exposure, Category 3, Narcosis	H336
Hazardous to the aquatic environment – Acute Hazard, Category 1	H400
Hazardous to the aquatic environment – Chronic Hazard, Category 1	H410

2.2. GHS Label elements, including precautionary statements

Hazard pictograms (GHS AU) :



Flame

Exclamation
mark

Environment

Signal word (GHS AU) :

Danger

Contains

: Ethyl acetate (≥ 60 – < 65 %); Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 3% normal hexane (≥ 20 – < 25 %); N-Cyclohexyl-N-ethylamine (< 1 %); Zinc oxide (< 1 %)

TIP TOP CEMENT SC-BL

Safety Data Sheet

according to the WHS Regulations
SDS No: 00156-0083

Hazard statements (GHS AU)	: H225 - Highly flammable liquid and vapour H319 - Causes serious eye irritation H336 - May cause drowsiness or dizziness H410 - Very toxic to aquatic life with long lasting effects
Precautionary statements (GHS AU)	: P101 - If medical advice is needed, have product container or label at hand. P102 - Keep out of reach of children. P103 - Read carefully and follow all instructions. P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P240 - Ground and bond container and receiving equipment. P241 - Use explosion-proof electrical equipment. P261 - Avoid breathing vapours. P264 - Wash hands thoroughly after handling. P271 - Use only outdoors or in a well-ventilated area. P273 - Avoid release to the environment. P280 - Wear eye protection, face protection, protective gloves, protective clothing. P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water . P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P312 - Call a doctor, a POISON CENTER if you feel unwell. P337+P313 - If eye irritation persists: Get medical attention. P391 - Collect spillage. P403+P233 - Store in a well-ventilated place. Keep container tightly closed. P403+P235 - Store in a well-ventilated place. Keep cool. P405 - Store locked up. P501 - Dispose of contents and container to an approved waste disposal plant.
Additional hazard statements (GHS AU)	: AUH066 - Repeated exposure may cause skin dryness or cracking.

2.3. Other hazards which do not result in classification

Other hazards not contributing to the classification : Vapours may form explosive mixture with air.

SECTION 3: Composition and information on ingredients

Comments : Preparation in organic solvents.

Name	CAS-No.	%	Classification according to the model Work Health and Safety Regulations (WHS Regulations)
Ethyl acetate	141-78-6	≥ 60 – < 65	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 3% normal hexane	92062-15-2	≥ 20 – < 25	Flam. Liq. 2, H225 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
N-Cyclohexyl-N-ethylamine	5459-93-8	< 1	Flam. Liq. 3, H226 Acute Tox. 4 (Oral), H302 Acute Tox. 3 (Dermal), H311 Acute Tox. 4 (Inhalation), H332 Skin Corr. 1B, H314 Eye Dam. 1, H318 Aquatic Chronic 3, H412
Zinc oxide	1314-13-2	< 1	Aquatic Acute 1, H400 Aquatic Chronic 1, H410

TIP TOP CEMENT SC-BL

Safety Data Sheet

according to the WHS Regulations
SDS No: 00156-0083

Name	CAS-No.	%	Classification according to the model Work Health and Safety Regulations (WHS Regulations)
Other substances (not contributing to the classification of this product)	-	Up to 100%	-

Comments : Note 10 : The classification as a carcinogen by inhalation applies only to mixtures in powder form containing 1 % or more of titanium dioxide which is in the form of or incorporated in particles with aerodynamic diameter $\leq 10 \mu\text{m}$.

SECTION 4: First aid measures

4.1. Description of necessary first-aid measures

First-aid measures general : Take off immediately all contaminated clothing. Move the affected person away from the contaminated area. Call a poison center or a doctor if you feel unwell.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Move to fresh air in case of accidental inhalation of vapours or decomposition products. If you feel unwell, seek medical advice.

First-aid measures after skin contact : Wash off immediately with soap and plenty of water. Get medical advice if skin irritation persists. Rinse skin with water/shower. Take off immediately all contaminated clothing.

First-aid measures after eye contact : Wash immediately with plenty water (during 20 minutes), also under eyelids. Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

First-aid measures after ingestion : Do not induce vomiting. Call a physician immediately. Do not induce vomiting without medical advice.

4.2. Symptoms caused by exposure

Symptoms/effects after inhalation : May cause drowsiness or dizziness.

Symptoms/effects after eye contact : Eye irritation.

Symptoms/effects after ingestion : Aspiration hazard.

4.3. Medical attention and special treatment

Treatment : Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

Unsuitable extinguishing media : high volume water jet.

5.2. Specific hazards arising from the chemical

Fire hazard : Highly flammable liquid and vapour.

Explosion hazard : Explosive vapour/air mixtures may be formed.

General measures : In case of vapour formation use adequate respirator. Use protective clothing. Ensure adequate air ventilation. Use explosion-proof equipment.

Hazardous decomposition products in case of fire : Carbon oxides (CO, CO₂).

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Fight fire from safe distance and protected location.

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

Hazchem Code : * 3Y

TIP TOP CEMENT SC-BL

Safety Data Sheet

according to the WHS Regulations
SDS No: 00156-0083

Other information : The vapour/air mixture is explosive, even in empty, uncleaned receptacles. Cool containers / tanks with spray water if possible. Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations. Vapours are heavier than air and may spread along floors.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : In case of vapour formation use adequate respirator. Use protective clothing. Ensure adequate air ventilation. Use explosion-proof equipment.

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment. Do not discharge into drains or the environment.

6.3. Methods and materials for containment and cleaning up

For containment : Dam up the liquid spill.

Methods for cleaning up : Take up liquid spill into absorbent material. Shovel or sweep up and put in a closed container for disposal. Soak up with inert absorbent material (for example sand, sawdust, a universal binder, silica gel). Notify authorities if product enters sewers or public waters.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Do not smoke. Avoid contact with skin, eyes and clothing. Provide sufficient air exchange and/or exhaust in work rooms. Vapours are heavier than air and may spread along floors. Keep container tightly closed. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Use only outdoors or in a well-ventilated area. Avoid breathing vapours. Avoid contact with skin and eyes.

Hygiene measures : Apply emollient cream. Avoid contact with skin, eyes and clothing. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Pay attention to explosion protection guidelines. Ground/bond container and receiving equipment.

Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.

Incompatible materials : oxidizing materials. Nitrous acid and other nitrosating agents.

Information on mixed storage : Keep away from food, drink and animal feeding stuffs.

SECTION 8: Exposure controls and personal protection

8.1. Control parameters - exposure standards

TIP TOP CEMENT SC-BL

Safety Data Sheet

according to the WHS Regulations
SDS No: 00156-0083

Ethyl acetate (141-78-6)	
Australia - Occupational Exposure Limits	
Local name	Ethyl acetate (Acetic acid ethyl ester; Acetic ester)
OES TWA	720 mg/m ³
	200 ppm
OES STEL	1440 mg/m ³
	400 ppm
Regulatory reference	Workplace exposure standards for airborne contaminants (2024)

Zinc oxide (1314-13-2)	
Australia - Occupational Exposure Limits	
Local name	Zinc oxide
OES TWA	10 mg/m ³ dust
	5 mg/m ³ fume
OES STEL	10 mg/m ³ fume
Remark (AU)	Dust: (a) This value is for inhalable dust containing no asbestos and < 1% crystalline silica.
Regulatory reference	Workplace exposure standards for airborne contaminants (2024)

8.2. Biological Monitoring

Monitoring methods : A specific exposure sampling method is not available.

8.3. Engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.

8.4. Individual protection measures, such as personal protective equipment (PPE)

Hand protection : Splash protection. This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions. Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves

Type	Material	Permeation	Thickness (mm)	Penetration	Standard
protective gloves	Natural rubber	1 (> 10 minutes)	≥0.6		EN ISO 374
protective gloves	Butyl rubber	3 (> 60 minutes)	≥0.7		EN ISO 374

Eye protection : Eyewash bottle with clean water (EN 15154)

Type	Field of application	Characteristics	Standard
Protective goggles (EN 166)	Liquid splashes may occur		EN 166

Skin and body protection :

Type	Standard
Chemical resistant apron	EN 467

Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment

Device	Filter type	Condition	Standard
Respiratory protective device with a gas filter	Type A - High-boiling (>65 °C) organic compounds		EN 14387

Environmental exposure controls : Avoid release to the environment.

TIP TOP CEMENT SC-BL

Safety Data Sheet

according to the WHS Regulations
SDS No: 00156-0083

SECTION 9: Physical and chemical properties

Physical state	: Liquid
Appearance	: Viscous.
Colour	: Blue
Odour	: Ester like
Odour threshold	: No data available
pH	: No data available
pH solution	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point / Freezing point	: No data available
Boiling point	: > 35 °C
Flash point	: -20 °C DIN EN ISO 3679
Auto-ignition temperature	: 460 °C
Flammability	: No data available
Vapour pressure	: Vapour pressure: 100 hPa @20°C
Relative density	: No data available
Density	: Density: 0.88 g/cm ³ @20°C
Solubility	: Water: Not miscible
Log Pow	: No data available
Viscosity, kinematic	: 3740 – 3820 mm ² /s @40°C (Flow time: 385 s @23°C, 6 DIN EN ISO 2431)
Viscosity, dynamic	: 4500 – 6500 mPa.s @20°C
Explosive properties	: Product is not explosive. May form flammable/explosive vapour-air mixture.
Oxidising properties	: Not oxidising
Explosive limits	: No data available
Minimum ignition energy	: No data available
VOC content	: < 85 %
Fat solubility	: No data available
Additional information	: Solvent separation test (%) : < 3 %

SECTION 10: Stability and reactivity

Reactivity	: No decomposition if stored normally. Highly flammable liquid and vapour.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: Reacts with oxidants.
Conditions to avoid	: To avoid thermal decomposition, do not overheat. Heating can release vapours which can be ignited. Vapour/air-mixtures are explosive at intense warming. Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.
Incompatible materials	: Oxidizing agent. Nitrous acid and other nitrosating agents.
Hazardous decomposition products	: Thermal decomposition generates : Carbon oxides (CO, CO ₂). An inappropriate handling, for instance major amounts of product combined with strong heat and nitrosating agents, renders possible a cleavage of nitrosamines in traces.

SECTION 11: Toxicological information

Acute toxicity (oral)	: Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (dermal)	: Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (inhalation)	: Not classified (Based on available data, the classification criteria are not met)

Ethyl acetate (141-78-6)	
LD50 oral rat	5620 mg/kg
LD50 dermal rabbit	> 18000 mg/kg
LC50 Inhalation - Rat	56 mg/l/4h
N-Cyclohexyl-N-ethylamine (5459-93-8)	
ATE AU (oral)	500 mg/kg bodyweight
ATE AU (dermal)	300 mg/kg bodyweight

TIP TOP CEMENT SC-BL

Safety Data Sheet

according to the WHS Regulations
SDS No: 00156-0083

N-Cyclohexyl-N-ethylamine (5459-93-8)	
ATE AU (gases)	4500 ppmv/4h
ATE AU (vapours)	11 mg/l/4h
ATE AU (dust,mist)	1.5 mg/l/4h
Zinc oxide (1314-13-2)	
LD50 oral rat	> 5000 mg/kg (OECD 401 method)
LD50 dermal rat	> 2000 mg/kg bodyweight (OECD 402 method)
LC50 Inhalation - Rat	> 5.7 mg/l/4h

Skin corrosion/irritation	: Not classified (Based on available data, the classification criteria are not met)
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: Not classified (Based on available data, the classification criteria are not met)
Germ cell mutagenicity	: Not classified (Based on available data, the classification criteria are not met)
Carcinogenicity	: Not classified (Based on available data, the classification criteria are not met)
Reproductive toxicity	: Not classified (Based on available data, the classification criteria are not met)
STOT-single exposure	: May cause drowsiness or dizziness.
STOT-repeated exposure	: Not classified (Based on available data, the classification criteria are not met)
Aspiration hazard	: Not classified (Based on available data, the classification criteria are not met).
Potential adverse human health effects and symptoms	: High concentration of vapours may induce: headache, nausea, dizziness. Repeated or prolonged exposure may cause skin irritation and dermatitis, due to degreasing properties of the product
Other information	: An inappropriate handling, for instance major amounts of product combined with strong heat and nitrosating agents, renders possible a cleavage of nitrosamines in traces

SECTION 12: Ecological information

12.1. Ecotoxicity

Hazardous to the aquatic environment, short-term (acute)	: Very toxic to aquatic life.
Hazardous to the aquatic environment, long-term (chronic)	: Very toxic to aquatic life with long lasting effects.
Other information	: Do not flush into surface water or sewer system.

Ethyl acetate (141-78-6)	
LC50 fish 1	230 mg/l (Exposure time: 96 h - Species: Pimephales promelas)
EC50 Daphnia 1	610 mg/l (Exposure time: 48 h - Species: Daphnia magna)
NOEC chronic crustacea	2.4 mg/l 21 d, Daphnia magna (Water flea)
NOEC chronic algae	> 100 mg/l 72 h, Desmodesmus subspicatus

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 3% normal hexane (92062-15-2)	
LC50 fish 1	12 mg/l 96 h, Oncorhynchus mykiss (Rainbow trout)
EC50 Daphnia 1	3 mg/l 48 h, Daphnia magna (Water flea)

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

TIP TOP CEMENT SC-BL

Safety Data Sheet

according to the WHS Regulations
SDS No: 00156-0083

12.5. Other adverse effects

Ozone : Not classified (Based on available data, the classification criteria are not met)
Other adverse effects : Significantly hazardous to water.

TIP TOP CEMENT SC-BL

Fluorinated greenhouse gases False

Ethyl acetate (141-78-6)

Fluorinated greenhouse gases False

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 3% normal hexane (92062-15-2)

Fluorinated greenhouse gases False

N-Cyclohexyl-N-ethylamine (5459-93-8)

Fluorinated greenhouse gases False

Zinc oxide (1314-13-2)

Fluorinated greenhouse gases False

SECTION 13: Disposal considerations

Waste treatment methods : Recycling is preferred to disposal or incineration. Can be incinerated according to local regulations. Dispose of contents/container in accordance with licensed collector's sorting instructions.

Product/Packaging disposal recommendations : Empty containers should be taken for local recycling, recovery or waste disposal. Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse. Packaging that cannot be cleaned should be disposed of like the product.

Additional information : Flammable vapours may accumulate in the container.

SECTION 14: Transport information

In accordance with ADG / IMDG / IATA

ADG	IMDG	IATA
14.1. UN number		
1133	1133	1133
14.2. UN Proper Shipping Name		
ADHESIVES	ADHESIVES	Adhesives
14.3. Transport hazard class(es)		
3	3	3
14.4. Packing group		
III - Substances presenting low danger	III	III
14.5. Environmental hazards		
Dangerous for the environment: Yes	Dangerous for the environment: Yes Marine pollutant: Yes	Dangerous for the environment: Yes

TIP TOP CEMENT SC-BL

Safety Data Sheet

according to the WHS Regulations
SDS No: 00156-0083

14.6. Special precautions for user

Specific storage requirement : No data available
Shock sensitivity : No data available

14.7. Additional information

Other information : No supplementary information available

Transport by road and rail

UN-No. (ADG) : 1133
Special provision (ADG) : 223
Limited quantities (ADG) : 5I
Excepted quantities (ADG) : E1
Packing instructions (ADG) : P001, IBC03, LP01
Special packing provisions (ADG) : PP1
Portable tank and bulk container instructions (ADG) : T2
Portable tank and bulk container special provisions (ADG) : TP1

Transport by sea

UN-No. (IMDG) : 1133
Special provisions (IMDG) : 223, 955
Limited quantities (IMDG) : 5 L
Excepted quantities (IMDG) : E1
Packing instructions (IMDG) : P001, LP01
Special packing provisions (IMDG) : PP1
IBC packing instructions (IMDG) : IBC03
Tank instructions (IMDG) : T2
Tank special provisions (IMDG) : TP1
Stowage category (IMDG) : A

Air transport

UN-No. (IATA) : 1133
PCA Excepted quantities (IATA) : E1
PCA Limited quantities (IATA) : Y344
PCA limited quantity max net quantity (IATA) : 10L
PCA packing instructions (IATA) : 355
PCA max net quantity (IATA) : 30L (IATA 3.3.3.1.)
CAO packing instructions (IATA) : 366
CAO max net quantity (IATA) : 100L (IATA 3.3.3.1)
Special provisions (IATA) : A3
ERG code (IATA) : 3L

Other applicable information : (Packing group III, if content of packaging ≤ 450l, according 2.2.3.1.4 ADR, RID, ADN);
(Packing group III, if content of packaging ≤ 450l, according 2.3.2.2 IMDG)

14.8. Hazchem or Emergency Action Code

Hazchem Code : * 3Y

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations

Australian Industrial Chemicals Introduction Scheme (AICIS)

Australian Inventory of Industrial Chemicals (AICIS Inventory) status : Contains substance(s) listed on Australian Industrial Chemicals Introduction Scheme (AICIS Inventory)

Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP)

Relevant Poisons Schedule number : Labelling requirements for SUSMP do not apply to a poison that is packed and sold solely for industrial, laboratory or manufacturing use. However, this product is labelled in accordance with the Safe Work Australia "Code of Practice" for workplace substances.

TIP TOP CEMENT SC-BL

Safety Data Sheet

according to the WHS Regulations
SDS No: 00156-0083

Australian Pesticides and Veterinary Medicines Authority (APVMA)

No additional information available

15.2. International agreements

No additional information available

SECTION 16: Other information

Abbreviations and acronyms

: ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE - Acute Toxicity Estimate
BCF - Bioconcentration factor
BLV - Biological limit value
BOD - Biochemical oxygen demand (BOD)
COD - Chemical oxygen demand (COD)
DMEL - Derived Minimal Effect level
DNEL - Derived-No Effect Level
EC-No. - European Community number
EC50 - Median effective concentration
EN - European Standard
IARC - International Agency for Research on Cancer
IATA - International Air Transport Association
IMDG - International Maritime Dangerous Goods
LC50 - Median lethal concentration
LD50 - Median lethal dose
LOAEL - Lowest Observed Adverse Effect Level
NOAEC - No-Observed Adverse Effect Concentration
NOAEL - No-Observed Adverse Effect Level
NOEC - No-Observed Effect Concentration
OECD - Organisation for Economic Co-operation and Development
OEL - Occupational Exposure Limit
PBT - Persistent Bioaccumulative Toxic
PNEC - Predicted No-Effect Concentration
RID - Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS - Safety Data Sheet
STP - Sewage treatment plant
ThOD - Theoretical oxygen demand (ThOD)
TLM - Median Tolerance Limit
VOC - Volatile Organic Compounds
CAS-No. - Chemical Abstract Service number
N.O.S. - Not Otherwise Specified
vPvB - Very Persistent and Very Bioaccumulative
ED - Endocrine disruptor
DOT - Department of Transport
TDG - Transportation of Dangerous Goods
REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
GHS - Globally Harmonized System of Classification, Labelling and Packaging of Chemicals
CAS - CAS (Chemical Abstracts Service) number
IBC-Code - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
MARPOL 73/78 - MARPOL 73/78: International Convention for the Prevention of Pollution From Ships
ADG - Transport of Australian Dangerous Goods

Revision date : 5/06/2024

TIP TOP CEMENT SC-BL

Safety Data Sheet

according to the WHS Regulations
SDS No: 00156-0083

Other information : Data of sections 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities. The information describes exclusively the safety requirements for the product(s) and is based on the present level of our knowledge. The delivery specifications are contained in the corresponding product sheet. This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

Classification	
Flam. Liq. 2	H225
Eye Irrit. 2A	H319
STOT SE 3	H336
Aquatic Acute 1	H400
Aquatic Chronic 1	H410

Full text of H-statements	
Acute Tox. 3 (Dermal)	Acute toxicity (dermal), Category 3
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2A	Serious eye damage/eye irritation, Category 2A
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Skin Corr. 1B	Skin corrosion/irritation, Category 1B
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis
H225	Highly flammable liquid and vapour
H226	Flammable liquid and vapour
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H311	Toxic in contact with skin
H314	Causes severe skin burns and eye damage
H318	Causes serious eye damage
H319	Causes serious eye irritation
H332	Harmful if inhaled
H336	May cause drowsiness or dizziness
H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects

TIP TOP CEMENT SC-BL

Safety Data Sheet

according to the WHS Regulations
SDS No: 00156-0083

Full text of H-statements	
H411	Toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should therefore not be construed as guaranteeing any specific property of the product.