

TIP TOP PRIMER PR 200

Safety Data Sheet

according to the WHS Regulations

Issue date:15/06/2021 Revision date:24/01/2025 Supersedes:11/02/2022 Version: 2.6

SDS No: 00156-0030



SECTION 1: Product identifier

1.1. GHS Product identifier

Product form : Mixture
Product name : TIP TOP PRIMER PR 200
Product code : 525 2406, 525 2451, 525 2743, 525 2744, 529 8109

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Recommended use : Primer

1.4. Details of manufacturer or importer

Manufacturer

REMA TIP TOP AG
65 Gruber Strasse
Poing 85586
Germany
T +49 (0) 8121 / 707 - 100
info@tiptop.de

Distributor

REMA TIP TOP Australia Pty Ltd.
3/20 Worth Street
Chullora NSW 2190
Australia
T +61 2 8755 8400
www.rema-tiptop.com.au

E-mail address of competent person responsible for the SDS: sds@gbk-ingelheim.de

1.5. Emergency phone number

Emergency number : +61-280735031, Infotrac/GBK GmbH-ID: 93591

SECTION 2: Hazard identification

2.1. Classification of the hazardous chemical

Classification according to the model Work Health and Safety Regulations (WHS Regulations)

Flammable liquids, Category 2	H225
Acute toxicity (inhalation:dust,mist) Category 4	H332
Skin corrosion/irritation, Category 2	H315
Serious eye damage/eye irritation, Category 2A	H319
Skin sensitisation, Category 1	H317
Germ cell mutagenicity, Category 2	H341
Carcinogenicity, Category 2	H351
Specific target organ toxicity – Single exposure, Category 3, Narcosis	H336
Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation	H335
Hazardous to the aquatic environment – Chronic Hazard, Category 3	H412

2.2. GHS Label elements, including precautionary statements

Hazard pictograms (GHS AU) :



Flame

Exclamation mark

Health hazard

Signal word (GHS AU) :

Danger

Contains :

Phenol formaldehyde resin (< 5 %); Phenol (< 3 %); Formaldehyde (< 0,1 %); Reaction mass of ethylbenzene and xylene (< 10 %); Toluene (< 2 %); 4-methylpentan-2-one (< 75 %)

TIP TOP PRIMER PR 200

Safety Data Sheet

according to the WHS Regulations
SDS No: 00156-0030

Hazard statements (GHS AU)	: H225 - Highly flammable liquid and vapour H315 - Causes skin irritation H317 - May cause an allergic skin reaction H319 - Causes serious eye irritation H332 - Harmful if inhaled H335 - May cause respiratory irritation H336 - May cause drowsiness or dizziness H341 - Suspected of causing genetic defects H351 - Suspected of causing cancer H412 - Harmful to aquatic life with long lasting effects
Precautionary statements (GHS AU)	: P201 - Obtain special instructions before use. P202 - Do not handle until all safety precautions have been read and understood. P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P240 - Ground and bond container and receiving equipment. P261 - Avoid breathing vapours. P264 - Wash hands thoroughly after handling. P271 - Use only outdoors or in a well-ventilated area. P272 - Contaminated work clothing should not be allowed out of the workplace. P273 - Avoid release to the environment. P280 - Wear eye protection, face protection, protective gloves, protective clothing. P281 - Use personal protective equipment as required. P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water . P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P312 - Call a doctor, a POISON CENTER if you feel unwell. P333+P313 - If skin irritation or rash occurs: Get medical attention. P337+P313 - If eye irritation persists: Get medical attention. P362+P364 - Take off contaminated clothing and wash it before reuse. P403+P233 - Store in a well-ventilated place. Keep container tightly closed. P403+P235 - Store in a well-ventilated place. Keep cool. P405 - Store locked up. P501 - Dispose of contents and container to an approved waste disposal plant.

2.3. Other hazards which do not result in classification

Other hazards not contributing to the classification : Vapours may form explosive mixture with air.

SECTION 3: Composition and information on ingredients

Comments : Preparation with polymers in xylene and 4-methylpentan-2-one.

Name	CAS-No.	%	Classification according to the model Work Health and Safety Regulations (WHS Regulations)
4-methylpentan-2-one (< 75 %)	108-10-1	< 75	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation), H332 Eye Irrit. 2A, H319 Carc. 2, H351 STOT SE 3, H336 STOT SE 3, H335

TIP TOP PRIMER PR 200

Safety Data Sheet

according to the WHS Regulations
SDS No: 00156-0030

Name	CAS-No.	%	Classification according to the model Work Health and Safety Regulations (WHS Regulations)
Reaction mass of ethylbenzene and xylene (< 10 %)	-	< 10	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304
Phenol formaldehyde resin (< 5 %)	9003-35-4	< 5	Skin Sens. 1, H317
Phenol (< 3 %)	108-95-2	< 3	Muta. 2, H341 Acute Tox. 3 (Inhalation), H331 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Oral), H301 STOT RE 2, H373 Skin Corr. 1B, H314
Zinc oxide	1314-13-2	< 2,5	Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Toluene	108-88-3	< 2	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Chronic 3, H412
Formaldehyde (< 0,1 %)	50-00-0	< 0,1	Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 2 (Inhalation:dust,mist), H330 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Muta. 2, H341 Carc. 1B, H350
Other substances (not contributing to the classification of this product)	-	Up to 100%	-

SECTION 4: First aid measures

4.1. Description of necessary first-aid measures

First-aid measures general	: Take off immediately all contaminated clothing. Symptoms of poisoning may not appear for several hours. Keep under medical supervision for at least 48 hours. In the event of persistent symptoms receive medical treatment.
First-aid measures after inhalation	: Move to fresh air in case of accidental inhalation of vapours or decomposition products. Call a physician immediately.
First-aid measures after skin contact	: Wash off immediately with soap and plenty of water. Possible risk of resorption through skin. If you feel unwell, seek medical advice.
First-aid measures after eye contact	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Consult an eye specialist. Remove contact lenses, if present and easy to do. Continue rinsing.
First-aid measures after ingestion	: Do not induce vomiting. Rinse mouth out with water. Never give anything by mouth to an unconscious person. Call a physician immediately.

TIP TOP PRIMER PR 200

Safety Data Sheet

according to the WHS Regulations
SDS No: 00156-0030

4.2. Symptoms caused by exposure

Symptoms/effects after inhalation	: Harmful if inhaled. May cause respiratory irritation.
Symptoms/effects after skin contact	: Causes skin irritation. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Causes serious eye irritation.
Chronic symptoms	: Suspected of causing cancer. Suspected of causing genetic defects.

4.3. Medical attention and special treatment

Treatment	: Treat symptomatically.
-----------	--------------------------

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: high volume water jet.

5.2. Specific hazards arising from the chemical

Fire hazard	: Highly flammable liquid and vapour.
Explosion hazard	: Product is not explosive. Explosive vapour/air mixtures may be formed.
General measures	: In case of vapour formation use adequate respirator. Explosion free apparatus have to be used. Ensure adequate air ventilation. Evacuate personnel to a safe area. Concerning personal protective equipment to use, see section 8. Remove ignition sources.
Hazardous decomposition products in case of fire	: Fire may produce: Carbon oxides (CO, CO ₂). Hydrogen chloride.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions	: Fight fire from safe distance and protected location.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
Hazchem Code	: * 3YE
Other information	: Vapours are heavier than air and may spread along floors. The vapour/air mixture is explosive, even in empty, uncleaned receptacles. Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: In case of vapour formation use adequate respirator. Explosion free apparatus have to be used. Ensure adequate air ventilation. Evacuate personnel to a safe area. Concerning personal protective equipment to use, see section 8. Remove ignition sources.
------------------	---

6.1.1. For non-emergency personnel

Emergency procedures	: Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing vapours. Avoid contact with skin and eyes.
----------------------	--

6.1.2. For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
----------------------	---

6.2. Environmental precautions

Do not discharge into the drains/surface waters/groundwater.

6.3. Methods and materials for containment and cleaning up

For containment	: Dike and contain spill.
Methods for cleaning up	: Soak up with inert absorbent material (for example sand, sawdust, a universal binder, silica gel). Shovel or sweep up and put in a closed container for disposal. Clean contaminated surface thoroughly.

TIP TOP PRIMER PR 200

Safety Data Sheet

according to the WHS Regulations
SDS No: 00156-0030

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Keep containers dry and tightly closed to avoid moisture absorption and contamination. Ensure good ventilation of the work station. Vapours are heavier than air. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharge. Use explosion-proof equipment. Wear personal protective equipment. Do not handle until all safety precautions have been read and understood.
- Hygiene measures : Do not inhale vapour. Always wash hands after handling the product. Do not eat, drink or smoke when using this product. Avoid contact with skin, eyes and clothing. Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Pay attention to explosion protection guidelines. Ground/bond container and receiving equipment.
- Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.
- Incompatible materials : oxidizing materials.
- Information on mixed storage : Keep away from food, drink and animal feeding stuffs.

SECTION 8: Exposure controls and personal protection

8.1. Control parameters - exposure standards

Phenol (< 3 %) (108-95-2)	
Australia - Occupational Exposure Limits	
Local name	Phenol
OES TWA	4 mg/m ³
	1 ppm
Remark (AU)	Sk - Absorption through the skin may be a significant source of exposure.
Regulatory reference	Workplace exposure standards for airborne contaminants (2024)
Zinc oxide (1314-13-2)	
Australia - Occupational Exposure Limits	
Local name	Zinc oxide
OES TWA	10 mg/m ³ dust
	5 mg/m ³ fume
OES STEL	10 mg/m ³ fume
Remark (AU)	Dust: (a) This value is for inhalable dust containing no asbestos and < 1% crystalline silica.
Regulatory reference	Workplace exposure standards for airborne contaminants (2024)
Formaldehyde (< 0,1 %) (50-00-0)	
Australia - Occupational Exposure Limits	
Local name	Formaldehyde
OES TWA	1.2 mg/m ³
	1 ppm
OES STEL	2.5 mg/m ³

TIP TOP PRIMER PR 200

Safety Data Sheet

according to the WHS Regulations
SDS No: 00156-0030

Formaldehyde (< 0,1 %) (50-00-0)	
	2 ppm
Remark (AU)	Carc. 2 - Suspected human carcinogen; Sen - Respiratory and/or Skin Sensitiser.
Chemical category	Probable carcinogen
Regulatory reference	Workplace exposure standards for airborne contaminants (2024)

Toluene (108-88-3)	
Australia - Occupational Exposure Limits	
Local name	Toluene
OES TWA	191 mg/m ³
	50 ppm
OES STEL	574 mg/m ³
	150 ppm
Remark (AU)	Sk - Absorption through the skin may be a significant source of exposure.
Chemical category	Skin notation
Regulatory reference	Workplace exposure standards for airborne contaminants (2024)

4-methylpentan-2-one (< 75 %) (108-10-1)	
Australia - Occupational Exposure Limits	
Local name	Methyl isobutyl ketone (MIBK; 4-Methyl-2-pentanone; Hexone)
OES TWA	205 mg/m ³
	50 ppm
OES STEL	307 mg/m ³
	75 ppm
Regulatory reference	Workplace exposure standards for airborne contaminants (2024)

8.2. Biological Monitoring

Monitoring methods : A specific exposure sampling method is not available.

8.3. Engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.

8.4. Individual protection measures, such as personal protective equipment (PPE)

Hand protection : Splash protection. This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions. Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves

Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Chemically resistant protective gloves	Butyl rubber	5 (> 240 minutes)	≥0.7		

Eye protection : Eyewash bottle with clean water (EN 15154)

Type	Field of application	Characteristics	Standard
Protective goggles (EN 166)	Liquid splashes may occur		EN 166

Skin and body protection :

TIP TOP PRIMER PR 200

Safety Data Sheet

according to the WHS Regulations
SDS No: 00156-0030

Type	Standard
Chemical resistant apron	EN 467

Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment

Device	Filter type	Condition	Standard
Respiratory protective device with a gas filter	Type A - High-boiling (>65 °C) organic compounds		EN 14387

Environmental exposure controls : Avoid release to the environment.

Other information : Do not inhale vapour. Do not eat, drink or smoke when using this product. Wash hands immediately after handling the product. Avoid contact with skin, eyes and clothing.

SECTION 9: Physical and chemical properties

Physical state	: Liquid
Appearance	: No data available
Colour	: Grey
Odour	: aromatic
Odour threshold	: No data available
pH	: Not determined
pH solution	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point / Freezing point	: Melting point: Not determined Freezing point: Not determined
Boiling point	: ≈ 117 °C
Flash point	: 17 °C
Auto-ignition temperature	: Not applicable
Decomposition temperature	: Not determined
Flammability	: No data available
Vapour pressure	: Vapour pressure: 7 – 9 hPa @20°C
Relative density	: No data available
Density	: Density: 0.93 g/cm ³ @ 20 °C
Solubility	: immiscible. at 20 °C. Water: Not miscible
Log Pow	: Not determined
Viscosity, kinematic	: > 20.5 mm ² /s @ 40 °C
Viscosity, dynamic	: 500 mPa·s
Explosive properties	: Product is not explosive. May form flammable/explosive vapour-air mixture.
Oxidising properties	: Non oxidizing
Explosive limits	: No data available
Minimum ignition energy	: No data available
VOC content	: < 70 %
Fat solubility	: No data available
Additional information	: Solvent content < 90%

SECTION 10: Stability and reactivity

Reactivity	: No decomposition if stored and applied as directed.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: Reactions with oxidizing agents.
Conditions to avoid	: To avoid thermal decomposition, do not overheat. Vapour/air mixtures are explosive. Heating can release vapours which can be ignited.
Incompatible materials	: Strong oxidizing agent.
Hazardous decomposition products	: No hazardous decomposition products known. Thermal decomposition generates : Carbon oxides (CO, CO ₂). Hydrogen chloride.

TIP TOP PRIMER PR 200

Safety Data Sheet

according to the WHS Regulations
SDS No: 00156-0030

SECTION 11: Toxicological information

Acute toxicity (oral) : Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (dermal) : Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (inhalation) : Inhalation:dust,mist: Harmful if inhaled.

TIP TOP PRIMER PR 200	
ATE AU (dust,mist)	1.684 mg/l/4h
Phenol (< 3 %) (108-95-2)	
ATE AU (oral)	100 mg/kg bodyweight
ATE AU (dermal)	300 mg/kg bodyweight
ATE AU (gases)	700 ppmv/4h
ATE AU (vapours)	3 mg/l/4h
ATE AU (dust,mist)	0.5 mg/l/4h
Zinc oxide (1314-13-2)	
LD50 oral rat	> 5000 mg/kg (OECD 401 method)
LD50 dermal rat	> 2000 mg/kg bodyweight (OECD 402 method)
LC50 Inhalation - Rat	> 5.7 mg/l/4h
Formaldehyde (< 0,1 %) (50-00-0)	
ATE AU (oral)	100 mg/kg bodyweight
ATE AU (dermal)	300 mg/kg bodyweight
ATE AU (dust,mist)	0.05 mg/l/4h
Reaction mass of ethylbenzene and xylene (< 10 %)	
ATE AU (dermal)	1100 mg/kg bodyweight
ATE AU (gases)	4500 ppmv/4h
ATE AU (vapours)	11 mg/l/4h
ATE AU (dust,mist)	1.5 mg/l/4h
4-methylpentan-2-one (< 75 %) (108-10-1)	
ATE AU (gases)	4500 ppmv/4h
ATE AU (vapours)	11 mg/l/4h
ATE AU (dust,mist)	1.5 mg/l/4h

Skin corrosion/irritation : Causes skin irritation.
pH: Not determined

Serious eye damage/irritation : Causes serious eye irritation.
pH: Not determined

Respiratory or skin sensitisation : May cause an allergic skin reaction.

Germ cell mutagenicity : Suspected of causing genetic defects.

Carcinogenicity : Suspected of causing cancer.

Reproductive toxicity : Not classified (Based on available data, the classification criteria are not met)

STOT-single exposure : May cause drowsiness or dizziness. May cause respiratory irritation.

STOT-repeated exposure : Not classified (Based on available data, the classification criteria are not met)

Aspiration hazard : Not classified (Based on available data, the classification criteria are not met).

Potential adverse human health effects and symptoms : High concentration of vapours may induce: headache, nausea, dizziness. Inhalation may cause irritation, cough, shortness of breath. Repeated exposure may cause skin dryness or cracking. Possible risk of resorption through skin

TIP TOP PRIMER PR 200

Safety Data Sheet

according to the WHS Regulations
SDS No: 00156-0030

SECTION 12: Ecological information

12.1. Ecotoxicity

Ecology - general	: Harmful to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short-term (acute)	: Not classified (Based on available data, the classification criteria are not met)
Hazardous to the aquatic environment, long-term (chronic)	: Harmful to aquatic life with long lasting effects.
Other information	: Do not flush into surface water or sewer system.

Formaldehyde (< 0,1 %) (50-00-0)

ErC50 algae	4.89 mg/l
-------------	-----------

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

TIP TOP PRIMER PR 200

Log Pow	Not determined
---------	----------------

Partition coefficient n-octanol/water (Log Kow)	Not determined
---	----------------

12.4. Mobility in soil

TIP TOP PRIMER PR 200

Ecology - soil	No data available.
----------------	--------------------

Log Pow	Not determined
---------	----------------

Partition coefficient n-octanol/water (Log Kow)	Not determined
---	----------------

12.5. Other adverse effects

Ozone	: Not classified (Based on available data, the classification criteria are not met)
Other adverse effects	: Significantly hazardous to water.

TIP TOP PRIMER PR 200

Fluorinated greenhouse gases	False
------------------------------	-------

Phenol formaldehyde resin (< 5 %) (9003-35-4)

Fluorinated greenhouse gases	False
------------------------------	-------

Phenol (< 3 %) (108-95-2)

Fluorinated greenhouse gases	False
------------------------------	-------

Zinc oxide (1314-13-2)

Fluorinated greenhouse gases	False
------------------------------	-------

Formaldehyde (< 0,1 %) (50-00-0)

Fluorinated greenhouse gases	False
------------------------------	-------

Reaction mass of ethylbenzene and xylene (< 10 %)

Fluorinated greenhouse gases	False
------------------------------	-------

Toluene (108-88-3)

Fluorinated greenhouse gases	False
------------------------------	-------

TIP TOP PRIMER PR 200

Safety Data Sheet

according to the WHS Regulations
SDS No: 00156-0030

4-methylpentan-2-one (< 75 %) (108-10-1)	
Fluorinated greenhouse gases	False

SECTION 13: Disposal considerations

Waste treatment methods	: Recycling is preferred to disposal or incineration. Can be incinerated according to local regulations. Dispose of contents/container in accordance with licensed collector's sorting instructions.
Product/Packaging disposal recommendations	: Packaging that cannot be cleaned should be disposed of like the product. Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse. Empty containers should be taken for local recycling, recovery or waste disposal.

SECTION 14: Transport information

In accordance with ADG / IMDG / IATA

ADG	IMDG	IATA
14.1. UN number		
1263	1263	1263
14.2. UN Proper Shipping Name		
PAINT	PAINT	Paint
14.3. Transport hazard class(es)		
3	3	3
		
14.4. Packing group		
II - Substances presenting medium danger	II	II
14.5. Environmental hazards		
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No

14.6. Special precautions for user

Specific storage requirement	: No data available
Shock sensitivity	: No data available

14.7. Additional information

Other information	: No supplementary information available
-------------------	--

Transport by road and rail

UN-No. (ADG)	: 1263
Special provision (ADG)	: 163, 367
Limited quantities (ADG)	: 5I
Packing instructions (ADG)	: P001, IBC02
Special packing provisions (ADG)	: PP1
Portable tank and bulk container instructions (ADG)	: T4
Portable tank and bulk container special provisions (ADG)	: TP1, TP8, TP28

TIP TOP PRIMER PR 200

Safety Data Sheet

according to the WHS Regulations
SDS No: 00156-0030

Transport by sea

UN-No. (IMDG) : 1263
Special provisions (IMDG) : 163, 367
Limited quantities (IMDG) : 5 L
Excepted quantities (IMDG) : E2
Packing instructions (IMDG) : P001
Special packing provisions (IMDG) : PP1
IBC packing instructions (IMDG) : IBC02
Tank instructions (IMDG) : T4
Tank special provisions (IMDG) : TP1, TP8, TP28
Stowage category (IMDG) : B

Air transport

UN-No. (IATA) : 1263
PCA Excepted quantities (IATA) : E2
PCA Limited quantities (IATA) : Y341
PCA limited quantity max net quantity (IATA) : 1L
PCA packing instructions (IATA) : 353
PCA max net quantity (IATA) : 5L
CAO packing instructions (IATA) : 364
CAO max net quantity (IATA) : 60L
Special provisions (IATA) : A3, A72, A192
ERG code (IATA) : 3L

14.8. Hazchem or Emergency Action Code

Hazchem Code : * 3YE

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations

Australian Industrial Chemicals Introduction Scheme (AICIS)

Australian Inventory of Industrial Chemicals (AICIS Inventory) status : Contains substance(s) listed on Australian Industrial Chemicals Introduction Scheme (AICIS Inventory)

Australian Inventory of Industrial Chemicals (AICIS Inventory) status : All components of this mixture are listed on or exempted from AICIS Inventory

Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP)

Relevant Poisons Schedule number : Labelling requirements for SUSMP do not apply to a poison that is packed and sold solely for industrial, laboratory or manufacturing use. However, this product is labelled in accordance with the Safe Work Australia "Code of Practice" for workplace substances.

Australian Pesticides and Veterinary Medicines Authority (APVMA)

No additional information available

15.2. International agreements

No additional information available

SECTION 16: Other information

Revision date : 24/01/2025

Abbreviations and acronyms:

ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
IATA	International Air Transport Association

TIP TOP PRIMER PR 200

Safety Data Sheet

according to the WHS Regulations
SDS No: 00156-0030

Abbreviations and acronyms:	
IMDG	International Maritime Dangerous Goods
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
DOT	Department of Transport
TDG	Transportation of Dangerous Goods
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
GHS	Globally Harmonized System of Classification, Labelling and Packaging of Chemicals
IARC	International Agency for Research on Cancer
vPvB	Very Persistent and Very Bioaccumulative
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
CAS	CAS (Chemical Abstracts Service) number
IBC-Code	International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
ATE	Acute Toxicity Estimate
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
BCF	Bioconcentration factor
MARPOL 73/78	MARPOL 73/78: International Convention for the Prevention of Pollution From Ships
ADG	Transport of Australian Dangerous Goods

Classification	
Flam. Liq. 2	H225
Acute Tox. 4 (Inhalation:dust,mist)	H332
Skin Irrit. 2	H315
Eye Irrit. 2A	H319
Skin Sens. 1	H317
Muta. 2	H341
Carc. 2	H351
STOT SE 3	H336
STOT SE 3	H335
Aquatic Chronic 3	H412

Full text of H-statements	
Acute Tox. 2 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 2
Acute Tox. 3 (Dermal)	Acute toxicity (dermal), Category 3
Acute Tox. 3 (Inhalation)	Acute toxicity (inhal.), Category 3
Acute Tox. 3 (Oral)	Acute toxicity (oral), Category 3
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1

TIP TOP PRIMER PR 200

Safety Data Sheet

according to the WHS Regulations
SDS No: 00156-0030

Full text of H-statements	
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3
Asp. Tox. 1	Aspiration hazard, Category 1
Carc. 1B	Carcinogenicity, Category 1B
Carc. 2	Carcinogenicity, Category 2
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2A	Serious eye damage/eye irritation, Category 2A
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Muta. 2	Germ cell mutagenicity, Category 2
Skin Corr. 1B	Skin corrosion/irritation, Category 1B
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
Skin Sens. 1A	Skin sensitisation, category 1A
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation
H225	Highly flammable liquid and vapour
H226	Flammable liquid and vapour
H301	Toxic if swallowed
H304	May be fatal if swallowed and enters airways
H311	Toxic in contact with skin
H312	Harmful in contact with skin
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H319	Causes serious eye irritation
H330	Fatal if inhaled
H331	Toxic if inhaled
H332	Harmful if inhaled
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H341	Suspected of causing genetic defects
H350	May cause cancer
H351	Suspected of causing cancer
H373	May cause damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects

TIP TOP PRIMER PR 200

Safety Data Sheet

according to the WHS Regulations
SDS No: 00156-0030

Full text of H-statements	
H412	Harmful to aquatic life with long lasting effects

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should therefore not be construed as guaranteeing any specific property of the product.