TIP TOP REMACOAT PR 100

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations
Issue date:11/03/2026 Supersedes:21/02/2022 Version: 1.5
SDS No: 00359-1106

SECTION 1: Identification

1.1. GHS Product identifier

Product form	:	Mixture
Product name	:	TIP TOP REMACOAT PR 100
Product code	:	590 2835, 590 2842, 590 2859, 590 3290

1.2. Other means of identification

No additional information available.

1.3. Recommended use of the chemical and restrictions on use

Recommended use	:	Coating system for protection against wear and corrosion

1.4. Details of manufacturer or importer

Distributor
TIP TOP Oberflaechenschutz Elbe GmbH
4 Heuweg
Wittenberg 6886
Germany
T +49(0)3491/635-50 - F +49(0)3491/635-552

Importer
REMA TIP TOP Australia Pty Ltd.
3/20 Worth Street
Chullora NSW 2190
Australia
T +61 2 8755 8400
www.rema-tiptop.com.au

E-mail address of competent person responsible for the SDS: sds@gbk-ingelheim.de

1.5. Emergency phone number

Emergency number	:	+61-280735031, Infotrac/GBK GmbH-ID: 93591

SECTION 2: Hazard identification

2.1. Classification of the hazardous chemical

Classification according to the model Work Health and Safety Regulations (WHS Regulations)

Flammable liquids, Category 3	H226
Acute toxicity (inhalation:dust,mist) Category 4	H332
Skin corrosion/irritation, Category 2	H315
Serious eye damage/eye irritation, Category 2A	H319
Respiratory sensitisation, Category 1	H334
Skin sensitisation, Category 1	H317
Carcinogenicity, Category 2	H351
Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation	H335
Specific target organ toxicity – Repeated exposure, Category 2	H373
Aspiration hazard, Category 1	H304
Hazardous to the aquatic environment – Chronic Hazard, Category 3	H412

2.2. GHS Label elements, including precautionary statements

Hazard pictograms (GHS AU) :

Flame | Exclamation mark | Health hazard

Signal word (GHS AU)	:	Danger

Contains	:	Diphenylmethanediisocyanate, isomers and homologues (25 - 50 %); 4-isocyanatosulphonyltoluene (≤ 1 %); Xylene (mixed isomers) (25 - 50 %); Ethylbenzene (< 15 %); hexamethylene-di-isocyanate (≤ 1 %)
Hazard statements (GHS AU)	:	H226 - Flammable liquid and vapour H304 - May be fatal if swallowed and enters airways H315 - Causes skin irritation H317 - May cause an allergic skin reaction H319 - Causes serious eye irritation H332 - Harmful if inhaled H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled H335 - May cause respiratory irritation H351 - Suspected of causing cancer H373 - May cause damage to organs through prolonged or repeated exposure H412 - Harmful to aquatic life with long lasting effects
Precautionary statements (GHS AU)	:	P201 - Obtain special instructions before use. P202 - Do not handle until all safety precautions have been read and understood. P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P233 - Keep container tightly closed. P240 - Ground and bond container and receiving equipment. P242 - Use non-sparking tools. P243 - Take action to prevent static discharges. P260 - Do not breathe vapours. P264 - Wash hands thoroughly after handling. P271 - Use only outdoors or in a well-ventilated area. P272 - Contaminated work clothing should not be allowed out of the workplace. P273 - Avoid release to the environment. P280 - Wear eye protection, face protection, protective gloves, protective clothing. P301+P310 - IF SWALLOWED: Immediately call a doctor, a POISON CENTER. P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water . P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P308+P313 - IF exposed or concerned: Get medical attention. P331 - Do NOT induce vomiting. P337+P313 - If eye irritation persists: Get medical attention. P342+P311 - If experiencing respiratory symptoms: Call a doctor, a POISON CENTER. P362 - Take off contaminated clothing. P363 - Wash contaminated clothing before reuse. P403+P235 - Store in a well-ventilated place. Keep cool. P405 - Store locked up. P501 - Dispose of contents and container to an approved waste disposal plant.

2.3. Other hazards which do not result in classification

Other hazards not contributing to the classification	:	Vapours may form explosive mixture with air.

SECTION 3: Composition and information on ingredients

Comments	:	Mixture of the substances listed below with nonhazardous additives.

Name	CAS-No.	%	Classification according to the model Work Health and Safety Regulations (WHS Regulations)
Diphenylmethanediisocyanate, isomers and homologues	9016-87-9	25 - 50	Acute Tox. 4 (Inhalation:dust,mist), H332 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Resp. Sens. 1, H334 Skin Sens. 1, H317 Carc. 2, H351 STOT SE 3, H335 STOT RE 2, H373
Xylene (mixed isomers)	1330-20-7	25 - 50	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Chronic 3, H412
Ethylbenzene	100-41-4	< 15	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation), H332 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Chronic 3, H412
4-isocyanatosulphonyltoluene	4083-64-1	≤ 1	Eye Irrit. 2A, H319 STOT SE 3, H335 Skin Irrit. 2, H315 Resp. Sens. 1, H334
hexamethylene-di-isocyanate	822-06-0	≤ 1	Acute Tox. 4 (Oral), H302 Acute Tox. 2 (Inhalation), H330 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Resp. Sens. 1, H334 Skin Sens. 1, H317 STOT SE 3, H335
Other substances (not contributing to the classification of this product)	-	Up to 100%	-

Specific concentration limits:		
Name	**Product identifier**	**Specific concentration limits (%)**
Diphenylmethanediisocyanate, isomers and homologues	CAS-No.: 9016-87-9	(0.1 ≤ C < 100) Resp. Sens. 1; H334 (5 ≤ C < 100) Skin Irrit. 2; H315 (5 ≤ C < 100) Eye Irrit. 2; H319 (5 ≤ C < 100) STOT SE 3; H335
4-isocyanatosulphonyltoluene	CAS-No.: 4083-64-1	(5 ≤ C ≤ 100) Eye Irrit. 2; H319 (5 ≤ C ≤ 100) STOT SE 3; H335 (5 ≤ C ≤ 100) Skin Irrit. 2; H315
hexamethylene-di-isocyanate	CAS-No.: 822-06-0	(0.5 ≤ C ≤ 100) Resp. Sens. 1; H334 (0.5 ≤ C ≤ 100) Skin Sens. 1; H317

SECTION 4: First aid measures

4.1. Description of necessary first-aid measures

First-aid measures general	:	Take off immediately all contaminated clothing. In the event of persistent symptoms receive medical treatment. Move the affected person away from the contaminated area. Keep under medical supervision for at least 48 hours.
First-aid measures after inhalation	:	Move to fresh air in case of accidental inhalation of vapours or decomposition products. Call a physician immediately. Apply artificial respiration if breathing stopped.
First-aid measures after skin contact	:	Remove immediately all sticky substance. Wash off immediately with soap and plenty of water. Call a physician immediately.
First-aid measures after eye contact	:	Wash immediately with plenty water (during 20 minutes), also under eyelids. Remove contact lenses, if present and easy to do. Continue rinsing. Consult an eye specialist.
First-aid measures after ingestion	:	Call a physician immediately. Do not induce vomiting. Rinse mouth out with water. Do not induce vomiting without medical advice. Attention. Beware, danger of aspiration.

4.2. Symptoms caused by exposure

Symptoms/effects	:	May cause damage to organs through prolonged or repeated exposure.
Symptoms/effects after inhalation	:	May cause respiratory irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled. Harmful if inhaled.
Symptoms/effects after skin contact	:	Causes skin irritation. May cause an allergic skin reaction.
Symptoms/effects after eye contact	:	Causes serious eye irritation.
Symptoms/effects after ingestion	:	May be fatal if swallowed and enters airways.
Chronic symptoms	:	Suspected of causing cancer.

4.3. Medical attention and special treatment

Treatment	:	Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

Suitable extinguishing media	:	Water spray. Dry powder. Alcohol resistant foam. Carbon dioxide.
Unsuitable extinguishing media	:	high volume water jet.

5.2. Specific hazards arising from the chemical

Fire hazard	:	Highly flammable liquid and vapour.
Explosion hazard	:	Explosive vapour/air mixtures may be formed. Product is not explosive.
General measures	:	Ensure adequate air ventilation. Evacuate personnel to a safe area. Concerning personal protective equipment to use, see section 8. Remove ignition sources. Store in tightly closed containers.
Hazardous decomposition products in case of fire	:	Hydrogen cyanide. Carbon monoxide. Carbon dioxide. Nitrous gasses.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions	:	Fight fire from safe distance and protected location.
Protection during firefighting	:	Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
Hazchem Code	:	* 3Y
Other information	:	Do not release chemically contaminated water into drains, soil or surface waters. Sufficient measures must be taken to retain water used for extinguishing. Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Ensure adequate air ventilation. Evacuate personnel to a safe area. Concerning personal protective equipment to use, see section 8. Remove ignition sources. Store in tightly closed containers.

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Do not breathe vapours. Avoid contact with skin and eyes.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment. Do not allow to enter drains or water courses.

6.3. Methods and materials for containment and cleaning up

For containment : Dam up the liquid spill.

Methods for cleaning up : Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Shovel or sweep up and put in a closed container for disposal. Container should not be closed gas-tight. Container can be pressurised by carbon dioxide due to reaction with humid air and/or water.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Take precautionary measures against static discharge. Do not smoke. Keep away from heat and sources of ignition. Use only outdoors or in a well-ventilated area. Vapours are heavier than air and may spread along floors. Keep container tightly closed. Avoid contact with skin and eyes.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Pay attention to explosion protection guidelines.

Storage conditions : Keep container tightly closed in a dry, cool and well-ventilated place.

Incompatible materials : Exothermic reaction on contact with: Acids. Bases. Water. Amines. alcohols.

Information on mixed storage : Keep away from food, drink and animal feeding stuffs. Container can be pressurised by carbon dioxide due to reaction with humid air and/or water.

SECTION 8: Exposure controls and personal protection

8.1. Control parameters - exposure standards

Xylene (mixed isomers) (1330-20-7)	
Australia - Occupational Exposure Limits	
OES TWA	350 mg/m³
	80 ppm
OES STEL	655 mg/m³
	150 ppm

Ethylbenzene (100-41-4)	
Australia - Occupational Exposure Limits	
Local name	Ethyl benzene
OES TWA	434 mg/m³
	100 ppm
OES STEL	543 mg/m³
	125 ppm
Regulatory reference	Workplace exposure standards for airborne contaminants (2025)

hexamethylene-di-isocyanate (822-06-0)	
Australia - Occupational Exposure Limits	
Local name	Hexamethylene diisocyanate (Hexane, 1,6-diisocyanato-; Isocyanates, (poly-) (HDI))
OES TWA	0.02 mg/m³
OES STEL	0.07 mg/m³
Remark (AU)	Sen - Respiratory and/or Skin Sensitiser.
Regulatory reference	Workplace exposure standards for airborne contaminants (2025)

8.2. Biological Monitoring

Monitoring methods : A specific exposure sampling method is not available.

8.3. Engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.

8.4. Individual protection measures, such as personal protective equipment (PPE)

Hand protection : This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions. Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves. Pls. find examples in the protective gloves database under: http://bestglove.com/site/chemrest/

Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Chemically resistant protective gloves	Viton	6 (> 480 minutes)	≥ 0.7		EN ISO 374

Eye protection : Eyewash bottle with clean water (EN 15154)

Type	Field of application	Characteristics	Standard
Protective goggles (EN 166)	Liquid splashes may occur		EN 166

Skin and body protection : Light protective clothing

Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment.

Device	Filter type	Condition	Standard
Respiratory protective device with a gas filter	Type A - High-boiling (>65 °C) organic compounds	In the event of insufficient ventilation:	EN 14387

Environmental exposure controls : Avoid release to the environment.

Other information : Do not inhale vapour. Wash hands before breaks and at the end of workday. Wash hands immediately after handling the product. Do not eat, drink or smoke during use. Treat subsequently with skin cream. Remove and wash contaminated clothing before re-use.

SECTION 9: Physical and chemical properties

Physical state	:	Liquid
Appearance	:	Liquid.
Colour	:	Brown
Odour	:	characteristic
Odour threshold	:	No data available.
pH	:	No data available.
pH solution	:	No data available.
Relative evaporation rate (butylacetate=1)	:	No data available.
Melting point / Freezing point	:	No data available.
Boiling point	:	137 °C
Flash point	:	30 °C
Auto-ignition temperature	:	500 °C
Flammability	:	No data available.
Vapour pressure	:	Vapour pressure: 6.7 hPa @ 20 °C
Relative density	:	No data available.
Density	:	Density: 0.98 g/cm³ @ 20 °C
Solubility	:	Water: Reacts with water
Log Pow	:	No data available.
Viscosity, kinematic	:	< 20.5 mm²/s @ 40 °C
Viscosity, dynamic	:	100 mPa·s
Explosive properties	:	Product is not explosive. Dust may form explosive mixture in air.
Oxidising properties	:	Not oxidising
Explosive limits	:	1.1 Vol-% 7 Vol-%
Minimum ignition energy	:	No data available.
VOC content	:	50 % VOC Directive 2004/42/EC - Decorative paints and varnishes
Fat solubility	:	No data available.
Solid content	:	49,9%

SECTION 10: Stability and reactivity

Reactivity	:	No decomposition if stored and applied as directed.
Chemical stability	:	Stable under normal conditions.
Possibility of hazardous reactions	:	Container can be pressurized by carbon dioxide due to reaction with humid air and/or water. Reactions with strong acids and alkalies.
Conditions to avoid	:	Vapour/air mixtures are explosive.
Incompatible materials	:	Amines. acids and bases. Water. alcohols.
Hazardous decomposition products	:	Thermal decomposition generates : Hydrogen cyanide. Nitrogen oxides. Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

Acute toxicity (oral)	:	No data available. (Based on available data, the classification criteria are not met)
Acute toxicity (dermal)	:	No data available. (Based on available data, the classification criteria are not met)
Acute toxicity (inhalation)	:	Inhalation:dust,mist: Harmful if inhaled.

TIP TOP REMACOAT PR 100	
ATE AU (dust,mist)	2.273 mg/l/4h

Diphenylmethanediisocyanate, isomers and homologues (9016-87-9)	
LD50 oral	> 10000 mg/kg
LD50 dermal	> 9400 mg/kg
ATE AU (dust,mist)	1.5 mg/l/4h

4-isocyanatosulphonyltoluene (4083-64-1)	
LD50 oral rat	2330 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity), 95% CL: 2080 - 2600
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), Guideline: EU Method B.3 (Acute Toxicity (Dermal))

Xylene (mixed isomers) (1330-20-7)	
LD50 oral	3500 mg/kg
LD50 dermal	1700 mg/kg
LC50 Inhalation - Rat (Vapours)	27.57 mg/l/4h
ATE AU (dermal)	1100 mg/kg bodyweight
ATE AU (gases)	4500 ppmv/4h
ATE AU (vapours)	11 mg/l/4h
ATE AU (dust,mist)	1.5 mg/l/4h

Ethylbenzene (100-41-4)	
ATE AU (gases)	4500 ppmv/4h
ATE AU (vapours)	11 mg/l/4h
ATE AU (dust,mist)	1.5 mg/l/4h

hexamethylene-di-isocyanate (822-06-0)	
Acute toxicity (oral)	Harmful if swallowed.
Acute toxicity (dermal)	No data available. (Based on available data, the classification criteria are not met)
Acute toxicity (inhalation)	Fatal if inhaled.
ATE AU (oral)	500 mg/kg bodyweight
ATE AU (gases)	100 ppmv/4h
ATE AU (vapours)	0.5 mg/l/4h
ATE AU (dust,mist)	0.05 mg/l/4h

Skin corrosion/irritation	:	Causes skin irritation.
Serious eye damage/irritation	:	Causes serious eye irritation.
Respiratory or skin sensitisation	:	May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction.
Germ cell mutagenicity	:	No data available. (Based on available data, the classification criteria are not met)
Carcinogenicity	:	Suspected of causing cancer.
Reproductive toxicity	:	No data available. (Based on available data, the classification criteria are not met)
STOT-single exposure	:	May cause respiratory irritation.

hexamethylene-di-isocyanate (822-06-0)	
STOT-single exposure	May cause respiratory irritation.

STOT-repeated exposure	:	May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	:	May be fatal if swallowed and enters airways.
Potential adverse human health effects and symptoms	:	With hypersensitive people, reactions as cough or difficulty of breathing may appear even with tiny concentrations of isocyanates; therefore keep room aerated and ventilated

SECTION 12: Ecological information

12.1. Ecotoxicity

Hazardous to the aquatic environment, short–term (acute) : No data available. (Based on available data, the classification criteria are not met)

Hazardous to the aquatic environment, long–term (chronic) : Harmful to aquatic life with long lasting effects.

Other information : Do not flush into surface water or sewer system. In aqueous systems, formation of unsoluble and chemically inert (inactive) polyureas.

4-isocyanatosulphonyltoluene (4083-64-1)	
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), Guideline: EU Method B.3 (Acute Toxicity (Dermal))
LD50 oral rat	2330 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity), 95% CL: 2080 - 2600

Xylene (mixed isomers) (1330-20-7)	
LC50 fish 1	3.3 mg/l
EC50 Daphnia 1	7.4 mg/l

hexamethylene-di-isocyanate (822-06-0)	
Hazardous to the aquatic environment, short–term (acute)	No data available. (Based on available data, the classification criteria are not met)
Hazardous to the aquatic environment, long–term (chronic)	No data available. (Based on available data, the classification criteria are not met)

12.2. Persistence and degradability

TIP TOP REMACOAT PR 100	
Persistence and degradability	No data available.

12.3. Bioaccumulative potential

TIP TOP REMACOAT PR 100	
Bioaccumulative potential	No data available.

12.4. Mobility in soil

TIP TOP REMACOAT PR 100	
Ecology - soil	No data available.

12.5. Other adverse effects

Ozone : No data available. (Based on available data, the classification criteria are not met)

Other adverse effects : No additional information available.

hexamethylene-di-isocyanate (822-06-0)	
Ozone	No data available. (Based on available data, the classification criteria are not met)

SECTION 13: Disposal considerations

Waste treatment methods : Recycling is preferred to disposal or incineration. Can be incinerated according to local regulations. Dispose of contents/container in accordance with licensed collector's sorting instructions.

Product/Packaging disposal recommendations	:	Packaging that cannot be cleaned should be disposed of like the product. Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse. Empty containers should be taken for local recycling, recovery or waste disposal.
Additional information	:	Flammable vapours may accumulate in the container.

SECTION 14: Transport information

In accordance with ADG / IMDG / IATA

ADG	IMDG	IATA
14.1. UN number		
1993	1993	1993
14.2. UN Proper Shipping Name		
FLAMMABLE LIQUID, N.O.S. (Xylene (mixed isomers) ; Ethylbenzene)	FLAMMABLE LIQUID, N.O.S. (Xylene (mixed isomers) ; Ethylbenzene)	Flammable liquid, n.o.s. (Xylene (mixed isomers) ; Ethylbenzene)
14.3. Transport hazard class(es)		
3	3	3
14.4. Packing group		
III - Substances presenting low danger	III	III
14.5. Environmental hazards		
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No

14.6. Special precautions for user

Specific storage requirement	:	No data available.
Shock sensitivity	:	No data available.

14.7. Additional information

Other information	:	No supplementary information available

Transport by road and rail

UN-No. (ADG)	:	1993
Special provision (ADG)	:	223, 274
Limited quantities (ADG)	:	5l
Packing instructions (ADG)	:	P001, IBC03, LP01
Portable tank and bulk container instructions (ADG)	:	T4
Portable tank and bulk container special provisions (ADG)	:	TP1, TP29

Transport by sea

UN-No. (IMDG)	:	1993
Special provisions (IMDG)	:	223, 274, 955
Limited quantities (IMDG)	:	5 L
Excepted quantities (IMDG)	:	E1
Packing instructions (IMDG)	:	LP01, P001
IBC packing instructions (IMDG)	:	IBC03
Tank instructions (IMDG)	:	T4
Tank special provisions (IMDG)	:	TP1, TP29

Stowage category (IMDG) : A

Air transport

UN-No. (IATA) : 1993
PCA Excepted quantities (IATA) : E1
PCA Limited quantities (IATA) : Y344
PCA limited quantity max net quantity (IATA) : 10L
PCA packing instructions (IATA) : 355
PCA max net quantity (IATA) : 60L
CAO packing instructions (IATA) : 366
CAO max net quantity (IATA) : 220L
Special provisions (IATA) : A3
ERG code (IATA) : 3L

14.8. Hazchem or Emergency Action Code

Hazchem Code : * 3Y

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations

Australian Industrial Chemicals Introduction Scheme (AICIS)

Australian Inventory of Industrial Chemicals (AICIS Inventory) status : All the chemicals contained in this product are listed introductions

Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP)

Relevant Poisons Schedule number : Labelling requirements for SUSMP do not apply to a poison that is packed and sold solely for industrial, laboratory or manufacturing use. However, this product is labelled in accordance with the Safe Work Australia "Code of Practice" for workplace substances.

Australian Pesticides and Veterinary Medicines Authority (APVMA)

Not applicable.

15.2. International agreements

No additional information available.

SECTION 16: Other information

Classification	
Flam. Liq. 3	H226
Acute Tox. 4 (Inhalation:dust,mist)	H332
Skin Irrit. 2	H315
Eye Irrit. 2A	H319
Resp. Sens. 1	H334
Skin Sens. 1	H317
Carc. 2	H351
STOT SE 3	H335
STOT RE 2	H373
Asp. Tox. 1	H304
Aquatic Chronic 3	H412

Full text of H-statements	
Acute Tox. 2 (Inhalation)	Acute toxicity (inhal.), Category 2
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3
Asp. Tox. 1	Aspiration hazard, Category 1
Carc. 2	Carcinogenicity, Category 2
Eye Irrit. 2A	Serious eye damage/eye irritation, Category 2A
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Resp. Sens. 1	Respiratory sensitisation, Category 1
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation
H225	Highly flammable liquid and vapour
H226	Flammable liquid and vapour
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H312	Harmful in contact with skin
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H330	Fatal if inhaled
H332	Harmful if inhaled
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled
H335	May cause respiratory irritation
H351	Suspected of causing cancer
H373	May cause damage to organs through prolonged or repeated exposure
H412	Harmful to aquatic life with long lasting effects

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should therefore not be construed as guaranteeing any specific property of the product.