

# TIP TOP SOLVENT LIQUID BUFFER

## Safety Data Sheet

according to the WHS Regulations

Issue date:03/12/2018 Revision date:24/01/2025 Supersedes:03/06/2022 Version: 2.7

SDS No: 00156-0008



### SECTION 1: Product identifier

#### 1.1. GHS Product identifier

Product form : Mixture  
Product name : TIP TOP SOLVENT LIQUID BUFFER  
Product code : 505 9685, 505 9702, 505 9719, 505 9740, 507 9706, 511 1190, 514 4870, 599 2200, 356 1810

#### 1.2. Other means of identification

No additional information available

#### 1.3. Recommended use of the chemical and restrictions on use

Recommended use : Cleaning agent

#### 1.4. Details of manufacturer or importer

##### Manufacturer

REMA TIP TOP AG  
65 Gruber Strasse  
Poing 85586  
Germany  
T +49 (0) 8121 / 707 - 100  
[info@tiptop.de](mailto:info@tiptop.de)

E-mail address of competent person responsible for the SDS: [sds@gbk-ingelheim.de](mailto:sds@gbk-ingelheim.de)

##### Supplier

REMA TIP TOP Australia Pty Ltd.  
3/20 Worth Street  
Chullora NSW 2190  
Australia  
T +61 2 8755 8400  
[www.rema-tiptop.com.au](http://www.rema-tiptop.com.au)

#### 1.5. Emergency phone number

Emergency number : +61-280735031, Infotrac/GBK GmbH-ID: 93591

### SECTION 2: Hazard identification

#### 2.1. Classification of the hazardous chemical

##### Classification according to the model Work Health and Safety Regulations (WHS Regulations)

Flammable liquids, Category 2	H225
Skin corrosion/irritation, Category 2	H315
Specific target organ toxicity – Single exposure, Category 3, Narcosis	H336
Aspiration hazard, Category 1	H304

#### 2.2. GHS Label elements, including precautionary statements

Hazard pictograms (GHS AU) :



Flame

Exclamation  
mark

Health hazard

Signal word (GHS AU) :

Danger

Contains :

Hydrocarbons, C6, iso, < 3% normal hexane (≤ 25 %)

Hazard statements (GHS AU) :

H225 - Highly flammable liquid and vapour  
H304 - May be fatal if swallowed and enters airways  
H315 - Causes skin irritation  
H336 - May cause drowsiness or dizziness

Precautionary statements (GHS AU) :

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P233 - Keep container tightly closed.  
P240 - Ground and bond container and receiving equipment.  
P242 - Use non-sparking tools.

# TIP TOP SOLVENT LIQUID BUFFER

## Safety Data Sheet

according to the WHS Regulations  
SDS No: 00156-0008

P243 - Take action to prevent static discharges.  
P261 - Avoid breathing vapours.  
P264 - Wash hands, forearms and face thoroughly after handling.  
P271 - Use only outdoors or in a well-ventilated area.  
P280 - Wear eye protection, face protection, protective gloves, protective clothing.  
P301+P310 - IF SWALLOWED: Immediately call a doctor, a POISON CENTER.  
P302+P352 - IF ON SKIN: Wash with plenty of soap and water.  
P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water .  
P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P312 - Call a doctor, a POISON CENTER if you feel unwell.  
P331 - Do NOT induce vomiting.  
P332+P313 - If skin irritation occurs: Get medical attention.  
P362 - Take off contaminated clothing.  
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.  
P403+P235 - Store in a well-ventilated place. Keep cool.  
P405 - Store locked up.  
P501 - Dispose of contents and container to an approved waste disposal plant.

### 2.3. Other hazards which do not result in classification

Other hazards not contributing to the classification : Vapours may form explosive mixture with air.

## SECTION 3: Composition and information on ingredients

Comments : Preparation solved in petroleum spirit.

Name	CAS-No.	%	Classification according to the model Work Health and Safety Regulations (WHS Regulations)
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 3% normal hexane	64742-49-0	≥ 75	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
Hydrocarbons, C6, iso, < 3% normal hexane (≤ 25 %)	64742-49-0	≤ 25	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
Other substances (not contributing to the classification of this product)	-	Up to 100%	-

## SECTION 4: First aid measures

### 4.1. Description of necessary first-aid measures

First-aid measures general : Take off immediately all contaminated clothing. Move the affected person away from the contaminated area. Call a poison center or a doctor if you feel unwell.

First-aid measures after inhalation : Move to fresh air in case of accidental inhalation of vapours or decomposition products. If you feel unwell, seek medical advice.

First-aid measures after skin contact : Wash off immediately with soap and plenty of water. Get medical advice if skin irritation persists.

First-aid measures after eye contact : Wash immediately with plenty water (during 20 minutes), also under eyelids. Consult an eye specialist.

First-aid measures after ingestion : Do not induce vomiting. Call a physician immediately. Do not induce vomiting without medical advice.

# TIP TOP SOLVENT LIQUID BUFFER

## Safety Data Sheet

according to the WHS Regulations  
SDS No: 00156-0008

### 4.2. Symptoms caused by exposure

Symptoms/effects after inhalation : May cause drowsiness or dizziness.  
Symptoms/effects after skin contact : May cause skin irritation.  
Symptoms/effects after ingestion : Aspiration hazard. May be fatal if swallowed and enters airways.

### 4.3. Medical attention and special treatment

Treatment : Treat symptomatically.

## SECTION 5: Fire-fighting measures

### 5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.  
Unsuitable extinguishing media : high volume water jet.

### 5.2. Specific hazards arising from the chemical

Fire hazard : Highly flammable liquid and vapour.  
Explosion hazard : Product is not explosive. Explosive vapour/air mixtures may be formed.  
General measures : In case of vapour formation use adequate respirator. Explosion free apparatus have to be used. Ensure adequate air ventilation. Avoid contact with skin, eyes and clothing.  
Hazardous decomposition products in case of fire : Carbon oxides (CO, CO<sub>2</sub>).

### 5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Fight fire from safe distance and protected location.  
Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.  
Hazchem Code : \* 3YE  
Other information : Vapours are heavier than air and may spread along floors. The vapour/air mixture is explosive, even in empty, uncleaned receptacles. Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : In case of vapour formation use adequate respirator. Explosion free apparatus have to be used. Ensure adequate air ventilation. Avoid contact with skin, eyes and clothing.

#### 6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing vapours. Avoid contact with skin and eyes.

#### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

### 6.2. Environmental precautions

Do not discharge into the drains/surface waters/groundwater.

### 6.3. Methods and materials for containment and cleaning up

For containment : Collect spillage.  
Methods for cleaning up : Soak up with inert absorbent material (for example sand, sawdust, a universal binder, silica gel). Shovel or sweep up and put in a closed container for disposal.

# TIP TOP SOLVENT LIQUID BUFFER

## Safety Data Sheet

according to the WHS Regulations  
SDS No: 00156-0008

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

- Precautions for safe handling : Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharge. Use explosion-proof equipment. Do not smoke. Vapours are heavier than air and may spread along floors. Keep container tightly closed. Avoid contact with skin, eyes and clothing.
- Hygiene measures : Do not inhale vapour. Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Apply emollient cream. Avoid contact with skin, eyes and clothing. Wash contaminated clothing before reuse.

#### 7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Pay attention to explosion protection guidelines. Ground/bond container and receiving equipment.
- Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.
- Incompatible materials : oxidizing materials.
- Information on mixed storage : Keep away from food, drink and animal feeding stuffs.

### SECTION 8: Exposure controls and personal protection

#### 8.1. Control parameters - exposure standards

No additional information available

#### 8.2. Biological Monitoring

- Monitoring methods : A specific exposure sampling method is not available.

#### 8.3. Engineering controls

- Appropriate engineering controls : Ensure good ventilation of the work station.

#### 8.4. Individual protection measures, such as personal protective equipment (PPE)

- Hand protection : Splash protection. This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions. Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves

Type	Material	Permeation	Thickness (mm)	Penetration	Standard
protective gloves	Nitrile rubber	6 (> 480 minutes)	≥0.4		EN ISO 374

Eye protection :

Type	Field of application	Characteristics	Standard
Protective goggles (EN 166)	Liquid splashes may occur		EN 166

Skin and body protection : EN 467

Type	Standard
Chemical resistant apron	EN 467

Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment

Device	Filter type	Condition	Standard
Respiratory protective device with a gas filter	Type A - High-boiling (>65 °C) organic compounds	In case of inadequate ventilation wear	EN 14387

Environmental exposure controls : Avoid release to the environment.

# TIP TOP SOLVENT LIQUID BUFFER

## Safety Data Sheet

according to the WHS Regulations  
SDS No: 00156-0008

### SECTION 9: Physical and chemical properties

Physical state	: Liquid
Appearance	: No data available
Colour	: Colourless
Odour	: Hydrocarbon-like
Odour threshold	: No data available
pH	: No data available
pH solution	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point / Freezing point	: No data available
Boiling point	: 60 – 95 °C ASTM D1078
Flash point	: -25 °C
Auto-ignition temperature	: 413 °C
Flammability	: No data available
Vapour pressure	: Vapour pressure: 150 hPa @ 20 °C
Relative density	: No data available
Density	: Density: 0.693 g/cm <sup>3</sup> @ 15 °C, DIN 51757
Solubility	: Water: 0.02 g/l @20°C
Log Pow	: 4 – 5.1 n-octanol/water
Viscosity, kinematic	: < 20.5 mm <sup>2</sup> /s @ 40 °C
Viscosity, dynamic	: 0.45 mPa·s
Explosive properties	: Product is not explosive. May form flammable/explosive vapour-air mixture.
Oxidising properties	: Non oxidizing
Explosive limits	: No data available
Minimum ignition energy	: No data available
VOC content	: 100 %
Fat solubility	: No data available
Additional information	: Solvent separation test (%) : 0

### SECTION 10: Stability and reactivity

Reactivity	: No decomposition if stored and applied as directed.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: Reactions with oxidizing agents.
Conditions to avoid	: To avoid thermal decomposition, do not overheat. Vapour/air-mixtures are explosive at intense warming. Heating can release vapours which can be ignited.
Incompatible materials	: Oxidizing agent.
Hazardous decomposition products	: No hazardous decomposition products known. Thermal decomposition generates : Carbon oxides (CO, CO <sub>2</sub> ).

### SECTION 11: Toxicological information

Acute toxicity (oral)	: Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (dermal)	: Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (inhalation)	: Not classified (Based on available data, the classification criteria are not met)

<b>Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, &lt; 3% normal hexane (64742-49-0)</b>	
LD50 oral rat	> 2000 mg/kg
LD50 dermal rat	> 2000 mg/kg
LC50 Inhalation - Rat	> 20 mg/l/4h

Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Not classified (Based on available data, the classification criteria are not met)
Respiratory or skin sensitisation	: Not classified (Based on available data, the classification criteria are not met)
Germ cell mutagenicity	: Not classified (Based on available data, the classification criteria are not met)
Carcinogenicity	: Not classified (Based on available data, the classification criteria are not met)
Reproductive toxicity	: Not classified (Based on available data, the classification criteria are not met)
STOT-single exposure	: May cause drowsiness or dizziness.

# TIP TOP SOLVENT LIQUID BUFFER

## Safety Data Sheet

according to the WHS Regulations  
SDS No: 00156-0008

STOT-repeated exposure	: Not classified (Based on available data, the classification criteria are not met)
Aspiration hazard	: May be fatal if swallowed and enters airways.
Potential adverse human health effects and symptoms	: High concentration of vapours may induce: headache, nausea, dizziness. Risk of lungs oedema.

### SECTION 12: Ecological information

#### 12.1. Ecotoxicity

Hazardous to the aquatic environment, short-term (acute)	: Not classified (Based on available data, the classification criteria are not met)
Hazardous to the aquatic environment, long-term (chronic)	: Not classified (Based on available data, the classification criteria are not met)
Other information	: Do not flush into surface water or sewer system.

#### Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 3% normal hexane (64742-49-0)

LC50 fish 1	1 – 10 mg/l
EC50 Daphnia 1	1 – 10 mg/l

#### 12.2. Persistence and degradability

<b>TIP TOP SOLVENT LIQUID BUFFER</b>	
Persistence and degradability	Readily biodegradable, according to appropriate OECD test

#### 12.3. Bioaccumulative potential

<b>TIP TOP SOLVENT LIQUID BUFFER</b>	
Log Pow	4 – 5.1 n-octanol/water
Bioaccumulative potential	No data available.
<b>Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, &lt; 3% normal hexane (64742-49-0)</b>	
Bioaccumulative potential	Potentially bioaccumulable.

#### 12.4. Mobility in soil

<b>TIP TOP SOLVENT LIQUID BUFFER</b>	
Ecology - soil	No data available.
Log Pow	4 – 5.1 n-octanol/water

#### 12.5. Other adverse effects

Ozone	: Not classified (Based on available data, the classification criteria are not met)
Other adverse effects	: No additional information available

<b>TIP TOP SOLVENT LIQUID BUFFER</b>	
Fluorinated greenhouse gases	False
<b>Hydrocarbons, C6, iso, &lt; 3% normal hexane (&lt;= 25 %) (64742-49-0)</b>	
Fluorinated greenhouse gases	False
<b>Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, &lt; 3% normal hexane (64742-49-0)</b>	
Fluorinated greenhouse gases	False

# TIP TOP SOLVENT LIQUID BUFFER

## Safety Data Sheet

according to the WHS Regulations  
SDS No: 00156-0008

### SECTION 13: Disposal considerations

- Waste treatment methods : Recycling is preferred to disposal or incineration. Can be incinerated according to local regulations. Dispose of contents/container in accordance with licensed collector's sorting instructions.
- Product/Packaging disposal recommendations : Empty containers should be taken for local recycling, recovery or waste disposal. Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse. Packaging that cannot be cleaned should be disposed of like the product.

### SECTION 14: Transport information

In accordance with ADG / IMDG / IATA

ADG	IMDG	IATA
<b>14.1. UN number</b>		
1263	1263	1263
<b>14.2. UN Proper Shipping Name</b>		
PAINT	PAINT	Paint
<b>14.3. Transport hazard class(es)</b>		
3	3	3
<b>14.4. Packing group</b>		
II - Substances presenting medium danger	II	II
<b>14.5. Environmental hazards</b>		
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No

### 14.6. Special precautions for user

- Specific storage requirement : No data available
- Shock sensitivity : No data available

### 14.7. Additional information

- Other information : No supplementary information available

### Transport by road and rail

- UN-No. (ADG) : 1263
- Special provision (ADG) : 163, 367
- Limited quantities (ADG) : 5l
- Excepted quantities (ADG) : E2
- Packing instructions (ADG) : P001, IBC02
- Special packing provisions (ADG) : PP1
- Portable tank and bulk container instructions (ADG) : T4
- Portable tank and bulk container special provisions (ADG) : TP1, TP8, TP28

### Transport by sea

- UN-No. (IMDG) : 1263
- Special provisions (IMDG) : 163, 367
- Limited quantities (IMDG) : 5 L

# TIP TOP SOLVENT LIQUID BUFFER

## Safety Data Sheet

according to the WHS Regulations  
SDS No: 00156-0008

Excepted quantities (IMDG) : E2  
Packing instructions (IMDG) : P001  
Special packing provisions (IMDG) : PP1  
IBC packing instructions (IMDG) : IBC02  
Tank instructions (IMDG) : T4  
Tank special provisions (IMDG) : TP1, TP8, TP28  
Stowage category (IMDG) : B

### Air transport

UN-No. (IATA) : 1263  
PCA Excepted quantities (IATA) : E2  
PCA Limited quantities (IATA) : Y341  
PCA limited quantity max net quantity (IATA) : 1L  
PCA packing instructions (IATA) : 353  
PCA max net quantity (IATA) : 5L  
CAO packing instructions (IATA) : 364  
CAO max net quantity (IATA) : 60L  
Special provisions (IATA) : A3, A72, A192  
ERG code (IATA) : 3L

### 14.8. Hazchem or Emergency Action Code

Hazchem Code : \* 3YE

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations

#### Australian Industrial Chemicals Introduction Scheme (AICIS)

Australian Inventory of Industrial Chemicals (AICIS Inventory) status : All the chemicals contained in this product are listed introductions

Australian Inventory of Industrial Chemicals (AICIS Inventory) status : All components of this mixture are listed on or exempted from AICIS

#### Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP)

Relevant Poisons Schedule number : Labelling requirements for SUSMP do not apply to a poison that is packed and sold solely for industrial, laboratory or manufacturing use. However, this product is labelled in accordance with the Safe Work Australia "Code of Practice" for workplace substances.

#### Australian Pesticides and Veterinary Medicines Authority (APVMA)

No additional information available

### 15.2. International agreements

No additional information available

## SECTION 16: Other information

Revision date : 24/01/2025

Classification	
Flam. Liq. 2	H225
Skin Irrit. 2	H315
STOT SE 3	H336
Asp. Tox. 1	H304

### Full text of H-statements

Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
-------------------	---

# TIP TOP SOLVENT LIQUID BUFFER

## Safety Data Sheet

according to the WHS Regulations  
SDS No: 00156-0008

Full text of H-statements	
Asp. Tox. 1	Aspiration hazard, Category 1
Flam. Liq. 2	Flammable liquids, Category 2
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis
H225	Highly flammable liquid and vapour
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H336	May cause drowsiness or dizziness
H411	Toxic to aquatic life with long lasting effects

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should therefore not be construed as guaranteeing any specific property of the product.