

## Safety Data Sheet

according to WHMIS

### TIP TOP PRIMER PR 805

Date (latest revision): 25.03.2026

Product code: 00156-0546

Page 1 of 10

## 1. Identification

### Product identifier

TIP TOP PRIMER PR 805

### Art.-No.

525 2422, 525 2431, 525 2732

### Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

Primer Coat

### Details of the supplier of the safety data sheet

Company name: REMA TIP TOP / North America Inc.  
Street: 1500 Industrial Blvd  
Place: Madison, GA 30650, USA  
Telephone: +1 800 225 7362,  
Internet: www.rematiptop.com  
Responsible Department: Responsible for the safety data sheet: sds@gbk-ingelheim.de

Emergency telephone number: (USA domestic) 1 800 535 5053 or international (001) 352 323 3500  
Infotrac/GBK GmbH-ID: 93591

## 2. Hazard identification

### Classification of the substance or mixture

#### WHMIS 2015

Flammable liquids: Category 2  
Carcinogenicity: Category 2  
Reproductive toxicity: Category 2  
Acute toxicity: Category 4 (inhalation)  
Skin corrosion/irritation: Category 2  
Serious eye damage/eye irritation: Category 2A  
Specific target organ toxicity - single exposure: Category 3 (narcotic effects) (respiratory tract irritation)  
Specific target organ toxicity - repeated exposure: Category 2  
Hazardous to the aquatic environment: Aquatic Chronic 3

### Label elements

#### WHMIS 2015

**Signal word:** Danger

**Pictograms:**



#### **Hazard statements**

Highly flammable liquid and vapour.  
Causes skin irritation and serious eye irritation.  
Harmful if inhaled.  
May cause respiratory irritation.  
May cause drowsiness or dizziness.  
Suspected of causing cancer.  
Suspected of damaging the unborn child.  
May cause damage to organs through prolonged or repeated exposure.  
Harmful to aquatic life with long lasting effects.

**Safety Data Sheet**

according to WHMIS

**TIP TOP PRIMER PR 805**

Date (latest revision): 25.03.2026

Product code: 00156-0546

Page 2 of 10

**Precautionary statements**

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
Take action to prevent static discharges.  
Wear protective gloves/protective clothing/eye protection/face protection.  
IF exposed or concerned: Get medical advice/attention.  
Store in a well-ventilated place. Keep cool.

**Other hazards**

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.  
Vapours may form explosive mixture with air.

**3. Composition/information on ingredients****Mixtures****Chemical characterization**

Preparation with polymers in xylene and 4-methylpentan-2-one

**Hazardous components**

CAS No	Chemical name	Quantity
108-10-1	4-Methylpentan-2-one	< 50 %
	Reaction mass of ethylbenzene and xylene	< 25 %
78-93-3	Butanone	< 5 %
1314-13-2	Zinc oxide	< 1 %
108-88-3	Toluene	< 1 %

**4. First-aid measures****Description of first aid measures****General information**

Remove contaminated soaked clothing immediately.  
Symptoms of poisoning may not appear for several hours. Keep under medical supervision for at least 48 hours.  
In the event of persistent symptoms receive medical treatment.  
Take away from danger area and lay down affected person.

**After inhalation**

Move to fresh air in case of accidental inhalation of vapours.  
Seek medical treatment immediately.

**After contact with skin**

Wash off with soap and plenty of water.  
Possible risk of resorption through skin.  
If a person feels unwell or symptoms of skin irritation appear, consult a physician.

**After contact with eyes**

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.  
Remove contact lenses, if present and easy to do. Continue rinsing.  
Seek medical treatment by eye specialist.

**After ingestion**

Do not induce vomiting.  
Rinse mouth.  
Never give anything by mouth to an unconscious person.  
Summon a doctor immediately.  
Induce vomiting only upon the advice of a physician.



## Safety Data Sheet

according to WHMIS

### TIP TOP PRIMER PR 805

Date (latest revision): 25.03.2026

Product code: 00156-0546

Page 3 of 10

#### Most important symptoms and effects, whether acute or delayed

- Harmful if inhaled.
- Causes skin irritation.
- Causes serious eye irritation.
- May cause respiratory irritation.
- May cause drowsiness or dizziness.
- Suspected of causing cancer.
- May cause damage to organs through prolonged or repeated exposure.
- Suspected of damaging the unborn child.

#### Indication of immediate medical attention and special treatment needed

- Treat symptoms.

## 5. Fire-fighting measures

#### Extinguishing media

##### **Suitable extinguishing media**

- Foam, carbon dioxide (CO<sub>2</sub>), dry chemical, water-spray.

##### **Unsuitable extinguishing media**

- Full water jet.

#### Specific hazards arising from the hazardous product

- Fire may produce:
  - carbon monoxide and carbon dioxide
  - Hydrogen chloride (HCl)

#### Special protective equipment and precautions for fire-fighters

- Use breathing apparatus with independent air supply.
- Protective suit.

#### **Additional information**

- Vapours are heavier than air and spread along ground.
- The vapour/air mixture is explosive, even in empty, uncleaned receptacles.
- Cool containers at risk with water spray jet.
- Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

## 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

##### **General advice**

- Ensure adequate ventilation.
- Remove persons to safety.

##### **For non-emergency personnel**

- Do not breathe vapours.
- Avoid contact with skin, eyes and clothing.

##### **For emergency responders**

- In case of vapour formation use respirator.
- Use personal protective clothing.

#### Environmental precautions

- Do not discharge into the drains/surface waters/groundwater.
- Clean contaminated surface thoroughly.

#### Methods and material for containment and cleaning up

##### **For containment**

- Prevent spread over a wide area (e.g. by containment or oil barriers).

##### **For cleaning up**

- Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder).



## Safety Data Sheet

according to WHMIS

### TIP TOP PRIMER PR 805

Date (latest revision): 25.03.2026

Product code: 00156-0546

Page 4 of 10

Shovel into suitable container for disposal.

#### Reference to other sections

Observe protective instructions (see Sections 7 and 8).  
Information for disposal look up chapter 13.

## 7. Handling and storage

### Precautions for safe handling

#### **Advice on safe handling**

Do not wear contact lenses when handling the product.  
Keep container tightly closed.  
Vapours are heavier than air and spread along ground.  
Keep a good ventilation and air-exhaust at the place of work.  
Avoid contact with skin, eyes and clothing.

#### **Advice on protection against fire and explosion**

Keep away from heat and sources of ignition.  
Do not smoke.  
Take precautionary measures against static discharges.  
Pay attention to anti-explosion protection rules: In case of an explosive atmosphere use only explosion-proof equipment.

#### **Advice on general occupational hygiene**

Do not inhale vapours.  
Wash hands before breaks and immediately after handling the product.  
When using do not eat, drink or smoke.  
Avoid contact with skin, eyes and clothing.  
Remove and wash contaminated clothes before re-use.

### Conditions for safe storage, including any incompatibilities

#### **Requirements for storage rooms and vessels**

Keep container tightly closed in a dry, cool and well-ventilated place.  
Pay attention to anti-explosion rules.

#### **Hints on joint storage**

Incompatible with oxidizing agents.

#### **Further information on storage conditions**

Keep away from food, drink and animal feeding stuffs.

## 8. Exposure controls/Personal protection

### Control parameters

**Safety Data Sheet**

according to WHMIS

**TIP TOP PRIMER PR 805**

Date (latest revision): 25.03.2026

Product code: 00156-0546

Page 5 of 10

**Exposure limits (ACGIH)**

CAS No	Chemical name	ppm	mg/m <sup>3</sup>	F/ml	Category	Origin
100-41-4	Ethyl benzene	20	-		TWA (8 h)	ACGIH-2025
78-93-3	Methyl ethyl ketone	75			TWA (8 h)	ACGIH-2025
		150			STEL (15 min)	ACGIH-2025
13463-67-7	Titanium dioxide: Finescale particles (Respirable particulate matter)	-	2.5		TWA (8 h)	ACGIH-2025
108-88-3	Toluene	20	-		TWA (8 h)	ACGIH-2025
-	Wood dusts (inhalable fraction): All other species/All other wood dusts		1		TWA (8 h)	ACGIH-2025
1330-20-7	Xylene: mixed isomers	20			TWA (8 h)	ACGIH-2025
1314-13-2	Zinc oxide (respirable fraction)		2		TWA (8 h)	ACGIH-2025
			10		STEL (15 min)	ACGIH-2025

**Biological limit values**

CAS No	Chemical name	Parameter	Value	Test material	Sampling time
108-10-1	METHYL ISOBUTYL KETONE (ACGIH 2025)	Methyl isobutyl ketone	1 mg/L	urine	End of shift
78-93-3	METHYL ETHYL KETONE (ACGIH 2025)	Methyl ethyl ketone	2 mg/L	urine	End of shift
108-88-3	TOLUENE (ACGIH 2025)	Toluene	0.02 mg/L	blood	Prior to last shift of workweek
100-41-4	Ethyl benzene (ACGIH 2025)	Sum of mandelic acid and phenylglyoxylic acid (creatinine)	0.15 g/g	urine	End of shift

**Exposure controls****Appropriate engineering controls**

Ensure adequate ventilation, especially in confined areas.

**Individual protection measures, such as personal protective equipment****Eye/face protection**

Tightly fitting goggles.

Eye wash bottle with pure water.

**Hand protection**

Splash protection:

Protective gloves resistant to chemicals made of butyl, Minimum coat thickness 0,7 mm, Permeation resistance (wear duration) > 240 minutes, i.e. protective glove <Butoject 898> made by www.kcl.de.

This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.

Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

**Skin protection**

Solvent-resistant apron.

**Respiratory protection**

In case of insufficient ventilation wear suitable respiratory equipment (gas filter type A).

**9. Physical and chemical properties****Information on basic physical and chemical properties**

Physical state:

Liquid

**Safety Data Sheet**

according to WHMIS

**TIP TOP PRIMER PR 805**

Date (latest revision): 25.03.2026

Product code: 00156-0546

Page 6 of 10

Colour: Grey  
Odour: Aromatic

**Test method****Changes in the physical state**

Melting point/freezing point: n. d.  
Boiling point or initial boiling point and boiling range: n. d.  
Sublimation point: n.a.  
Softening point: n. d.  
Pour point: n. d.  
Flash point: 15 °C

**Flammability**

Solid/liquid: n.a.

**Explosive properties**

The product is considered non-explosive; nevertheless explosive vapour/air mixture can be generated.

Lower explosive limits: 1,4 vol. % (\*)  
Upper explosive limits: 7,5 vol. % (\*)  
Auto-ignition temperature: n. d.

**Self-ignition temperature**

Solid: n.a.  
Gas: n.a.

Decomposition temperature: n. d.

pH-Value: n. d.

Viscosity / dynamic: 10 - 300 mPa·s

Viscosity / kinematic:  
(at 40 °C) > 20,5 mm<sup>2</sup>/s

Flow time: n. d.

Water solubility:  
(at 20 °C) Immiscible

**Solubility in other solvents**

n. d.

Partition coefficient n-octanol/water: n. d.

Vapour pressure:  
(at 20 °C) n. d.

Density (at 20 °C): 0,87 - 0,92 g/cm<sup>3</sup>

Bulk density: n.a.

Relative vapour density: n. d.

**Other information****Information with regard to physical hazard classes**

Sustained combustibility: Sustained combustibility

Oxidizing properties  
Not oxidising.

**Other safety characteristics**

Solvent separation test: n. d.

Solvent content: < 75 %

Evaporation rate: n. d.

**Safety Data Sheet**

according to WHMIS

**TIP TOP PRIMER PR 805**

Date (latest revision): 25.03.2026

Product code: 00156-0546

Page 7 of 10

**Further Information**

(\*) 4-Methylpentan-2-one

**10. Stability and reactivity****Reactivity**

No decomposition if stored and applied as directed.

**Chemical stability**

Stable under normal conditions.

**Possibility of hazardous reactions**

Reactions with oxidizing agents.

**Conditions to avoid**

To avoid thermal decomposition, do not overheat.  
Vapour/air mixtures are explosive at intensive warming.  
Heating can release vapours which can be ignited.

**Incompatible materials**

Strong oxidizing agents

**Hazardous decomposition products**

No hazardous decomposition products known.  
Fire may produce:  
Carbon monoxide and carbon dioxide  
Hydrogen chloride (HCl)

**11. Toxicological information****Information on toxicological effects****Acute toxicity**

Harmful if inhaled.  
No toxicological data available.

**ATEmix calculated**

ATE (oral) &gt; 2000 mg/kg; ATE (dermal) &gt; 2000 mg/kg

**Irritation and corrosivity**

Skin corrosion/irritation: Causes skin irritation.  
Serious eye damage/eye irritation: Causes serious eye irritation.

**Sensitizing effects**

Based on available data, the classification criteria are not met.

**Carcinogenic/mutagenic/toxic effects for reproduction**

Suspected of causing cancer. (4-Methylpentan-2-one)  
Suspected of damaging the unborn child. (Toluene)  
Germ cell mutagenicity: Based on available data, the classification criteria are not met.

**STOT-single exposure**

May cause respiratory irritation. (4-Methylpentan-2-one; Reaction mass of ethylbenzene and xylene)  
May cause drowsiness or dizziness. (4-Methylpentan-2-one)

**STOT-repeated exposure**

May cause damage to organs through prolonged or repeated exposure. (Reaction mass of ethylbenzene and xylene)

**Aspiration hazard**

Based on available data, the classification criteria are not met.

**Practical experience**

Classification in compliance with the assessment procedure specified in the Regulation (EC) no 1272/2008.

**Safety Data Sheet**

according to WHMIS

**TIP TOP PRIMER PR 805**

Date (latest revision): 25.03.2026

Product code: 00156-0546

Page 8 of 10

**Information on other hazards****Endocrine disrupting properties**

No data available

**Other information**

Inhalation of vapours is irritating to the respiratory system, may cause throat pain and cough.

Repeated exposure may cause skin dryness or cracking.

Possible risk of resorption through skin.

Inhalation of high vapour concentration may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

Inhalation of vapours is irritating to the respiratory system, may cause throat pain and cough.

May cause irritation of the mucous membranes.

**12. Ecological information****Ecotoxicity**

Ecological data are not available.

Harmful to aquatic life with long lasting effects.

Zinc oxide

EC50/Selenastrum capricornutum/72 h = 0,17 mg/l

4-Methylpentan-2-one

LC50/Pimephales promelas/96 h = 505 - 540 mg/l

EC50/Daphnia magna/48 h = 170 mg/l

EC50/Selenastrum capricornutum/72 h = 170 mg/l

Toluene

LC50/Carassius Auratus/96 h = 13 mg/l

EC50/algae/72 h = 12,5 mg/l [OECD 201]

Ethyl benzene

ErC50/algae/96 h = 3,6 mg/l

**Persistence and degradability**

No data available

**Bioaccumulative potential**

No data available

**Mobility in soil**

No data available

**Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

**Other adverse effects**

Hazardous water pollutant.

**Further information**

Do not flush into surface water or sanitary sewer system.

**13. Disposal considerations****Waste treatment methods****Disposal recommendations**

Where possible recycling is preferred to disposal.

Can be incinerated, when in compliance with local regulations.

**Contaminated packaging**

Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.

Packaging that cannot be cleaned should be disposed of like the product.

Empty containers should be taken for local recycling, recovery or waste disposal.

**Safety Data Sheet**

according to WHMIS

**TIP TOP PRIMER PR 805**

Date (latest revision): 25.03.2026

Product code: 00156-0546

Page 9 of 10

**14. Transport information****Canadian TDG**

**UN number:** UN 1263  
**Proper shipping name:** Paint  
**Hazard classes:** 3  
**Packing group:** II  
Hazard label: 3  
Limited quantity: 5L

**Marine transport (IMDG)**

**UN number or ID number:** UN 1263  
**United Nations proper shipping name:** Paint  
**Transport hazard class(es):** 3  
**Packing group:** II  
Hazard label: 3



Marine pollutant: No  
Limited quantity: 5 L / 30 kg  
Excepted quantity: E2  
EmS: F-E, S-E

**Air transport (ICAO-TI/IATA-DGR)**

**UN number or ID number:** UN 1263  
**United Nations proper shipping name:** Paint  
**Transport hazard class(es):** 3  
**Packing group:** II  
Hazard label: 3



Limited quantity Passenger: 1 L  
Passenger LQ: Y341  
Excepted quantity: E2  
IATA-packing instructions - Passenger: 353  
IATA-max. quantity - Passenger: 5 L  
IATA-packing instructions - Cargo: 364  
IATA-max. quantity - Cargo: 60 L

**Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: No

**15. Regulatory information****Canadian regulations**



## Safety Data Sheet

according to WHMIS

### TIP TOP PRIMER PR 805

Date (latest revision): 25.03.2026

Product code: 00156-0546

Page 10 of 10

#### DSL/NDSL inventory status

All components are listed on the DSL Inventory.

#### National Pollutant Release Inventory (NPRI)

4-Methylpentan-2-one, Xylene, Ethyl benzene, Phenol, Toluene, Zinc oxide

## 16. Other information

#### Changes

This data sheet contains changes from the previous version in section(s): 1,2,4,9,11,12.

#### Abbreviations and acronyms

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route

RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses

ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure

IMDG = International Maritime Code for Dangerous Goods

IATA/ICAO = International Air Transport Association / International Civil Aviation Organization

MARPOL = International Convention for the Prevention of Pollution from Ships

IBC-Code = International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

REACH = Registration, Evaluation, Authorization and Restriction of Chemicals

CAS = Chemical Abstract Service

EN = European norm

ISO = International Organization for Standardization

DIN = Deutsche Industrie Norm

PBT = Persistent Bioaccumulative and Toxic

vPvB = Very Persistent and very Bio-accumulative

LD = Lethal dose

LC = Lethal concentration

EC = Effect concentration

IC = Median immobilisation concentration or median inhibitory concentration

#### Further Information

Data of sections 4 to 8, as well as 10 to 12, do not necessarily refer to the use and the regular handling of the product (in this sense consult package leaflet and expert information), but to release of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product (s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

(n.a. = not applicable; n.d. = not determined)

*(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*