

**Safety Data Sheet**

according to UK REACH Regulation

**TIP TOP ADHESIVE TC 5002**

Revision date: 30.11.2023

Product code: 00359-1244

Page 1 of 12

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

TIP TOP ADHESIVE TC 5002

**Art.-No.**

525 2790, 525 2800, 525 2810

**1.2. Relevant identified uses of the substance or mixture and uses advised against****Use of the substance/mixture**

adhesive

**1.3. Details of the supplier of the safety data sheet****Manufacturer**

Company name: TIP TOP Oberflächenschutz Elbe GmbH  
Street: Heuweg 4  
Place: D-06886 Wittenberg  
Telephone: +49(0)3491/635-50  
Responsible Department: Responsible for the safety data sheet: sds@gbk-ingelheim.de

Telefax:

**Supplier**

Company name: REMA TIP TOP INDUSTRY UK LTD  
Street: Plumtree Industrial Estate, Harworth  
Place: Doncaster, DN11 8EW, South Yorkshire  
Telephone: +44 (0)1302 711233  
Internet: www.rema-tiptop.co.uk

**1.4. Emergency telephone number:**

INTERNATIONAL: +49 - (0) 6132 - 84463, GBK GmbH (24h - 7d/w - 365d/a)  
In England and Wales: NHS 111 In Scotland: NHS 24 - dial 111

**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****GB CLP Regulation**

Flam. Liq. 3; H226  
Acute Tox. 4; H312  
Acute Tox. 4; H332  
Skin Irrit. 2; H315  
Eye Irrit. 2; H319  
Repr. 1A; H360D  
STOT SE 3; H335  
STOT RE 2; H373  
Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

**2.2. Label elements****GB CLP Regulation****Hazard components for labelling**

Reaction mass of ethylbenzene and xylene  
Phenol, 4-(1,1-dimethylethyl)-, polymer with ethyne

**Signal word:** Danger

## Safety Data Sheet

according to UK REACH Regulation

### TIP TOP ADHESIVE TC 5002

Revision date: 30.11.2023

Product code: 00359-1244

Page 2 of 12

#### Pictograms:



#### Hazard statements

H226	Flammable liquid and vapour.
H312+H332	Harmful in contact with skin or if inhaled.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H360D	May damage the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.

#### Precautionary statements

P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260	Do not breathe vapour.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312	Call a POISON CENTER/doctor if you feel unwell.
P273	Avoid release to the environment.

#### Special labelling of certain mixtures

Restricted to professional users.

#### 2.3. Other hazards

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605

Vapours may form explosive mixture with air.

### SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

##### Chemical characterization

Preparation in xylene

**Safety Data Sheet**

according to UK REACH Regulation

**TIP TOP ADHESIVE TC 5002**

Revision date: 30.11.2023

Product code: 00359-1244

Page 3 of 12

**Hazardous components**

CAS No	Chemical name	Quantity		
	EC No	Index No	REACH No	
	GHS Classification			
	Reaction mass of ethylbenzene and xylene			< 70 %
	905-588-0		01-2119488216-32	
	Flam. Liq. 3, Acute Tox. 4, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, STOT SE 3, STOT RE 2, Asp. Tox. 1; H226 H332 H312 H315 H319 H335 H373 H304			
103-50-4	dibenzylether			< 1 %
	203-118-2		01-2119782240-44	
	Aquatic Chronic 1; H410			
1314-13-2	Zinc oxide			< 1 %
	215-222-5	030-013-00-7	01-2119463881-32	
	Aquatic Acute 1, Aquatic Chronic 1; H400 H410			
28514-92-3	Phenol, 4-(1,1-dimethylethyl)-, polymer with ethyne			< 1 %
	Repr. 1B; H360D			

Full text of H and EUH statements: see section 16.

**Specific Conc. Limits, M-factors and ATE**

CAS No	EC No	Chemical name	Quantity	
	Specific Conc. Limits, M-factors and ATE			
	905-588-0	Reaction mass of ethylbenzene and xylene	< 70 %	
	inhalation: ATE = 11 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: ATE = 1100 mg/kg STOT RE 2; H373: >= 10 - 100			
103-50-4	203-118-2	dibenzylether	< 1 %	
	oral: LD50 = > 4000 mg/kg			
1314-13-2	215-222-5	Zinc oxide	< 1 %	
	Aquatic Acute 1; H400: M=1 Aquatic Chronic 1; H410: M=1			

**SECTION 4: First aid measures****4.1. Description of first aid measures****General information**

- Remove contaminated soaked clothing immediately.
- In the event of persistent symptoms receive medical treatment.
- Take away from danger area and lay down affected person.

**After inhalation**

- Move to fresh air in case of accidental inhalation of vapours.
- In the event of symptoms refer for medical treatment.

**After contact with skin**

- Wash off immediately with soap and plenty of water.
- Consult a doctor if skin irritation persists.

**After contact with eyes**

- Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.
- Consult (eye) doctor immediately.

**After ingestion**

- Do not induce vomiting.
- Rinse out mouth and give plenty of water to drink.



## Safety Data Sheet

according to UK REACH Regulation

### TIP TOP ADHESIVE TC 5002

Revision date: 30.11.2023

Product code: 00359-1244

Page 4 of 12

Never give anything by mouth to an unconscious person.  
Summon a doctor immediately.  
The decision whether to induce vomiting or not is to be taken by a physician.

#### **4.2. Most important symptoms and effects, both acute and delayed**

Harmful in contact with skin or if inhaled.  
Causes skin irritation.  
Causes serious eye irritation.  
May cause respiratory irritation.  
May damage the unborn child.  
May cause damage to organs through prolonged or repeated exposure.

#### **4.3. Indication of any immediate medical attention and special treatment needed**

Treat symptoms.

### SECTION 5: Firefighting measures

#### **5.1. Extinguishing media**

##### **Suitable extinguishing media**

Foam, carbon dioxide (CO<sub>2</sub>), dry chemical, water-spray.

##### **Unsuitable extinguishing media**

Full water jet

#### **5.2. Special hazards arising from the substance or mixture**

Fire may produce:  
Carbon monoxide (CO), carbon dioxide (CO<sub>2</sub>) and sulphur oxides (SO<sub>x</sub>)  
Bromine compounds

#### **5.3. Advice for firefighters**

Use breathing apparatus with independent air supply.  
Protective suit.

#### **Additional information**

Vapours are heavier than air and spread along ground.  
The vapour/air mixture is explosive, even in empty, uncleaned receptacles.  
Cool containers at risk with water spray jet.  
Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

### SECTION 6: Accidental release measures

#### **6.1. Personal precautions, protective equipment and emergency procedures**

##### **General advice**

Ensure adequate ventilation.  
Keep away sources of ignition.  
Keep away noninvolved persons.

##### **For non-emergency personnel**

Avoid contact with skin, eyes and clothing.  
Do not breathe vapours.

##### **For emergency responders**

In case of vapour formation use respirator.  
Use personal protective clothing.

#### **6.2. Environmental precautions**

Do not discharge into the drains/surface waters/ground water.  
Do not discharge into the subsoil/soil.

#### **6.3. Methods and material for containment and cleaning up**

##### **For containment**

Prevent spread over a wide area (e.g. by containment or oil barriers).

**Safety Data Sheet**

according to UK REACH Regulation

**TIP TOP ADHESIVE TC 5002**

Revision date: 30.11.2023

Product code: 00359-1244

Page 5 of 12

**For cleaning up**

- Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder).
- Shovel into suitable container for disposal.
- Clean contaminated surface thoroughly.

**6.4. Reference to other sections**

- Observe protective instructions (see Sections 7 and 8).
- Information for disposal see section 13.

**SECTION 7: Handling and storage****7.1. Precautions for safe handling****Advice on safe handling**

- Keep container tightly closed.
- Use only in area provided with appropriate exhaust ventilation.
- In case of insufficient ventilation wear suitable respiratory equipment (gas filter type A) (EN 14387).

**Advice on protection against fire and explosion**

- Keep product and empty container away from heat and sources of ignition.
- Pay attention to anti-explosion rules.
- Do not smoke.
- Take precautionary measures against static discharges.

**7.2. Conditions for safe storage, including any incompatibilities****Requirements for storage rooms and vessels**

- Keep containers tightly closed in a cool, well-ventilated place.
- Keep away from heat and sources of ignition.

**Hints on joint storage**

- Incompatible with oxidizing agents.

**Further information on storage conditions**

- Keep away from food, drink and animal feeding stuffs.

**7.3. Specific end use(s)**

adhesive

**SECTION 8: Exposure controls/personal protection****8.1. Control parameters****Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
1333-86-4	Carbon black	-	3.5		TWA (8 h)	WEL
		-	7		STEL (15 min)	WEL
100-41-4	Ethylbenzene	100	441		TWA (8 h)	WEL
		125	552		STEL (15 min)	WEL
1330-20-7	Xylene: mixed isomers	50	220		TWA (8 h)	WEL
		100	441		STEL (15 min)	WEL

**8.2. Exposure controls****Appropriate engineering controls**

- Ensure adequate ventilation, especially in confined areas.
- Pay attention to explosion protection guidelines.

**Protective and hygiene measures**

- Do not inhale vapours.

**Safety Data Sheet**

according to UK REACH Regulation

**TIP TOP ADHESIVE TC 5002**

Revision date: 30.11.2023

Product code: 00359-1244

Page 6 of 12

Avoid contact with eyes and skin.  
Wash hands before breaks and immediately after handling the product.  
When using do not eat, drink or smoke.  
Remove and wash contaminated clothes before re-use.

**Eye/face protection**

Tightly fitting goggles (EN 166).  
Eye wash bottle with pure water (EN 15154).

**Hand protection**

Protective gloves resistant to chemicals made off viton, minimum coat thickness 0.7 mm, permeation resistance (wear duration) approx. 480 minutes, i.e. protective glove <Vitoject 890> made by www.kcl.de. This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.  
Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

**Skin protection**

Long sleeved clothing (DIN EN ISO 6530)

**Respiratory protection**

In case of insufficient ventilation wear suitable respiratory equipment (gas filter type A) (EN 14387).

**SECTION 9: Physical and chemical properties****9.1. Information on basic physical and chemical properties**

Physical state: Viscous liquid  
Colour: Black  
Odour: Aromatic

**Test method**

pH-Value: n.d.

**Changes in the physical state**

Melting point/freezing point: - 25 °C (\*)  
Boiling point or initial boiling point and boiling range: 136 - 145 °C (\*)  
Sublimation point: n.a.  
Softening point: n.d.  
Flash point: 24 °C (\*)  
Sustaining combustion: Sustaining combustion

**Flammability**

Solid/liquid: n.a.

**Explosive properties**

The product is considered non-explosive; nevertheless explosive vapour/air mixture can be generated.

Lower explosion limits: 1,0 vol. % (\*)  
Upper explosion limits: 7,0 vol. % (\*)  
Auto-ignition temperature: approx. 460 °C (\*)

**Self-ignition temperature**

Solid: n.a.  
Gas: n.a.

Decomposition temperature: n.d.

**Oxidizing properties**

Not oxidising.

**Safety Data Sheet**

according to UK REACH Regulation

**TIP TOP ADHESIVE TC 5002**

Revision date: 30.11.2023

Product code: 00359-1244

Page 7 of 12

Vapour pressure: (at 20 °C)	8 hPa (*)
Vapour pressure: (at 50 °C)	45 hPa DIN 51754
Density (at 20 °C):	0,92 g/cm <sup>3</sup>
Bulk density:	n.a.
Water solubility:	Immiscible
<b>Solubility in other solvents</b> n.d.	
Partition coefficient n-octanol/water:	n.d.
Viscosity / dynamic:	2000 mPa·s
Viscosity / kinematic: (at 40 °C)	> 20,5 mm <sup>2</sup> /s
Flow time:	n.d.
Relative vapour density:	n.d.
Evaporation rate:	n.d.
Solvent separation test:	n.d.
Solvent content:	< 75 %

**9.2. Other information**

\*) Xylene (mixed isomers)

**SECTION 10: Stability and reactivity****10.1. Reactivity**

No decomposition if stored and applied as directed.

**10.2. Chemical stability**

Stable under normal conditions.

**10.3. Possibility of hazardous reactions**

Reactions with oxidizing agents.

**10.4. Conditions to avoid**To avoid thermal decomposition, do not overheat.  
Vapours may form explosive mixture with air.**10.5. Incompatible materials**

Strong oxidizing agents

**10.6. Hazardous decomposition products**No hazardous decomposition products known.  
Fire may produce:  
Carbon monoxide, carbon dioxide, sulphur oxides.  
bromine compounds**SECTION 11: Toxicological information****11.1. Information on hazard classes as defined in GB CLP Regulation****Acute toxicity**Harmful in contact with skin.  
Harmful if inhaled.  
No toxicological data available.



## Safety Data Sheet

according to UK REACH Regulation

### TIP TOP ADHESIVE TC 5002

Revision date: 30.11.2023

Product code: 00359-1244

Page 8 of 12

**ATEmix calculated**

ATE (oral) > 2000 mg/kg; ATE (dermal) 1558 mg/kg; ATE (inhalation vapour) 15,58 mg/l; ATE (inhalation dust/mist) 2,125 mg/l

**Irritation and corrosivity**

Causes skin irritation.  
Causes serious eye irritation.

**Sensitising effects**

Based on available data, the classification criteria are not met.

**Carcinogenic/mutagenic/toxic effects for reproduction**

May damage the unborn child. (Phenol, 4-(1,1-dimethylethyl)-, polymer with ethyne)  
Germ cell mutagenicity: Based on available data, the classification criteria are not met.  
Carcinogenicity: Based on available data, the classification criteria are not met.

**STOT-single exposure**

May cause respiratory irritation. (Reaction mass of ethylbenzene and xylene)

**STOT-repeated exposure**

May cause damage to organs through prolonged or repeated exposure. (Reaction mass of ethylbenzene and xylene)

**Aspiration hazard**

Based on available data, the classification criteria are not met.

**Additional information on tests**

Classification in compliance with the assessment procedure specified in the Regulation (EC) no 1272/2008.

**11.2. Information on other hazards****Endocrine disrupting properties**

No data available

**Other information**

Inhalation of vapours in high concentration can cause narcotic effects.  
Inhalation of high vapour concentration may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.  
Repeated or prolonged exposure may cause skin irritation and dermatitis, due to degreasing properties of the product.

**SECTION 12: Ecological information****12.1. Toxicity**

Ecological data are not available.  
Harmful to aquatic life with long lasting effects.

**12.2. Persistence and degradability**

No data available

**12.3. Bioaccumulative potential**

No data available

**12.4. Mobility in soil**

No data available

**12.5. Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

**12.6. Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

**12.7. Other adverse effects**

Hazardous water pollutant.

**Further information**

Do not flush into surface water or sanitary sewer system.

## Safety Data Sheet

according to UK REACH Regulation

### TIP TOP ADHESIVE TC 5002

Revision date: 30.11.2023

Product code: 00359-1244

Page 9 of 12

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

#### Disposal recommendations

Where possible recycling is preferred to disposal.  
Can be incinerated, when in compliance with local regulations.

#### List of Wastes Code - residues/unused products

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

#### Contaminated packaging

Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.  
Packaging that cannot be cleaned should be disposed of like the product.  
Empty containers should be taken for local recycling, recovery or waste disposal.

## SECTION 14: Transport information

### Land transport (ADR/RID)

<b>14.1. UN number:</b>	UN 1133
<b>14.2. UN proper shipping name:</b>	Adhesives
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	III
Hazard label:	3



Classification code:	F1
Limited quantity:	5 L / 30 kg
Excepted quantity:	E1
Transport category:	3
Hazard No:	30
Tunnel restriction code:	D/E

### Inland waterways transport (ADN)

<b>14.1. UN number:</b>	UN 1133
<b>14.2. UN proper shipping name:</b>	Adhesives
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	III
Hazard label:	3



Classification code:	F1
Limited quantity:	5 L / 30 kg
Excepted quantity:	E1

### Marine transport (IMDG)

<b>14.1. UN number:</b>	UN 1133
-------------------------	---------

## Safety Data Sheet

according to UK REACH Regulation

### TIP TOP ADHESIVE TC 5002

Revision date: 30.11.2023

Product code: 00359-1244

Page 10 of 12

**14.2. UN proper shipping name:** Adhesives  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** III  
Hazard label: 3



Marine pollutant: No  
Limited quantity: 5 L / 30 kg  
Excepted quantity: E1  
EmS: F-E, S-D

#### Air transport (ICAO-TI/IATA-DGR)

**14.1. UN number:** UN 1133  
**14.2. UN proper shipping name:** Adhesives  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** III  
Hazard label: 3



Limited quantity Passenger: 10 L  
Passenger LQ: Y344  
Excepted quantity: E1  
IATA-packing instructions - Passenger: 355  
IATA-max. quantity - Passenger: 60 L  
IATA-packing instructions - Cargo: 366  
IATA-max. quantity - Cargo: 220 L

#### 14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

#### 14.6. Special precautions for user

Handle in accordance with good industrial hygiene and safety practice.

#### 14.7. Maritime transport in bulk according to IMO instruments

The transport takes place only in approved and appropriate packaging.

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

##### EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

Directive 2004/42/EC on VOC in  
paints and varnishes: < 75 %

Information according to Directive  
2012/18/EU (SEVESO III): P5c FLAMMABLE LIQUIDS

##### National regulatory information



## Safety Data Sheet

according to UK REACH Regulation

### TIP TOP ADHESIVE TC 5002

Revision date: 30.11.2023

Product code: 00359-1244

Page 11 of 12

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water hazard class (D): 2 - obviously hazardous to water

#### 15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

### SECTION 16: Other information

#### Changes

This data sheet contains changes from the previous version in section(s): 2.

#### Abbreviations and acronyms

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route  
RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses  
ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure  
IMDG = International Maritime Code for Dangerous Goods  
IATA/ICAO = International Air Transport Association / International Civil Aviation Organization  
MARPOL = International Convention for the Prevention of Pollution from Ships  
IBC-Code = International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk

GHS = Globally Harmonized System of Classification and Labelling of Chemicals  
REACH = Registration, Evaluation, Authorization and Restriction of Chemicals  
CAS = Chemical Abstract Service  
EN = European norm  
ISO = International Organization for Standardization  
DIN = Deutsche Industrie Norm  
PBT = Persistent Bioaccumulative and Toxic  
vPvB = Very Persistent and very Bio-accumulative  
LD = Lethal dose  
LC = Lethal concentration  
EC = Effect concentration  
IC = Median immobilisation concentration or median inhibitory concentration

#### Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Flam. Liq. 3; H226	On basis of test data
Acute Tox. 4; H312	Calculation method
Acute Tox. 4; H332	Calculation method
Skin Irrit. 2; H315	Calculation method
Eye Irrit. 2; H319	Calculation method
Repr. 1A; H360D	Calculation method
STOT SE 3; H335	Calculation method
STOT RE 2; H373	Calculation method
Aquatic Chronic 3; H412	Calculation method

#### Relevant H and EUH statements (number and full text)

H226 Flammable liquid and vapour.  
H304 May be fatal if swallowed and enters airways.  
H312 Harmful in contact with skin.  
H312+H332 Harmful in contact with skin or if inhaled.

**Safety Data Sheet**

according to UK REACH Regulation

**TIP TOP ADHESIVE TC 5002**

Revision date: 30.11.2023

Product code: 00359-1244

Page 12 of 12

H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H360D	May damage the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

**Further Information**

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product(s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

(n.a. = not applicable; n.d. = not determined)

---

*(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*