

**Safety Data Sheet**

according to UK REACH Regulation

Asplit® CN 916 Solution

Revision date: 06.12.2023

Product code: 00359-1164

Page 1 of 12

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Asplit® CN 916 Solution

Art.-No.

592 0040, 592 0041, 592 0042

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

Mortar

1.3. Details of the supplier of the safety data sheet**Manufacturer**

Company name: TIP TOP Oberflächenschutz Elbe GmbH
Street: Heuweg 4
Place: D-06886 Wittenberg
Telephone: +49(0)3491/635-50
Responsible Department: Responsible for the safety data sheet: sds@gbk-ingelheim.de

Telefax:

Supplier

Company name: REMA TIP TOP INDUSTRY UK LTD
Street: Plumtree Industrial Estate, Harworth
Place: Doncaster, DN11 8EW, South Yorkshire
Telephone: +44 (0)1302 711233
Internet: www.rema-tiptop.co.uk

1.4. Emergency telephone number:

INTERNATIONAL: +49 - (0) 6132 - 84463, GBK GmbH (24h - 7d/w - 365d/a)
In England and Wales: NHS 111 In Scotland: NHS 24 - dial 111

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****GB CLP Regulation**

Hazard categories:

Flammable liquids: Flam. Liq. 3

Acute toxicity: Acute Tox. 4

Skin corrosion/irritation: Skin Corr. 1B

Serious eye damage/eye irritation: Eye Dam. 1

Respiratory or skin sensitisation: Skin Sens. 1A

Germ cell mutagenicity: Muta. 2

Carcinogenicity: Carc. 1B

Hazardous to the aquatic environment: Aquatic Chronic 3

Hazard Statements:

Flammable liquid and vapour.

Harmful if swallowed.

Causes severe skin burns and eye damage.

May cause an allergic skin reaction.

Suspected of causing genetic defects.

May cause cancer.

Harmful to aquatic life with long lasting effects.

2.2. Label elements**GB CLP Regulation**

Safety Data Sheet

according to UK REACH Regulation

Asplit® CN 916 Solution

Revision date: 06.12.2023

Product code: 00359-1164

Page 2 of 12

Hazard components for labelling

Phenol
Furfuryl alcohol
formaldehyde
N-(3-(trimethoxysilyl)propyl)ethylenediamine

Signal word: Danger

Pictograms:



Hazard statements

H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H341	Suspected of causing genetic defects.
H350	May cause cancer.
H412	Harmful to aquatic life with long lasting effects.

Precautionary statements

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260	Do not breathe vapour.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P405	Store locked up.

Special labelling of certain mixtures

Restricted to professional users.

2.3. Other hazards

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605

Vapours may form explosive mixture with air.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Mixture containing following substances with additives

**Safety Data Sheet**

according to UK REACH Regulation

Asplit® CN 916 Solution

Revision date: 06.12.2023

Product code: 00359-1164

Page 3 of 12

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	GHS Classification			
64-17-5	Ethanol			< 10 %
	200-578-6	603-002-00-5	01-2119457610-43	
	Flam. Liq. 2, Eye Irrit. 2; H225 H319			
108-95-2	Phenol			< 5 %
	203-632-7	604-001-00-2	01-2119471329-32	
	Muta. 2, Acute Tox. 3, Acute Tox. 3, Acute Tox. 3, Skin Corr. 1B, STOT RE 2, Aquatic Chronic 2; H341 H331 H311 H301 H314 H373 H411			
98-00-0	Furfuryl alcohol			< 5 %
	202-626-1	603-018-00-2	01-2119493965-18	
	Carc. 2, Acute Tox. 3, Acute Tox. 4, Acute Tox. 4, Eye Irrit. 2, STOT SE 3, STOT RE 2; H351 H331 H312 H302 H319 H335 H373			
50-00-0	formaldehyde			< 0,5 %
	200-001-8	605-001-00-5	01-2119488953-20	
	Carc. 1B, Muta. 2, Acute Tox. 3, Acute Tox. 3, Acute Tox. 3, Skin Corr. 1B, Skin Sens. 1A; H350 H341 H331 H311 H301 H314 H317			
1760-24-3	N-(3-(trimethoxysilyl)propyl)ethylenediamine			~ 0,1 %
	217-164-6		01-2119970215-39	
	Eye Dam. 1, Skin Sens. 1; H318 H317			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
64-17-5	200-578-6	Ethanol	< 10 %
	Eye Irrit. 2; H319: >= 50 - 100		
108-95-2	203-632-7	Phenol	< 5 %
	inhalation: ATE = 3 mg/l (vapours); inhalation: ATE = 0,5 mg/l (dusts or mists); dermal: ATE = 300 mg/kg; oral: ATE = 100 mg/kg Skin Corr. 1B; H314: >= 3 - 100 Skin Irrit. 2; H315: >= 1 - < 3 Eye Irrit. 2; H319: >= 1 - < 3		
98-00-0	202-626-1	Furfuryl alcohol	< 5 %
	inhalation: LC50 = 0,935 mg/l (vapours); inhalation: ATE = 0,5 mg/l (dusts or mists); dermal: ATE = 1100 mg/kg; oral: ATE = 500 mg/kg		
50-00-0	200-001-8	formaldehyde	< 0,5 %
	inhalation: ATE = 3 mg/l (vapours); inhalation: LC50 = 0,578 mg/l (dusts or mists); dermal: LD50 = 270 mg/kg; oral: LD50 = 600 - 800 mg/kg Skin Corr. 1B; H314: >= 25 - 100 Skin Irrit. 2; H315: >= 5 - < 25 Eye Irrit. 2; H319: >= 5 - < 25 Skin Sens. 1; H317: >= 0,2 - 100 STOT SE 3; H335: >= 5 - 100		

SECTION 4: First aid measures**4.1. Description of first aid measures****General information**

- Remove contaminated soaked clothing immediately.
- In the event of persistent symptoms receive medical treatment.
- Take away from danger area and lay down affected person.

After inhalation

- Move to fresh air in case of accidental inhalation of vapours.



Safety Data Sheet

according to UK REACH Regulation

Asplit® CN 916 Solution

Revision date: 06.12.2023

Product code: 00359-1164

Page 4 of 12

Seek medical treatment immediately.

After contact with skin

Wash off immediately with soap and plenty of water.
Consult a physician.

After contact with eyes

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.
Consult (eye) doctor immediately.

After ingestion

Do not induce vomiting.
Summon a doctor immediately.
Rinse out mouth and give plenty of water to drink.
Never give anything by mouth to an unconscious person.
Induce vomiting only upon the advice of a physician.

4.2. Most important symptoms and effects, both acute and delayed

May cause cancer.
Harmful if swallowed.
Causes severe skin burns and eye damage.
May cause an allergic skin reaction.
Suspected of causing genetic defects.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Alcohol-resistant foam, dry chemical, carbon dioxide (CO₂), water-spray.

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Fire may produce:
carbon monoxide and carbon dioxide
Irritant/corrosive, flammable as well as toxic distillation gases (carbonization gases).

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective suit.

Additional information

Vapours are heavier than air and spread along ground.
The vapour/air mixture is explosive, even in empty, uncleaned receptacles.
Cool containers at risk with water spray jet.
Collect contaminated firefighting water separately, must not be discharged into the drains.
Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Ensure adequate ventilation.
Remove persons to safety.
Keep away sources of ignition.

For non-emergency personnel

Do not breathe vapours.
Avoid contact with skin, eyes and clothing.



Safety Data Sheet

according to UK REACH Regulation

Asplit® CN 916 Solution

Revision date: 06.12.2023

Product code: 00359-1164

Page 5 of 12

For emergency responders

In case of vapour formation use respirator.
Use personal protective clothing.

6.2. Environmental precautions

Do not discharge into the drains/surface waters/ground water.
Do not discharge into the subsoil/soil.

6.3. Methods and material for containment and cleaning up

For containment

Prevent spread over a wide area (e.g. by containment or oil barriers).

For cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder).
Shovel into suitable container for disposal.

6.4. Reference to other sections

Observe protective instructions (see Sections 7 and 8).
Information for disposal see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Keep container tightly closed.
Vapours are heavier than air and spread along ground.
Use only in thoroughly ventilated areas.
Provide suitable extraction at the processing machines.

Advice on protection against fire and explosion

Keep away from heat and sources of ignition.
Do not smoke.
Take precautionary measures against static discharges.
Use only explosion-proof equipment.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a dry, cool and well-ventilated place.
Pay attention to anti-explosion rules.
Recommended storage temperature: < 20°C

Hints on joint storage

Incompatible with acids.

Further information on storage conditions

Keep away from food, drink and animal feeding stuffs.

7.3. Specific end use(s)

Mortar

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

**Safety Data Sheet**

according to UK REACH Regulation

Asplit® CN 916 Solution

Revision date: 06.12.2023

Product code: 00359-1164

Page 6 of 12

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
64-17-5	Ethanol	1000	1920		TWA (8 h)	WEL
50-00-0	Formaldehyde	2	2.5		TWA (8 h)	WEL
		2	2.5		STEL (15 min)	WEL
108-95-2	Phenol	2	7.8		TWA (8 h)	WEL
		4	16		STEL (15 min)	WEL

8.2. Exposure controls**Appropriate engineering controls**

Ensure adequate ventilation, especially in confined areas.
Pay attention to explosion protection guidelines.

Protective and hygiene measures

Do not inhale vapours.
Wash hands before breaks and immediately after handling the product.
When using do not eat, drink or smoke.
Treat subsequently with skin cream.
Remove and wash contaminated clothes before re-use.

Eye/face protection

Tightly fitting goggles (EN 166).
Eye wash bottle with pure water (EN 15154).

Hand protection

Protective gloves resistant to chemicals made off viton, minimum coat thickness 0.7 mm, permeation resistance (wear duration) approx. 480 minutes, i.e. protective glove <Vitoject 890> made by www.kcl.de.
This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.
Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

Skin protection

Long sleeved clothing (DIN EN ISO 6530)
Solvent-resistant apron (EN 467).

Respiratory protection

In case of insufficient ventilation wear suitable respiratory equipment (gas filter type A) (EN 14387).

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state: Liquid
Colour: Yellow - brown
Odour: Characteristic

Test method

pH-Value: n.d.

Changes in the physical state

Melting point/freezing point: n.d.
Boiling point or initial boiling point and boiling range: 60 - 100 °C
Sublimation point: n.a.
Softening point: n.d.

**Safety Data Sheet**

according to UK REACH Regulation

Asplit® CN 916 Solution

Revision date: 06.12.2023

Product code: 00359-1164

Page 7 of 12

Flash point: 33 °C DIN EN ISO 1523

Flammability

Solid/liquid: n.a.

Explosive properties

The product is considered non-explosive; nevertheless explosive vapour/air mixture can be generated.

Lower explosion limits: 3,5 vol. %

Upper explosion limits: 15 vol. %

Auto-ignition temperature: > 210 °C

Self-ignition temperature

Solid: n.a.

Gas: n.a.

Decomposition temperature: 84 °C

Oxidizing properties

Not oxidising.

Vapour pressure:
(at 20 °C) ~ 57 hPaDensity: 1,1 g/cm³

Bulk density: n.a.

Water solubility:
(at 20 °C) Partially soluble**Solubility in other solvents**

n.d.

Partition coefficient n-octanol/water: n.d.

Viscosity / dynamic:
(at 23 °C) ~ 700 mPa·s ISO 3219

Viscosity / kinematic: n.d.

Flow time: n.d.

Relative vapour density: n.d.

Evaporation rate: n.d.

Solvent separation test: n.d.

9.2. Other information

No data available

SECTION 10: Stability and reactivity**10.1. Reactivity**

No decomposition if stored and applied as directed.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Exothermic reaction with strong acids.

10.4. Conditions to avoid

To avoid thermal decomposition, do not overheat.

Vapour/air mixtures are explosive at intensive warming.

Heating can release vapours which can be ignited.

Avoid temperatures above 25°C .



Safety Data Sheet

according to UK REACH Regulation

Asplit® CN 916 Solution

Revision date: 06.12.2023

Product code: 00359-1164

Page 8 of 12

10.5. Incompatible materials

Acids.

10.6. Hazardous decomposition products

No hazardous decomposition products known.

Fire may produce:

Irritant/corrosive, flammable as well as toxic distillation gases (carbonization gases).

Carbon monoxide and carbon dioxide

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Acute toxicity

Harmful if swallowed.

ATEmix/oral: 1400 mg/kg

ATEmix/dermal: > 2000 mg/kg

ATEmix/inhalation: > 20 mg/l/4 h (vapour)

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

Irritation and corrosivity

Causes severe skin burns and eye damage.

Sensitising effects

May cause an allergic skin reaction. (formaldehyde; N-(3-(trimethoxysilyl)propyl)ethylenediamine)

Carcinogenic/mutagenic/toxic effects for reproduction

Suspected of causing genetic defects. (Phenol; formaldehyde)

May cause cancer. (formaldehyde)

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Additional information on tests

Classification in compliance with the assessment procedure specified in the Regulation (EC) no 1272/2008.

11.2. Information on other hazards

Endocrine disrupting properties

No data available

SECTION 12: Ecological information

12.1. Toxicity

Ecological data are not available.

Harmful to aquatic life with long lasting effects.

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential

No data available

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

Safety Data Sheet

according to UK REACH Regulation

Asplit® CN 916 Solution

Revision date: 06.12.2023

Product code: 00359-1164

Page 9 of 12

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

Hazardous water pollutant.

Further information

Do not flush into surface water or sanitary sewer system.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Can be incinerated, when in compliance with local regulations.
Where possible recycling is preferred to disposal.

List of Wastes Code - residues/unused products

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

Contaminated packaging

Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.

Packaging that cannot be cleaned should be disposed of like the product.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number:	UN 2924
14.2. UN proper shipping name:	FLAMMABLE LIQUID, CORROSIVE, N.O.S. (Ethanol, Phenol)
14.3. Transport hazard class(es):	3
14.4. Packing group:	III
Hazard label:	3+8



Classification code:	FC
Limited quantity:	5 L / 30 kg
Excepted quantity:	E1
Transport category:	3
Hazard No:	38
Tunnel restriction code:	D/E

Inland waterways transport (ADN)

14.1. UN number:	UN 2924
14.2. UN proper shipping name:	FLAMMABLE LIQUID, CORROSIVE, N.O.S. (Ethanol, Phenol)
14.3. Transport hazard class(es):	3
14.4. Packing group:	III
Hazard label:	3+8

Safety Data Sheet

according to UK REACH Regulation

Asplit® CN 916 Solution

Revision date: 06.12.2023

Product code: 00359-1164

Page 10 of 12



Classification code: FC
 Limited quantity: 5 L / 30 kg
 Excepted quantity: E1

Marine transport (IMDG)

14.1. UN number: UN 2924
14.2. UN proper shipping name: FLAMMABLE LIQUID, CORROSIVE, N.O.S. (Ethanol, phenol)
14.3. Transport hazard class(es): 3
14.4. Packing group: III
 Hazard label: 3+8



Marine pollutant: No
 Limited quantity: 5 L / 30 kg
 Excepted quantity: E1
 EmS: F-E, S-C

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number: UN 2924
14.2. UN proper shipping name: FLAMMABLE LIQUID, CORROSIVE, N.O.S. (Ethanol, phenol, solution)
14.3. Transport hazard class(es): 3
14.4. Packing group: III
 Hazard label: 3+8



Limited quantity Passenger: 1 L
 Passenger LQ: Y342
 Excepted quantity: E1
 IATA-packing instructions - Passenger: 354
 IATA-max. quantity - Passenger: 5 L
 IATA-packing instructions - Cargo: 365
 IATA-max. quantity - Cargo: 60 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Handle in accordance with good industrial hygiene and safety practice.

14.7. Maritime transport in bulk according to IMO instruments

The transport takes place only in approved and appropriate packaging.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):
 Entry 3, Entry 28, Entry 40, Entry 75

**Safety Data Sheet**

according to UK REACH Regulation

Asplit® CN 916 Solution

Revision date: 06.12.2023

Product code: 00359-1164

Page 11 of 12

Directive 2004/42/EC on VOC in
paints and varnishes: < 20 %
Information according to Directive
2012/18/EU (SEVESO III): P5c FLAMMABLE LIQUIDS

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water hazard class (D): 2 - obviously hazardous to water

Additional information

Consider Chemical prohibition regulation.

15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

SECTION 16: Other information**Changes**

This data sheet contains changes from the previous version in section(s): 2,6,7,8,10,11,12,14.

Abbreviations and acronyms

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route
RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses
ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure
IMDG = International Maritime Code for Dangerous Goods
IATA/ICAO = International Air Transport Association / International Civil Aviation Organization
MARPOL = International Convention for the Prevention of Pollution from Ships
IBC-Code = International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk

GHS = Globally Harmonized System of Classification and Labelling of Chemicals
REACH = Registration, Evaluation, Authorization and Restriction of Chemicals
CAS = Chemical Abstract Service
EN = European norm
ISO = International Organization for Standardization
DIN = Deutsche Industrie Norm
PBT = Persistent Bioaccumulative and Toxic
vPvB = Very Persistent and very Bio-accumulative
LD = Lethal dose
LC = Lethal concentration
EC = Effect concentration
IC = Median immobilisation concentration or median inhibitory concentration

Relevant H and EUH statements (number and full text)

H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H301 Toxic if swallowed.
H302 Harmful if swallowed.
H311 Toxic in contact with skin.
H312 Harmful in contact with skin.
H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.

**Safety Data Sheet**

according to UK REACH Regulation

Asplit® CN 916 Solution

Revision date: 06.12.2023

Product code: 00359-1164

Page 12 of 12

H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H335	May cause respiratory irritation.
H341	Suspected of causing genetic defects.
H350	May cause cancer.
H351	Suspected of causing cancer.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Further Information

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product(s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

(n.a. = not applicable; n.d. = not determined)

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)