



Safety Data Sheet

according to UK REACH Regulation

Asplit® LC Hardener

Revision: 23.10.2025

Product code: 00359-1208

Page 2 of 12

Hazard statements

H226	Flammable liquid and vapour.
H290	May be corrosive to metals.
H314	Causes severe skin burns and eye damage.
H336	May cause drowsiness or dizziness.
H341	Suspected of causing genetic defects.

Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260	Do not breathe vapour.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P301+P330+P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P312	Call a POISON CENTER/doctor if you feel unwell.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER/doctor.
P406	Store in a corrosion-resistant container with a resistant inner liner.

2.3. Other hazards

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

Vapours may form explosive mixture with air.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Mixture containing following substances with additives

Safety Data Sheet

according to UK REACH Regulation

Asplit® LC Hardener

Revision: 23.10.2025

Product code: 00359-1208

Page 3 of 12

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)			
98-67-9	4-Hydroxybenzenesulphonic acid			< 45 %
	202-691-6		01-2119538813-35	
	Met. Corr. 1, Skin Corr. 1B, Eye Dam. 1; H290 H314 H318			
67-63-0	Propan-2-ol			< 25 %
	200-661-7	603-117-00-0	01-2119457558-25	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336			
104-15-4	p-toluenesulphonic acid (containing a maximum of 5 % H2SO4)			< 15 %
	203-180-0	016-030-00-2	01-2119538811-39	
	Skin Irrit. 2, Eye Irrit. 2, STOT SE 3; H315 H319 H335			
7664-38-2	Phosphoric acid			< 10 %
	231-633-2	015-011-00-6	01-2119485924-24	
	Met. Corr. 1, Skin Corr. 1B; H290 H314			
7664-93-9	Sulphuric acid			< 5 %
	231-639-5	016-020-00-8	01-2119458838-20	
	Met. Corr. 1, Skin Corr. 1A, Eye Dam. 1; H290 H314 H318			
108-95-2	Phenol			< 2 %
	203-632-7	604-001-00-2	01-2119471329-32	
	Muta. 2, Acute Tox. 3, Acute Tox. 3, Acute Tox. 3, Skin Corr. 1B, Eye Dam. 1, STOT RE 2, Aquatic Chronic 2; H341 H331 H311 H301 H314 H318 H373 H411			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
67-63-0	200-661-7	Propan-2-ol	< 25 %
	dermal: LD50 = 12800 mg/kg; oral: LD50 = 5050 mg/kg		
104-15-4	203-180-0	p-toluenesulphonic acid (containing a maximum of 5 % H2SO4)	< 15 %
	STOT SE 3; H335: >= 20 - 100		
7664-38-2	231-633-2	Phosphoric acid	< 10 %
	Skin Corr. 1B; H314: >= 25 - 100 Skin Irrit. 2; H315: >= 10 - < 25 Eye Irrit. 2; H319: >= 10 - < 25		
7664-93-9	231-639-5	Sulphuric acid	< 5 %
	Skin Corr. 1A; H314: >= 15 - 100 Skin Irrit. 2; H315: >= 5 - < 15 Eye Irrit. 2; H319: >= 5 - < 15		
108-95-2	203-632-7	Phenol	< 2 %
	inhalation: ATE = 3 mg/l (vapours); inhalation: ATE = 0,5 mg/l (dusts or mists); dermal: ATE = 300 mg/kg; oral: ATE = 100 mg/kg Skin Corr. 1B; H314: >= 3 - 100 Skin Irrit. 2; H315: >= 1 - < 3 Eye Irrit. 2; H319: >= 1 - < 3		

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

- Remove contaminated soaked clothing immediately.
- In the event of persistent symptoms receive medical treatment.
- Take away from danger area and lay down affected person.

Safety Data Sheet

according to UK REACH Regulation

Asplit® LC Hardener

Revision: 23.10.2025

Product code: 00359-1208

Page 4 of 12

After inhalation

Move to fresh air in case of accidental inhalation of vapours.
In the event of symptoms refer for medical treatment.

After contact with skin

Wash off immediately with soap and plenty of water.
Seek medical treatment immediately.

After contact with eyes

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.
Consult (eye) doctor immediately.

After ingestion

Do not induce vomiting.
Summon a doctor immediately.
Rinse out mouth and give plenty of water to drink.
Never give anything by mouth to an unconscious person.
Induce vomiting only upon the advice of a physician.

4.2. Most important symptoms and effects, both acute and delayed

Causes severe skin burns and eye damage.
May cause drowsiness or dizziness.
Suspected of causing genetic defects.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Alcohol-resistant foam, dry chemical, carbon dioxide (CO₂), water-spray.

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Fire may produce:
Carbon monoxide (CO), carbon dioxide (CO₂), sulphur oxides (SO_x) and phosphorus oxides (PO_x).

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective suit.

Additional information

Cool containers at risk with water spray jet.
Collect contaminated firefighting water separately, must not be discharged into the drains.
Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Ensure adequate ventilation.
Keep away noninvolved persons.

For non-emergency personnel

Avoid contact with skin, eyes and clothing.
Do not breathe vapours.

For emergency responders

In case of vapour formation use respirator.
Use personal protective clothing.



Safety Data Sheet

according to UK REACH Regulation

Asplit® LC Hardener

Revision: 23.10.2025

Product code: 00359-1208

Page 5 of 12

6.2. Environmental precautions

- Do not discharge into the drains/surface waters/ground water.
- Do not discharge into the subsoil/soil.

6.3. Methods and material for containment and cleaning up

For containment

- Prevent spread over a wide area (e.g. by containment or oil barriers).

For cleaning up

- Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder).
- Shovel into suitable container for disposal.
- Do not use metal containers.

6.4. Reference to other sections

- Observe protective instructions (see Sections 7 and 8).
- Information for disposal see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

- Keep container tightly closed.
- Provide appropriate ventilation and exhaust ventilation at the workplaces.
- Avoid contact with skin, eyes and clothing.

Advice on protection against fire and explosion

- Keep away from heat and sources of ignition.
- Do not smoke.
- Take precautionary measures against static discharges.
- Use only explosion-proof equipment.

Advice on general occupational hygiene

- Do not inhale vapours.
- Wash hands before breaks and immediately after handling the product.
- When using do not eat, drink or smoke.
- Remove and wash contaminated clothes before re-use.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

- Keep only in original container.
- Keep container tightly closed in a dry, cool and well-ventilated place.
- Pay attention to anti-explosion rules.

Hints on joint storage

- Incompatible with bases.

Further information on storage conditions

- Keep away from food, drink and animal feeding stuffs.

7.3. Specific end use(s)

- Hardener

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

**Safety Data Sheet**

according to UK REACH Regulation

Asplit® LC Hardener

Revision: 23.10.2025

Product code: 00359-1208

Page 6 of 12

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
7664-38-2	Orthophosphoric acid	-	1		TWA (8 h)	WEL
		-	2		STEL (15 min)	WEL
108-95-2	Phenol	2	7.8		TWA (8 h)	WEL
		4	16		STEL (15 min)	WEL
67-63-0	Propan-2-ol	400	999		TWA (8 h)	WEL
		500	1250		STEL (15 min)	WEL
7664-93-9	Sulphuric acid (mist)	-	0.05		TWA (8 h)	WEL

8.2. Exposure controls**Appropriate engineering controls**

Ensure adequate ventilation, especially in confined areas.

Individual protection measures, such as personal protective equipment**Eye/face protection**

Tightly fitting goggles (EN 166).

Eye wash bottle with pure water (EN 15154).

Hand protection

Protective gloves resistant to chemicals made off viton, Minimum coat thickness 0.7 mm, Permeation resistance (wear duration) approx. 60 minutes, i.e. protective glove <Vitoject 890> made by www.kcl.de. This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.

Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

Skin protection

Long sleeved clothing (DIN EN ISO 6530)

Solvent-resistant apron (EN 467).

Respiratory protection

In case of insufficient ventilation wear suitable respiratory equipment (gas filter type A) (EN 14387).

Environmental exposure controls

Do not flush into surface water or sanitary sewer system.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state:	Liquid
Colour:	Colourless
Odour:	Characteristic

Changes in the physical state

Melting point/freezing point:	n.d.
Boiling point or initial boiling point and boiling range:	n.d.
Sublimation point:	n.a.
Softening point:	n.d.
Flash point:	approx. 41 °C

Flammability

Solid/liquid:	n.a.
---------------	------

**Safety Data Sheet**

according to UK REACH Regulation

Asplit® LC Hardener

Revision: 23.10.2025

Product code: 00359-1208

Page 7 of 12

Explosive properties

The product is considered non-explosive; nevertheless explosive vapour/air mixture can be generated.

Lower explosion limits: 2,0 vol. %

Upper explosion limits: 12,0 vol. %

Auto-ignition temperature: approx. 350 °C

Self-ignition temperature

Solid: n.a.

Gas: n.a.

Decomposition temperature: n.d.

pH-Value: n.d.

Viscosity / dynamic: n.d.

Viscosity / kinematic: > 7 - < 20,5 mm²/s
(at 40 °C)

Flow time: n.d.

Water solubility: Miscible
(at 20 °C)**Solubility in other solvents**

n.d.

Partition coefficient n-octanol/water: n.d.

Vapour pressure: 43 hPa
(at 20 °C)Density: approx. 1,18 g/cm³

Bulk density: n.a.

Relative vapour density: n.d.

9.2. Other information**Information with regard to physical hazard classes**

Sustained combustibility: Sustained combustibility

Oxidizing properties

Not oxidising.

Other safety characteristics

Solvent separation test: n.d.

Solvent content: < 25 %

Evaporation rate: n.d.

Further Information

No data available

SECTION 10: Stability and reactivity**10.1. Reactivity**

No decomposition if stored and applied as directed.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Reactions with alkalis.

10.4. Conditions to avoid

Heating can release vapours which can be ignited.

Safety Data Sheet

according to UK REACH Regulation

Asplit® LC Hardener

Revision: 23.10.2025

Product code: 00359-1208

Page 8 of 12

Vapours may form explosive mixture with air.
Gives off hydrogen by reaction with metals.

10.5. Incompatible materials

Bases.

10.6. Hazardous decomposition products

Hydrogen, by reaction with metals.

Fire may produce:

Carbon monoxide (CO), carbon dioxide (CO₂), sulphur oxides (SO_x) and phosphorus oxides (PO_x).

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Acute toxicity

Based on available data, the classification criteria are not met.
No toxicological data available.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

Irritation and corrosivity

Skin corrosion/irritation: Causes severe skin burns and eye damage.
Serious eye damage/eye irritation: Causes serious eye damage.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Suspected of causing genetic defects. (Phenol)
Carcinogenicity: Based on available data, the classification criteria are not met.
Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (Propan-2-ol)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Additional information on tests

Classification in compliance with the assessment procedure specified in the Regulation (EC) no 1272/2008.

11.2. Information on other hazards

Endocrine disrupting properties

No data available

SECTION 12: Ecological information

12.1. Toxicity

Ecological data are not available.

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential

No data available

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

Safety Data Sheet

according to UK REACH Regulation

Asplit® LC Hardener

Revision: 23.10.2025

Product code: 00359-1208

Page 9 of 12

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

No data available

12.7. Other adverse effects

Low hazard to waters.

Further information

Do not flush into surface water or sanitary sewer system.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Can be incinerated, when in compliance with local regulations.

Where possible recycling is preferred to disposal.

List of Wastes Code - residues/unused products

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

Contaminated packaging

Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.

Packaging that cannot be cleaned should be disposed of like the product.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number:

UN 2920

14.2. UN proper shipping name:

CORROSIVE LIQUID, FLAMMABLE, N.O.S. (4-Hydroxybenzenesulphonic acid, Propan-2-ol)

14.3. Transport hazard class(es):

8

14.4. Packing group:

II

Hazard label:

8+3



Classification code:

CF1

Limited quantity:

1 L / 30 kg

Excepted quantity:

E2

Transport category:

2

Hazard No:

83

Tunnel restriction code:

D/E

Inland waterways transport (ADN)

14.1. UN number or ID number:

UN 2920

14.2. UN proper shipping name:

CORROSIVE LIQUID, FLAMMABLE, N.O.S. (4-Hydroxybenzenesulphonic acid, Propan-2-ol)

14.3. Transport hazard class(es):

8

Safety Data Sheet

according to UK REACH Regulation

Asplit® LC Hardener

Revision: 23.10.2025

Product code: 00359-1208

Page 10 of 12

14.4. Packing group:

Hazard label:

II
8+3

Classification code:

CF1

Limited quantity:

1 L / 30 kg

Excepted quantity:

E2

Marine transport (IMDG)**14.1. UN number or ID number:**

UN 2920

14.2. UN proper shipping name:

CORROSIVE LIQUID, FLAMMABLE, N.O.S. (4-Hydroxybenzenesulphonic acid, Propan-2-ol)

14.3. Transport hazard class(es):

8

14.4. Packing group:

II

Hazard label:

8+3



Marine pollutant:

No

Limited quantity:

1 L / 30 kg

Excepted quantity:

E2

EmS:

F-E, S-C

Air transport (ICAO-TI/IATA-DGR)**14.1. UN number or ID number:**

UN 2920

14.2. UN proper shipping name:

CORROSIVE LIQUID, FLAMMABLE, N.O.S. (4-Hydroxybenzenesulphonic acid, Propan-2-ol, mixture)

14.3. Transport hazard class(es):

8

14.4. Packing group:

II

Hazard label:

8+3



Limited quantity Passenger:

0.5 L

Passenger LQ:

Y840

Excepted quantity:

E2

IATA-packing instructions - Passenger:

851

IATA-max. quantity - Passenger:

1 L

IATA-packing instructions - Cargo:

855

IATA-max. quantity - Cargo:

30 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS:

No

14.6. Special precautions for user

Handle in accordance with good industrial hygiene and safety practice.

14.7. Maritime transport in bulk according to IMO instruments

The transport takes place only in approved and appropriate packaging.

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

**Safety Data Sheet**

according to UK REACH Regulation

Asplit® LC Hardener

Revision: 23.10.2025

Product code: 00359-1208

Page 11 of 12

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

Directive 2004/42/EC on VOC in
paints and varnishes: 24 %Information according to Directive
2012/18/EU (SEVESO III): P5c FLAMMABLE LIQUIDS**Additional information**

This product is regulated by Annex II of Regulation (EU) 2019/1148 on the marketing and use of explosives precursors. All suspicious transactions and significant disappearances and thefts have to be reported to the responsible national contact point. Sales personnel at all trading levels has to be instructed.

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water hazard class (D): 1 - slightly hazardous to water

15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

SECTION 16: Other information**Changes**

This data sheet contains changes from the previous version in section(s): 2,4,6,7,9,10,11,12,15.

Abbreviations and acronyms

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route
RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses
ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure
IMDG = International Maritime Code for Dangerous Goods
IATA/ICAO = International Air Transport Association / International Civil Aviation Organization
MARPOL = International Convention for the Prevention of Pollution from Ships
IBC-Code = International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk

GHS = Globally Harmonized System of Classification and Labelling of Chemicals
REACH = Registration, Evaluation, Authorization and Restriction of Chemicals
CAS = Chemical Abstract Service
EN = European norm
ISO = International Organization for Standardization
DIN = Deutsche Industrie Norm
PBT = Persistent Bioaccumulative and Toxic
vPvB = Very Persistent and very Bio-accumulative

LD = Lethal dose
LC = Lethal concentration
EC = Effect concentration
IC = Median immobilisation concentration or median inhibitory concentration

**Safety Data Sheet**

according to UK REACH Regulation

Asplit® LC Hardener

Revision: 23.10.2025

Product code: 00359-1208

Page 12 of 12

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Flam. Liq. 3; H226	On basis of test data
Met. Corr. 1; H290	Practical experience/human evidence
Muta. 2; H341	Calculation method
Skin Corr. 1B; H314	Calculation method
Eye Dam. 1; H318	Calculation method
STOT SE 3; H336	Calculation method

Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H290	May be corrosive to metals.
H301	Toxic if swallowed.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H341	Suspected of causing genetic defects.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.

Further Information

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product(s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

(n.a. = not applicable; n.d. = not determined)

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)