

## Safety Data Sheet

according to UK REACH Regulation

### TIP TOP CAMPLAST CEMENT

Revision: 25.09.2025

Product code: 00156-0045

Page 1 of 11

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

##### 1.1. Product identifier

TIP TOP CAMPLAST CEMENT

##### Art.-No.

514 9229, 514 9230, 552 2208, 552 2209, 552 2215, 552 2246, 552 3001, 552 3128, 552 3190, 552 3197, 552 3198, 552 3199, 552 3207, 552 3208, 552 4000, 552 4196, 552 4200, 552 4206, 552 4270, 5096

##### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### Use of the substance/mixture

adhesive

##### 1.3. Details of the supplier of the safety data sheet

##### Manufacturer

Company name: REMA TIP TOP AG  
Street: Gruber Strasse 65  
Place: D-85586 Poing  
Telephone: +49 (0) 8121 / 707 - 100  
Responsible Department: Responsible for the safety data sheet: sds@gbk-ingelheim.de

##### Supplier

Company name: REMA TIP TOP AUTOMOTIVE UK LTD  
Street: Westland Square, LEEDS  
Place: West Yorkshire, LS11 5XS  
Telephone: +44 (0)113 2770044  
E-mail: info@tip-top.co.uk  
Internet: www.rema-tiptop.co.uk

##### 1.4. Emergency telephone number:

INTERNATIONAL: +49 - (0) 6132 - 84463, GBK GmbH (24h - 7d/w - 365d/a)  
In England and Wales: NHS 111 In Scotland: NHS 24 - dial 111

#### SECTION 2: Hazards identification

##### 2.1. Classification of the substance or mixture

##### GB CLP Regulation

Hazard Statements:  
Highly flammable liquid and vapour.  
Causes serious eye irritation.  
May cause drowsiness or dizziness.

##### 2.2. Label elements

##### GB CLP Regulation

##### Hazard components for labelling

Butanone

Signal word: Danger

##### Pictograms:



##### Hazard statements

H225 Highly flammable liquid and vapour.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.

## Safety Data Sheet

according to UK REACH Regulation

### TIP TOP CAMPLAST CEMENT

Revision: 25.09.2025

Product code: 00156-0045

Page 2 of 11

#### Precautionary statements

P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P501	Dispose of contents/container to in accordance with local and national regulations.

#### Special labelling of certain mixtures

EUH066	Repeated exposure may cause skin dryness or cracking.
--------	---

#### 2.3. Other hazards

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605

Vapours may form explosive mixture with air.

### SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

##### Chemical characterization

Preparation in butanone

##### Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)			
78-93-3	Butanone			< 90 %
	201-159-0	606-002-00-3	01-2119457290-43	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066			

Full text of H and EUH statements: see section 16.

##### Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
78-93-3	201-159-0	Butanone	< 90 %
	dermal: LD50 = > 8000 mg/kg; oral: LD50 = 3400 mg/kg		

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

##### General information

Remove contaminated soaked clothing immediately.  
If you feel unwell, seek medical advice.

##### After inhalation

Move to fresh air in case of accidental inhalation of vapours or decomposition products.  
Refer for medical treatment.



## Safety Data Sheet

according to UK REACH Regulation

### TIP TOP CAMPLAST CEMENT

Revision: 25.09.2025

Product code: 00156-0045

Page 3 of 11

#### After contact with skin

Wash off with soap and plenty of water.  
Consult a doctor if skin irritation persists.

#### After contact with eyes

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.  
Seek medical treatment by eye specialist.

#### After ingestion

Do not induce vomiting.  
Rinse out mouth and give plenty of water to drink.  
Never give anything by mouth to an unconscious person.  
Summon a doctor immediately.  
The decision whether to induce vomiting or not is to be taken by a physician.

#### 4.2. Most important symptoms and effects, both acute and delayed

Causes serious eye irritation.  
May cause drowsiness or dizziness.  
Repeated exposure may cause skin dryness or cracking.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptoms.

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

##### Suitable extinguishing media

Alcohol-resistant foam, dry chemical, carbon dioxide (CO<sub>2</sub>), water-spray.

##### Unsuitable extinguishing media

Full water jet

#### 5.2. Special hazards arising from the substance or mixture

Fire may produce:  
carbon monoxide and carbon dioxide

#### 5.3. Advice for firefighters

Use breathing apparatus with independent air supply.  
Protective suit.

#### Additional information

Vapours are heavier than air and spread along ground.  
The vapour/air mixture is explosive, even in empty, uncleaned receptacles.  
Cool containers at risk with water spray jet.  
Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

##### General advice

Use only explosion-proof equipment.  
Ensure adequate ventilation.  
Keep away sources of ignition.  
Keep away noninvolved persons.

##### For non-emergency personnel

Do not breathe vapours.  
Avoid contact with skin, eyes and clothing.

##### For emergency responders

In case of vapour formation use respirator.  
Use personal protective clothing.



## Safety Data Sheet

according to UK REACH Regulation

### TIP TOP CAMPLAST CEMENT

Revision: 25.09.2025

Product code: 00156-0045

Page 4 of 11

#### **6.2. Environmental precautions**

Do not discharge into the drains/surface waters/ground water.

#### **6.3. Methods and material for containment and cleaning up**

##### **For containment**

Prevent spread over a wide area (e.g. by containment or oil barriers).

##### **For cleaning up**

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder).

Shovel into suitable container for disposal.

#### **6.4. Reference to other sections**

Observe protective instructions (see Sections 7 and 8).

Information for disposal see section 13.

### SECTION 7: Handling and storage

#### **7.1. Precautions for safe handling**

##### **Advice on safe handling**

Keep container tightly closed.

When using do not eat, drink or smoke.

Use only in thoroughly ventilated areas.

Avoid contact with skin, eyes and clothing.

##### **Advice on protection against fire and explosion**

Keep away from heat and sources of ignition.

Do not smoke.

Take precautionary measures against static discharges.

Use only explosion-proof equipment.

##### **Advice on general occupational hygiene**

Avoid contact with eyes and skin.

Wash hands before breaks and immediately after handling the product.

When using do not eat, drink or smoke.

Remove and wash contaminated clothes before re-use.

#### **7.2. Conditions for safe storage, including any incompatibilities**

##### **Requirements for storage rooms and vessels**

Keep container tightly closed in a dry, cool and well-ventilated place.

##### **Hints on joint storage**

Incompatible with oxidizing agents.

##### **Further information on storage conditions**

Keep away from food, drink and animal feeding stuffs.

#### **7.3. Specific end use(s)**

adhesive

### SECTION 8: Exposure controls/personal protection

#### **8.1. Control parameters**

##### **Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
78-93-3	Butan-2-one (methyl ethyl ketone)	200	600		TWA (8 h)	WEL
		300	899		STEL (15 min)	WEL

## Safety Data Sheet

according to UK REACH Regulation

### TIP TOP CAMPLAST CEMENT

Revision: 25.09.2025

Product code: 00156-0045

Page 5 of 11

#### Biological Monitoring Guidance Values (EH40)

CAS No	Substance	Parameter	Value	Test material	Sampling time
78-93-3	Butan-2-one	butan-2-one	70 µmol/L	urine	Post shift

#### 8.2. Exposure controls

##### Appropriate engineering controls

Ensure adequate ventilation, especially in confined areas.

##### Individual protection measures, such as personal protective equipment

##### Eye/face protection

Tightly fitting goggles (EN 166).

Eye wash bottle with pure water (EN 15154).

##### Hand protection

Protective gloves resistant to chemicals made off butyl, minimum coat thickness 0.7 mm, permeation resistance (wear duration) > 240 minutes, i.e. protective glove <Butoject 898> made by www.kcl.de. This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.

Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves. Protective gloves resistant to chemicals made off butyl, minimum coat thickness 0.7 mm, permeation resistance (wear duration) > 30 minutes, i.e. protective glove <Butoject 898> made by www.kcl.de.

##### Skin protection

Long sleeved clothing (DIN EN ISO 6530)

##### Respiratory protection

In case of insufficient ventilation wear suitable respiratory equipment (gas filter type A) (EN 14387).

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	yellow
Odour:	Like ketone

#### Test method

##### Changes in the physical state

Melting point/freezing point:	n.d.
Boiling point or initial boiling point and boiling range:	approx. 80 °C
Sublimation point:	n.a.
Softening point:	n.d.
Flash point:	- 7 °C DIN EN ISO 3679

##### Flammability

Solid/liquid:	n.a.
---------------	------

##### Explosive properties

The product is considered non-explosive; nevertheless explosive vapour/air mixture can be generated.

Lower explosion limits:	1,8 vol. %
Upper explosion limits:	11,5 vol. %
Auto-ignition temperature:	505 °C

##### Self-ignition temperature

Solid:	n.a.
--------	------

**Safety Data Sheet**

according to UK REACH Regulation

**TIP TOP CAMPLAST CEMENT**

Revision: 25.09.2025

Product code: 00156-0045

Page 6 of 11

Gas:	n.a.
Decomposition temperature:	n.d.
Viscosity / dynamic:	n.d.
Viscosity / kinematic:	n.d.
Flow time:	n.d.
Water solubility: (at 20 °C)	350 g/L
<b>Solubility in other solvents</b> n.d.	
Partition coefficient n-octanol/water:	n.d.
Vapour pressure: (at 20 °C)	105 hPa
Density (at 20 °C):	0,86 g/cm <sup>3</sup>
Bulk density:	n.a.
Relative vapour density:	n.d.

**9.2. Other information****Information with regard to physical hazard classes**

Sustained combustibility: Sustained combustibility

Oxidizing properties

Not oxidising.

**Other safety characteristics**

Solvent separation test: 0 %

Solvent content: &lt; 90 %

Evaporation rate: n.d.

**Further Information**

No data available

**SECTION 10: Stability and reactivity****10.1. Reactivity**

No decomposition if stored and applied as directed.

**10.2. Chemical stability**

Stable under normal conditions.

**10.3. Possibility of hazardous reactions**

Reactions with oxidizing agents.

**10.4. Conditions to avoid**

Vapour/air mixtures are explosive at intensive warming.

Heating can release vapours which can be ignited.

**10.5. Incompatible materials**

oxidizing agents

**10.6. Hazardous decomposition products**

No hazardous decomposition products known.

Fire may produce:

Carbon monoxide and carbon dioxide

**SECTION 11: Toxicological information****11.1. Information on hazard classes as defined in GB CLP Regulation**

## Safety Data Sheet

according to UK REACH Regulation

### TIP TOP CAMPLAST CEMENT

Revision: 25.09.2025

Product code: 00156-0045

Page 7 of 11

#### Acute toxicity

Based on available data, the classification criteria are not met.  
No toxicological data available.  
Butanone  
LD50/oral/rat: 3300 mg/kg  
LD50/dermal/rabbit: 6400 - 8000 mg/kg

#### ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

#### Irritation and corrosivity

Serious eye damage/eye irritation: Causes serious eye irritation.  
Skin corrosion/irritation: Based on available data, the classification criteria are not met.  
Repeated exposure may cause skin dryness or cracking.

#### Sensitising effects

Based on available data, the classification criteria are not met.

#### Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.  
Carcinogenicity: Based on available data, the classification criteria are not met.  
Reproductive toxicity: Based on available data, the classification criteria are not met.

#### STOT-single exposure

May cause drowsiness or dizziness. (Butanone)

#### STOT-repeated exposure

Based on available data, the classification criteria are not met.

#### Aspiration hazard

Based on available data, the classification criteria are not met.

#### Additional information on tests

Classification in compliance with the assessment procedure specified in the Regulation (EC) no 1272/2008.

#### 11.2. Information on other hazards

##### Endocrine disrupting properties

No data available

##### Other information

Concentration above the admissible concentration at the workplace may cause dizziness, headache and inebriation.  
Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea.

### SECTION 12: Ecological information

#### 12.1. Toxicity

Ecological data are not available.  
Butanone  
LC50/Pimephales promelas/96 h = 3220 mg/l  
EC50/Daphnia magna/48 h = 5091 mg/l

#### 12.2. Persistence and degradability

No data available  
Butanone  
Readily biodegradable (to OECD criteria).

#### 12.3. Bioaccumulative potential

No data available

#### 12.4. Mobility in soil

No data available

#### 12.5. Results of PBT and vPvB assessment

## Safety Data Sheet

according to UK REACH Regulation

### TIP TOP CAMPLAST CEMENT

Revision: 25.09.2025

Product code: 00156-0045

Page 8 of 11

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

#### 12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

#### 12.7. Other adverse effects

Low hazard to waters.

#### **Further information**

Ecological injuries are not known or expected under normal use.

Do not flush into surface water or sanitary sewer system.

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

##### **Disposal recommendations**

Can be disposed of as a solid waste or burned in a suitable installation subject to local regulations.

Where possible recycling is preferred to disposal.

##### **List of Wastes Code - residues/unused products**

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

##### **Contaminated packaging**

Empty containers should be taken for local recycling, recovery or waste disposal.

Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.

Packaging that cannot be cleaned should be disposed of like the product.

### SECTION 14: Transport information

#### **Land transport (ADR/RID)**

<u>14.1. UN number or ID number:</u>	UN 1133
<u>14.2. UN proper shipping name:</u>	Adhesives
<u>14.3. Transport hazard class(es):</u>	3
<u>14.4. Packing group:</u>	II
Hazard label:	3



Classification code:	F1
Limited quantity:	5 L / 30 kg
Excepted quantity:	E2
Transport category:	2
Hazard No:	33
Tunnel restriction code:	D/E

#### **Other applicable information (land transport)**

HAZCHEM: 3YE

#### **Inland waterways transport (ADN)**

<u>14.1. UN number or ID number:</u>	UN 1133
<u>14.2. UN proper shipping name:</u>	Adhesives
<u>14.3. Transport hazard class(es):</u>	3
<u>14.4. Packing group:</u>	II

## Safety Data Sheet

according to UK REACH Regulation

### TIP TOP CAMPLAST CEMENT

Revision: 25.09.2025

Product code: 00156-0045

Page 9 of 11

Hazard label: 3



Classification code: F1  
Limited quantity: 5 L / 30 kg  
Excepted quantity: E2

#### Marine transport (IMDG)

**14.1. UN number or ID number:** UN 1133  
**14.2. UN proper shipping name:** Adhesives  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** II  
Hazard label: 3



Marine pollutant: No  
Limited quantity: 5 L / 30 kg  
Excepted quantity: E2  
EmS: F-E, S-D  
Segregation group: alkalis

#### Air transport (ICAO-TI/IATA-DGR)

**14.1. UN number or ID number:** UN 1133  
**14.2. UN proper shipping name:** Adhesives  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** II  
Hazard label: 3



Limited quantity Passenger: 1 L  
Passenger LQ: Y341  
Excepted quantity: E2  
IATA-packing instructions - Passenger: 353  
IATA-max. quantity - Passenger: 5 L  
IATA-packing instructions - Cargo: 364  
IATA-max. quantity - Cargo: 60 L

#### 14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

#### 14.6. Special precautions for user

Handle in accordance with good industrial hygiene and safety practice.

#### 14.7. Maritime transport in bulk according to IMO instruments

The transport takes place only in approved and appropriate packaging.

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

##### EU regulatory information

Restrictions on use (REACH, annex XVII):  
Entry 40, Entry 75

**Safety Data Sheet**

according to UK REACH Regulation

**TIP TOP CAMPLAST CEMENT**

Revision: 25.09.2025

Product code: 00156-0045

Page 10 of 11

Directive 2004/42/EC on VOC in  
paints and varnishes:  
Information according to Directive  
2012/18/EU (SEVESO III):

&lt; 90 %

P5c FLAMMABLE LIQUIDS

**National regulatory information**

Employment restrictions:

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water hazard class (D):

1 - slightly hazardous to water

**15.2. Chemical safety assessment**

For this substance a chemical safety assessment has not been carried out.

**SECTION 16: Other information****Changes**

This data sheet contains changes from the previous version in section(s): 2,6,7,9,10,11,12,14.

**Abbreviations and acronyms**

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route

RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses

ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure

IMDG = International Maritime Code for Dangerous Goods

IATA/ICAO = International Air Transport Association / International Civil Aviation Organization

MARPOL = International Convention for the Prevention of Pollution from Ships

IBC-Code = International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

REACH = Registration, Evaluation, Authorization and Restriction of Chemicals

CAS = Chemical Abstract Service

EN = European norm

ISO = International Organization for Standardization

DIN = Deutsche Industrie Norm

PBT = Persistent Bioaccumulative and Toxic

vPvB = Very Persistent and very Bio-accumulative

LD = Lethal dose

LC = Lethal concentration

EC = Effect concentration

IC = Median immobilisation concentration or median inhibitory concentration

**Relevant H and EUH statements (number and full text)**

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

EUH066 Repeated exposure may cause skin dryness or cracking.

**Further Information**

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product(s) and is based on the present level of our knowledge.

**Safety Data Sheet**

according to UK REACH Regulation

**TIP TOP CAMPLAST CEMENT**

Revision: 25.09.2025

Product code: 00156-0045

Page 11 of 11

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

(n.a. = not applicable; n.d. = not determined)

---

*(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*