



## ESKANOL PU 23 COMP. A

Revision date: 23.08.2022

Product code: 00359-1309

Page 2 of 13

### Pictograms:



### Hazard statements

H226	Flammable liquid and vapour.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H317	May cause an allergic skin reaction.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.

### Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260	Do not breathe vapour.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P314	Get medical advice/attention if you feel unwell.
P273	Avoid release to the environment.

### 2.3. Other hazards

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605

Vapours may form explosive mixture with air.

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

#### Chemical characterization

Mixture containing following substances with additives

## ESKANOL PU 23 COMP. A

Revision date: 23.08.2022

Product code: 00359-1309

Page 3 of 13

### Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	GHS Classification			
64742-95-6	Solvent naphta (petroleum)			< 35 %
	918-668-5	649-356-00-4	01-2119455851-35	
	Flam. Liq. 3, STOT SE 3, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H226 H335 H336 H304 H411 EUH066			
1330-20-7	Xylene (mixed isomers)			< 30 %
	215-535-7	601-022-00-9	01-2119488216-32	
	Flam. Liq. 3, Acute Tox. 4, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, STOT SE 3, STOT RE 2, Asp. Tox. 1, Aquatic Chronic 3; H226 H332 H312 H315 H319 H335 H373 H304 H412			
166736-08-9	Oxirane, 2-methyl-, polymer with oxirane, mono(2-propylheptyl) ether			< 3 %
	605-450-7			
	Acute Tox. 4, Eye Dam. 1; H302 H318			
123-86-4	n-butyl acetate			< 3 %
	204-658-1	607-025-00-1	01-2119485493-29	
	Flam. Liq. 3, STOT SE 3; H226 H336 EUH066			
2682-20-4	2-methyl-2H-isothiazol-3-one			< 0,1 %
	220-239-6	613-326-00-9	01-2120764690-50	
	Acute Tox. 2, Acute Tox. 3, Acute Tox. 3, Skin Corr. 1B, Eye Dam. 1, Skin Sens. 1A, Aquatic Acute 1, Aquatic Chronic 1; H330 H311 H301 H314 H318 H317 H400 H410 EUH071			

Full text of H and EUH statements: see section 16.

### Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
1330-20-7	215-535-7	Xylene (mixed isomers)	< 30 %
		inhalation: ATE = 11 mg/l (vapours); dermal: ATE = 1100 mg/kg	
166736-08-9	605-450-7	Oxirane, 2-methyl-, polymer with oxirane, mono(2-propylheptyl) ether	< 3 %
		oral: ATE = 500 mg/kg	
123-86-4	204-658-1	n-butyl acetate	< 3 %
		dermal: LD50 = > 17600 mg/kg; oral: LD50 = 10800 mg/kg	
2682-20-4	220-239-6	2-methyl-2H-isothiazol-3-one	< 0,1 %
		inhalation: ATE = 0,5 mg/l (vapours); inhalation: ATE = 0,05 mg/l (dusts or mists); dermal: ATE = 300 mg/kg; oral: ATE = 100 mg/kg Skin Sens. 1A; H317: >= 0,0015 - 100 M acute; H400: M=10 M chron.; H410: M=1	

### Further Information

According to note P to the regulation (EC) no. 1272/2008, "Solvent naphta (petroleum)" is not to be classified as "carcinogenic" or "mutagen" ingredient because a benzene content (EINECS No. 200-753-7) is below 0.1 % by weight.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### General information

Remove contaminated soaked clothing immediately.  
Take away from danger area and lay down affected person.

## ESKANOL PU 23 COMP. A

Revision date: 23.08.2022

Product code: 00359-1309

Page 4 of 13

### After inhalation

Move to fresh air in case of accidental inhalation of vapours or decomposition products.  
Keep warm and calm injured person.  
If patient is not breathing, apply artificial respiration.  
Seek medical treatment immediately.

### After contact with skin

In case of contact with skin wash off immediately with soap and water.  
Do not use solvents or thinners.  
Consult a doctor if skin irritation persists.

### After contact with eyes

Remove contact lens.  
Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.  
Seek medical treatment by eye specialist.

### After ingestion

Do not induce vomiting.  
Rinse mouth.  
Never give anything by mouth to an unconscious person.  
Summon a doctor immediately.  
Induce vomiting only upon the advice of a physician.

### 4.2. Most important symptoms and effects, both acute and delayed

Causes skin irritation.  
May cause an allergic skin reaction.  
Causes serious eye irritation.  
May cause respiratory irritation.  
May cause drowsiness or dizziness.  
May cause damage to organs through prolonged or repeated exposure.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptoms.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

#### Suitable extinguishing media

Alcohol-resistant foam, dry chemical, carbon dioxide (CO<sub>2</sub>), water-spray.

#### Unsuitable extinguishing media

Full water jet

### 5.2. Special hazards arising from the substance or mixture

Fire may produce:  
carbon monoxide (CO), carbon dioxide (CO<sub>2</sub>) and nitrogen oxides (NO<sub>x</sub>)  
Traces of Hydrogen cyanide (HCN)

### 5.3. Advice for firefighters

In case of fire, wear suitable respiratory equipment with positive air supply.  
Protective suit.

### Additional information

Vapours are heavier than air and spread along ground.  
The vapour/air mixture is explosive, even in empty, uncleaned receptacles.  
Cool containers at risk with water spray jet.  
Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

## ESKANOL PU 23 COMP. A

Revision date: 23.08.2022

Product code: 00359-1309

Page 5 of 13

### General advice

Ensure adequate ventilation.  
Remove persons to safety.  
Keep away sources of ignition.

### For non-emergency personnel

Avoid contact with skin, eyes and clothing.  
Do not breathe vapours.

### For emergency responders

In case of vapour formation use respirator.  
Use personal protective clothing.

### 6.2. Environmental precautions

Do not discharge into the drains/surface waters/ground water.  
Do not discharge into the subsoil/soil.

### 6.3. Methods and material for containment and cleaning up

#### For containment

Prevent spread over a wide area (e.g. by containment or oil barriers).

#### For cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder).  
Shovel into suitable container for disposal.  
Clean contaminated surface thoroughly.

### 6.4. Reference to other sections

Observe protective instructions (see Sections 7 and 8).  
Information for disposal see section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

#### Advice on safe handling

Do not wear contact lenses when handling the product.  
Keep container tightly closed.  
Vapours are heavier than air and spread along ground.  
Keep a good ventilation and air-exhaust at the place of work.  
Do not empty container under pressure. No pressure tank!

#### Advice on protection against fire and explosion

Keep away from heat and sources of ignition.  
Do not smoke.  
Take precautionary measures against static discharges.  
Use only explosion-proof equipment.

### 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Keep container tightly closed in a dry, cool and well-ventilated place.  
Pay attention to anti-explosion rules.  
Take precautionary measures against static discharges.  
Recommended storage temperature: 10°C - 30°C

#### Hints on joint storage

Incompatible with:  
strong oxidizing agents  
strong acids and strong bases

#### Further information on storage conditions

Keep away from food, drink and animal feeding stuffs.

### 7.3. Specific end use(s)

**ESKANOL PU 23 COMP. A**

Revision date: 23.08.2022

Product code: 00359-1309

Page 6 of 13

Coating

**SECTION 8: Exposure controls/personal protection****8.1. Control parameters****Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
123-86-4	Butyl acetate	150	724		TWA (8 h)	WEL
		200	966		STEL (15 min)	WEL
1330-20-7	Xylene: mixed isomers	50	220		TWA (8 h)	WEL
		100	441		STEL (15 min)	WEL

**Biological Monitoring Guidance Values (EH40)**

CAS No	Substance	Parameter	Value	Test material	Sampling time
1330-20-7	Xylene, o-, m-, p- or mixed isomers	methyl hippuric acid (creatinine)	650 mmol/mol	urine	Post shift

**8.2. Exposure controls****Appropriate engineering controls**

Ensure adequate ventilation, especially in confined areas.

**Protective and hygiene measures**

Do not inhale vapours.

Wash hands before breaks and immediately after handling the product.

When using do not eat, drink or smoke.

Avoid contact with skin, eyes and clothing.

Remove and wash contaminated clothes before re-use.

**Eye/face protection**

Tightly fitting goggles (EN 166).

Eye wash bottle with pure water (EN 15154).

**Hand protection**

Protective gloves resistant to chemicals made of nitrile, minimum coat thickness 0.4 mm, permeation resistance (wear duration) approx. 480 minutes, i.e. protective glove <Camatril Velours 730> made by [www.kcl.de](http://www.kcl.de).

This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.

Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

**Skin protection**

Long sleeved clothing

**Respiratory protection**

In case of insufficient ventilation wear suitable respiratory equipment (gas filter type A) (EN 14387).

**SECTION 9: Physical and chemical properties****9.1. Information on basic physical and chemical properties**

Physical state:	Liquid
Colour:	Pigmented
Odour:	Soft

## ESKANOL PU 23 COMP. A

Revision date: 23.08.2022

Product code: 00359-1309

Page 7 of 13

### Test method

pH-Value:	n.d.	
<b>Changes in the physical state</b>		
Melting point/freezing point:	n.d.	
Boiling point or initial boiling point and boiling range:	n.d.	
Sublimation point:	n.a.	
Softening point:	n.d.	
Flash point:	27 °C	DIN EN ISO 2719
Sustaining combustion:	Sustaining combustion	
<b>Flammability</b>		
Solid/liquid:	n.a.	
Gas:	n.a.	
<b>Explosive properties</b>		
The product is considered non-explosive; nevertheless explosive vapour/air mixture can be generated.		
Lower explosion limits:	n.d.	
Upper explosion limits:	n.d.	
Auto-ignition temperature:	n.d.	
<b>Self-ignition temperature</b>		
Solid:	n.a.	
Gas:	n.a.	
Decomposition temperature:	n.d.	
<b>Oxidizing properties</b>		
Not oxidising.		
Vapour pressure:	n.d.	
Density (at 20 °C):	approx. 1,29 g/cm <sup>3</sup>	ISO 2811-2
Bulk density:	n.a.	
Water solubility:	Immiscible	
<b>Solubility in other solvents</b>		
n.d.		
Partition coefficient n-octanol/water:	n.d.	
Viscosity / dynamic: (at 25 °C)	700 - 1050 mPa·s	ISO 2884-1
Viscosity / kinematic: (at 40 °C)	700 mm <sup>2</sup> /s	
Flow time: (at 23 °C)	> 60 s	
Relative vapour density:	n.d.	
Evaporation rate:	n.d.	
Solvent separation test:	< 3 %	
Solvent content:	70 %	

### 9.2. Other information

No data available

## SECTION 10: Stability and reactivity

## ESKANOL PU 23 COMP. A

Revision date: 23.08.2022

Product code: 00359-1309

Page 8 of 13

### **10.1. Reactivity**

No decomposition if stored and applied as directed.

### **10.2. Chemical stability**

Stable under normal conditions.

### **10.3. Possibility of hazardous reactions**

Reactions with acids, alkalies and oxidizing agents

### **10.4. Conditions to avoid**

To avoid thermal decomposition, do not overheat.  
Vapour/air mixtures are explosive at intensive warming.  
Heating can release vapours which can be ignited.

### **10.5. Incompatible materials**

Strong oxidizing agents  
Strong acids and strong bases

### **10.6. Hazardous decomposition products**

No known hazardous decomposition products.  
Fire may produce:  
carbon monoxide (CO), carbon dioxide (CO<sub>2</sub>) and nitrogen oxides (NO<sub>x</sub>)  
Traces of Hydrogen cyanide (HCN)

## SECTION 11: Toxicological information

### **11.1. Information on hazard classes as defined in GB CLP Regulation**

#### **Acute toxicity**

Based on available data, the classification criteria are not met.  
No toxicological data available.

#### **Irritation and corrosivity**

Causes skin irritation.  
Causes serious eye irritation.

#### **Sensitising effects**

May cause an allergic skin reaction. (2-methyl-2H-isothiazol-3-one)

#### **Carcinogenic/mutagenic/toxic effects for reproduction**

Based on available data, the classification criteria are not met.

#### **STOT-single exposure**

May cause respiratory irritation. (Solvent naphta (petroleum); Xylene (mixed isomers))  
May cause drowsiness or dizziness. (Solvent naphta (petroleum))

#### **STOT-repeated exposure**

May cause damage to organs through prolonged or repeated exposure. (Xylene (mixed isomers))

#### **Aspiration hazard**

Based on available data, the classification criteria are not met.

#### **Additional information on tests**

Classification in compliance with the assessment procedure specified in the Regulation (EC) no 1272/2008.

### **11.2. Information on other hazards**

#### **Endocrine disrupting properties**

No data available

#### **Other information**

Inhalation of high vapour concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.  
Repeated or prolonged exposure may cause skin irritation and dermatitis, due to degreasing properties of the product.  
Ingestion causes irritation of upper respiratory system and gastrointestinal disturbance.

## ESKANOL PU 23 COMP. A

Revision date: 23.08.2022

Product code: 00359-1309

Page 9 of 13

Attention. Beware, danger of aspiration!

### SECTION 12: Ecological information

#### 12.1. Toxicity

Ecological data are not available.  
Harmful to aquatic life with long lasting effects.

#### 12.2. Persistence and degradability

No data available

#### 12.3. Bioaccumulative potential

No data available

#### 12.4. Mobility in soil

No data available

#### 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

#### 12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

#### 12.7. Other adverse effects

Hazardous water pollutant.

#### Further information

Do not flush into surface water or sanitary sewer system.

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

##### Disposal recommendations

Where possible recycling is preferred to disposal.  
Can be incinerated, when in compliance with local regulations.

##### List of Wastes Code - residues/unused products

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances; hazardous waste

##### Contaminated packaging

Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.

Packaging that cannot be cleaned should be disposed of like the product.

Empty containers should be taken for local recycling, recovery or waste disposal.

### SECTION 14: Transport information

#### Land transport (ADR/RID)

<u>14.1. UN number:</u>	UN 1263
<u>14.2. UN proper shipping name:</u>	Paint
<u>14.3. Transport hazard class(es):</u>	3
<u>14.4. Packing group:</u>	III
Hazard label:	3



**ESKANOL PU 23 COMP. A**

Revision date: 23.08.2022

Product code: 00359-1309

Page 10 of 13

Classification code: F1  
Limited quantity: 5 L / 30 kg  
Excepted quantity: E1  
Transport category: 3  
Hazard No: 30  
Tunnel restriction code: D/E

**Other applicable information (land transport)**

Viscous substance - excepted quantity if in containers with a capacity up to 450 l (subsection 2.2.3.1.5 ADR).

**Inland waterways transport (ADN)**

**14.1. UN number:** UN 1263  
**14.2. UN proper shipping name:** Paint  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** III  
Hazard label: 3



Classification code: F1  
Limited quantity: 5 L / 30 kg  
Excepted quantity: E1

**Other applicable information (inland waterways transport)**

Viscous substance - excepted quantity if in containers with a capacity up to 450 l (subsection 2.2.3.1.5 ADN).

**Marine transport (IMDG)**

**14.1. UN number:** UN 1263  
**14.2. UN proper shipping name:** Paint  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** III  
Hazard label: 3



Marine pollutant: Yes  
Limited quantity: 5 L / 30 kg  
Excepted quantity: E1  
EmS: F-E, S-E

**Other applicable information (marine transport)**

Viscous substance - excepted quantity if in containers with a capacity up to 30 l (subsection 2.3.2.5 IMDG Code).

**Air transport (ICAO-TI/IATA-DGR)**

**14.1. UN number:** UN 1263  
**14.2. UN proper shipping name:** Paint  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** III  
Hazard label: 3



Limited quantity Passenger: 10 L

## ESKANOL PU 23 COMP. A

Revision date: 23.08.2022

Product code: 00359-1309

Page 11 of 13

Passenger LQ:	Y344	
Excepted quantity:	E1	
IATA-packing instructions - Passenger:		355
IATA-max. quantity - Passenger:		60 L
IATA-packing instructions - Cargo:		366
IATA-max. quantity - Cargo:		220 L

### 14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: Yes



### 14.6. Special precautions for user

Handle in accordance with good industrial hygiene and safety practice.

### 14.7. Maritime transport in bulk according to IMO instruments

The transport takes place only in approved and appropriate packaging.

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

2004/42/EC (VOC):	< 500 g/l
Information according to 2012/18/EU (SEVESO III):	P5c FLAMMABLE LIQUIDS

#### National regulatory information

Employment restrictions:	Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.
--------------------------	---

Water hazard class (D):	2 - obviously hazardous to water
-------------------------	----------------------------------

### 15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

## SECTION 16: Other information

### Changes

This data sheet contains changes from the previous version in section(s): 2,4,6,7,8,9,10,11,12,14,15.

### Abbreviations and acronyms

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route  
RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses  
ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure  
IMDG = International Maritime Code for Dangerous Goods  
IATA/ICAO = International Air Transport Association / International Civil Aviation Organization  
MARPOL = International Convention for the Prevention of Pollution from Ships  
IBC-Code = International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk

## ESKANOL PU 23 COMP. A

Revision date: 23.08.2022

Product code: 00359-1309

Page 12 of 13

GHS = Globally Harmonized System of Classification and Labelling of Chemicals  
 REACH = Registration, Evaluation, Authorization and Restriction of Chemicals  
 CAS = Chemical Abstract Service  
 EN = European norm  
 ISO = International Organization for Standardization  
 DIN = Deutsche Industrie Norm  
 PBT = Persistent Bioaccumulative and Toxic  
 vPvB = Very Persistent and very Bio-accumulative  
 LD = Lethal dose  
 LC = Lethal concentration  
 EC = Effect concentration  
 IC = Median immobilisation concentration or median inhibitory concentration

### Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Flam. Liq. 3; H226	On basis of test data
Skin Irrit. 2; H315	Calculation method
Eye Irrit. 2; H319	Calculation method
Skin Sens. 1; H317	Calculation method
STOT SE 3; H335	Calculation method
STOT SE 3; H336	Calculation method
STOT RE 2; H373	Calculation method
Aquatic Chronic 2; H411	
Aquatic Chronic 3; H412	Calculation method

### Relevant H and EUH statements (number and full text)

H226	Flammable liquid and vapour.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.
EUH071	Corrosive to the respiratory tract.

### Further Information

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product(s) and is based on the present



## Safety Data Sheet

according to UK REACH Regulation



### ESKANOL PU 23 COMP. A

Revision date: 23.08.2022

Product code: 00359-1309

Page 13 of 13

level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

(n.a. = not applicable; n.d. = not determined)

---

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*