



# Safety Data Sheet

according to UK REACH Regulation

## TIP TOP REMACOAT A-80 HP POLY

Revision date: 17.12.2024

Product code: 00359-1093

Page 2 of 11

### Pictograms:



### Hazard statements

H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.

### Precautionary statements

P280	Wear protective gloves/protective clothing/eye protection/face protection.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P301+P330+P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P308+P311	IF exposed or concerned: Call a POISON CENTER/doctor.
P405	Store locked up.
P273	Avoid release to the environment.

### 2.3. Other hazards

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

#### Chemical characterization

Mixture of organic amines

#### Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)			
64852-22-8	Glyceryl poly(oxypropylene) triamine			< 30 %
	Skin Irrit. 2, Eye Dam. 1, Aquatic Chronic 3; H315 H318 H412			
9046-10-0	Poly(oxy(methyl-1,2-ethanediyl)),alpha-(2-aminomethylethyl)omega-(2-aminomethylethoxy)-			< 25 %
	Acute Tox. 4, Skin Corr. 1B, Eye Dam. 1, Aquatic Chronic 3; H302 H314 H318 H412			
68479-98-1	Diethylmethylbenzenediamine			< 15 %
	270-877-4	612-130-00-0	01-2119486805-25	
	Acute Tox. 4, Acute Tox. 4, Eye Irrit. 2, STOT RE 2, Aquatic Acute 1, Aquatic Chronic 1; H312 H302 H319 H373 H400 H410			
106264-79-3	6-Methyl-2,4-bis(methylthio)phenylene-1,3-diamine			< 5 %
	403-240-8	612-113-00-8	01-2119943036-42	
	Acute Tox. 4, Skin Sens. 1, Aquatic Acute 1, Aquatic Chronic 1; H302 H317 H400 H410			
105-76-0	Dibutyl maleate			< 1 %
	203-328-4		01-2119523581-45	
	Skin Sens. 1, STOT RE 2, Aquatic Acute 1; H317 H373 H400			

Full text of H and EUH statements: see section 16.

## Safety Data Sheet

according to UK REACH Regulation

### TIP TOP REMACOAT A-80 HP POLY

Revision date: 17.12.2024

Product code: 00359-1093

Page 3 of 11

#### Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
9046-10-0		Poly(oxy(methyl-1,2-ethanediyl)),alpha-(2-aminomethylethyl)omega-(2-aminomethylethoxy)-	< 25 %
		dermal: LD50 = 2090 mg/kg; oral: LD50 = 475 mg/kg	
68479-98-1	270-877-4	Diethylmethylbenzenediamine	< 15 %
		dermal: LD50 = > 2000 mg/kg; oral: LD50 = 598 mg/kg	
106264-79-3	403-240-8	6-Methyl-2,4-bis(methylthio)phenylene-1,3-diamine	< 5 %
		dermal: LD50 = > 2000 mg/kg; oral: LD50 = 1515 mg/kg	
105-76-0	203-328-4	Dibutyl maleate	< 1 %
		Aquatic Acute 1; H400: M=1	

#### SECTION 4: First aid measures

##### 4.1. Description of first aid measures

###### General information

- Remove contaminated soaked clothing immediately.
- Consult a physician.
- Take away from danger area and lay down affected person.

###### After inhalation

- Move to fresh air in case of accidental inhalation of vapours or decomposition products.
- In the event of symptoms refer for medical treatment.

###### After contact with skin

- In case of contact with skin wash off immediately with plenty of water.
- Consult a physician.

###### After contact with eyes

- Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.
- Consult (eye) doctor immediately.

###### After ingestion

- Do not induce vomiting.
- Rinse out mouth and give plenty of water to drink.
- Never give anything by mouth to an unconscious person.
- Induce vomiting only upon the advice of a physician.
- Summon a doctor immediately.

##### 4.2. Most important symptoms and effects, both acute and delayed

- Harmful if swallowed.
- Causes severe skin burns and eye damage.
- May cause an allergic skin reaction.
- May cause damage to organs through prolonged or repeated exposure.

##### 4.3. Indication of any immediate medical attention and special treatment needed

- Treat symptoms.

#### SECTION 5: Firefighting measures

##### 5.1. Extinguishing media

###### Suitable extinguishing media

- Foam, carbon dioxide (CO<sub>2</sub>), dry chemical, water-spray.

###### Unsuitable extinguishing media

- Full water jet

##### 5.2. Special hazards arising from the substance or mixture

- Fire may produce:



## Safety Data Sheet

according to UK REACH Regulation

### TIP TOP REMACOAT A-80 HP POLY

Revision date: 17.12.2024

Product code: 00359-1093

Page 4 of 11

carbon monoxide (CO), carbon dioxide (CO<sub>2</sub>) and nitrogen oxides (NO<sub>x</sub>)

#### **5.3. Advice for firefighters**

Wear self-contained breathing apparatus and protective suit.

#### **Additional information**

Do not release chemically contaminated water into drains, soil or surface waters. Sufficient measures must be taken to retain water used for extinguishing.

Cool containers at risk with water spray jet.

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

### **SECTION 6: Accidental release measures**

#### **6.1. Personal precautions, protective equipment and emergency procedures**

##### **General advice**

Ensure adequate ventilation.

Keep away noninvolved persons.

##### **For non-emergency personnel**

Do not breathe vapours.

Avoid contact with skin, eyes and clothing.

##### **For emergency responders**

In case of vapour formation use respirator.

Use personal protective clothing.

#### **6.2. Environmental precautions**

Do not discharge into the drains/surface waters/ground water.

#### **6.3. Methods and material for containment and cleaning up**

##### **For containment**

Prevent spread over a wide area (e.g. by containment or oil barriers).

##### **For cleaning up**

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder).

Shovel into suitable container for disposal.

#### **6.4. Reference to other sections**

Observe protective instructions (see Sections 7 and 8).

Information for disposal see section 13.

### **SECTION 7: Handling and storage**

#### **7.1. Precautions for safe handling**

##### **Advice on safe handling**

Keep container tightly closed.

Avoid contact with the skin and the eyes.

Use only in well-ventilated areas.

Do not breathe vapours or spray mist.

##### **Advice on protection against fire and explosion**

Keep away from heat and sources of ignition.

No special protective measures against fire required.

##### **Advice on general occupational hygiene**

Avoid contact with eyes and skin.

Wash hands before breaks and immediately after handling the product.

When using do not eat, drink or smoke.

Remove and wash contaminated clothes before re-use.

Do not breathe vapours or spray mist.

#### **7.2. Conditions for safe storage, including any incompatibilities**



## Safety Data Sheet

according to UK REACH Regulation

### TIP TOP REMACOAT A-80 HP POLY

Revision date: 17.12.2024

Product code: 00359-1093

Page 5 of 11

#### Requirements for storage rooms and vessels

Keep container tightly closed in a dry, cool and well-ventilated place.

#### Hints on joint storage

Incompatible with acids.

#### Further information on storage conditions

Keep away from food, drink and animal feeding stuffs.

#### 7.3. Specific end use(s)

Resin component for 2K coating system

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

##### Additional advice on limit values

This product does not contain any substances for which a Workplace Exposure Limit has been set in concentrations above the limits.

#### 8.2. Exposure controls

##### Appropriate engineering controls

Ensure adequate ventilation, especially in confined areas.

##### Individual protection measures, such as personal protective equipment

##### Eye/face protection

Eye wash bottle with pure water (EN 15154).

Tightly fitting goggles (EN 166).

##### Hand protection

Chemical protective gloves made of nitrile, nitrile/cotton, butyl or neoprene, with a minimum thickness of 0.7 mm, permeation time of approx. 480 minutes.

This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.

Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

Pls. find examples in the protective gloves database under: <http://bestglove.com/site/chemrest/>

##### Skin protection

Long sleeved clothing (DIN EN ISO 6530)

##### Respiratory protection

In case of insufficient ventilation wear suitable respiratory equipment (gas filter type A) (EN 14387).

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Physical state:	Viscous liquid
Colour:	Various
Odour:	Amine like

##### Changes in the physical state

Melting point/freezing point:	n.d.
Boiling point or initial boiling point and boiling range:	n.d.
Sublimation point:	n.a.
Softening point:	n.d.
Flash point:	> 100 °C

##### Flammability

**Safety Data Sheet**

according to UK REACH Regulation

**TIP TOP REMACOAT A-80 HP POLY**

Revision date: 17.12.2024

Product code: 00359-1093

Page 6 of 11

Solid/liquid: n.a.

**Explosive properties**

The product is not explosive.

Lower explosion limits: n.d.

Upper explosion limits: n.d.

Auto-ignition temperature: n.d.

**Self-ignition temperature**

Solid: n.a.

Gas: n.a.

Decomposition temperature: n.d.

pH-Value: n.d.

Viscosity / dynamic: 1200 - 1800 mPa·s  
(at 25 °C)

Viscosity / kinematic: n.d.

Flow time: n.d.

Water solubility: Immiscible

**Solubility in other solvents**

n.d.

Partition coefficient n-octanol/water: n.d.

Vapour pressure: n.d.

Density (at 25 °C): 1,02 - 1,06 g/cm<sup>3</sup>

Bulk density: n.a.

Relative vapour density: n.d.

**9.2. Other information****Information with regard to physical hazard classes**

Oxidizing properties

Not oxidising.

**Other safety characteristics**

Solvent separation test: 0 %

Solvent content: 0 %

Evaporation rate: n.d.

**Further Information**

No data available

**SECTION 10: Stability and reactivity****10.1. Reactivity**

No decomposition if stored and applied as directed.

**10.2. Chemical stability**

Stable under normal conditions.

**10.3. Possibility of hazardous reactions**

Reactions with strong acids.

**10.4. Conditions to avoid**

To avoid thermal decomposition, do not overheat.

**10.5. Incompatible materials**

Acids.



## Safety Data Sheet

according to UK REACH Regulation

### TIP TOP REMACOAT A-80 HP POLY

Revision date: 17.12.2024

Product code: 00359-1093

Page 7 of 11

#### **10.6. Hazardous decomposition products**

No hazardous decomposition products known.

Fire may produce:

Carbon monoxide (CO), carbon dioxide (CO<sub>2</sub>) and nitrogen oxides (NO<sub>x</sub>)

### **SECTION 11: Toxicological information**

#### **11.1. Information on hazard classes as defined in GB CLP Regulation**

##### **Acute toxicity**

Harmful if swallowed.

No toxicological data available.

ATEmix/oral: approx. 1200 mg/kg

ATEmix/dermal: > 2000 mg/kg

ATEmix/inhalation: > 20 mg/l

##### **Irritation and corrosivity**

Serious eye damage/eye irritation: Skin corrosion/irritation: Causes severe skin burns and eye damage.

##### **Sensitising effects**

May cause an allergic skin reaction. (6-Methyl-2,4-bis(methylthio)phenylene-1,3-diamine; Dibutyl maleate)

##### **Carcinogenic/mutagenic/toxic effects for reproduction**

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

##### **STOT-single exposure**

Based on available data, the classification criteria are not met.

##### **STOT-repeated exposure**

May cause damage to organs through prolonged or repeated exposure. (Diethylmethylbenzenediamine )

##### **Aspiration hazard**

Based on available data, the classification criteria are not met.

##### **Additional information on tests**

Classification in compliance with the assessment procedure specified in the Regulation (EC) no 1272/2008.

#### **11.2. Information on other hazards**

##### **Endocrine disrupting properties**

No data available

##### **Other information**

Repeated or prolonged exposure may cause skin irritation and dermatitis, due to degreasing properties of the product.

Inhalation of vapours in high concentration may cause irritation of respiratory system.

After single absorption, risk of blood damage (methaemoglobinaemia).

### **SECTION 12: Ecological information**

#### **12.1. Toxicity**

Ecological data are not available.

Toxic to aquatic life with long lasting effects.

#### **12.2. Persistence and degradability**

Not readily biodegradable.

#### **12.3. Bioaccumulative potential**

No data available

#### **12.4. Mobility in soil**

No data available

#### **12.5. Results of PBT and vPvB assessment**

## Safety Data Sheet

according to UK REACH Regulation

### TIP TOP REMACOAT A-80 HP POLY

Revision date: 17.12.2024

Product code: 00359-1093

Page 8 of 11

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

#### **12.6. Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

#### **12.7. Other adverse effects**

Severe hazard to waters.

#### **Further information**

Do not flush into surface water or sanitary sewer system.

### SECTION 13: Disposal considerations

#### **13.1. Waste treatment methods**

##### **Disposal recommendations**

Where possible recycling is preferred to disposal.

Can be incinerated, when in compliance with local regulations.

##### **List of Wastes Code - residues/unused products**

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

##### **Contaminated packaging**

Empty containers should be taken for local recycling, recovery or waste disposal.

Contaminated packagings are to be treated like the product itself.

Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.

### SECTION 14: Transport information

#### **Land transport (ADR/RID)**

##### **14.1. UN number or ID number:**

UN 2735

##### **14.2. UN proper shipping name:**

AMINES, LIQUID, CORROSIVE, N.O.S. (Polyoxypropylene diamine)

##### **14.3. Transport hazard class(es):**

8

##### **14.4. Packing group:**

II

Hazard label:

8



Classification code:

C7

Limited quantity:

1 L / 30 kg

Excepted quantity:

E2

Transport category:

2

Hazard No:

80

Tunnel restriction code:

E

#### **Inland waterways transport (ADN)**

##### **14.1. UN number or ID number:**

UN 2735

##### **14.2. UN proper shipping name:**

AMINES, LIQUID, CORROSIVE, N.O.S. (Polyoxypropylene diamine)

##### **14.3. Transport hazard class(es):**

8

##### **14.4. Packing group:**

II

Hazard label:

8

## Safety Data Sheet

according to UK REACH Regulation

### TIP TOP REMACOAT A-80 HP POLY

Revision date: 17.12.2024

Product code: 00359-1093

Page 9 of 11



Classification code: C7  
Limited quantity: 1 L / 30 kg  
Excepted quantity: E2

#### Marine transport (IMDG)

**14.1. UN number or ID number:** UN 2735  
**14.2. UN proper shipping name:** AMINES, LIQUID, CORROSIVE, N.O.S. (Polyoxypropylene diamine)  
**14.3. Transport hazard class(es):** 8  
**14.4. Packing group:** II  
Hazard label: 8



Marine pollutant: Yes  
Limited quantity: 1 L / 30 kg  
Excepted quantity: E2  
EmS: F-A, S-B

#### Air transport (ICAO-TI/IATA-DGR)

**14.1. UN number or ID number:** UN 2735  
**14.2. UN proper shipping name:** AMINES, LIQUID, CORROSIVE, N.O.S. (Polyoxypropylene diamine)  
**14.3. Transport hazard class(es):** 8  
**14.4. Packing group:** II  
Hazard label: 8



Limited quantity Passenger: 0.5 L  
Passenger LQ: Y840  
Excepted quantity: E2  
IATA-packing instructions - Passenger: 851  
IATA-max. quantity - Passenger: 1 L  
IATA-packing instructions - Cargo: 855  
IATA-max. quantity - Cargo: 30 L

#### 14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: Yes



#### 14.6. Special precautions for user

Handle in accordance with good industrial hygiene and safety practice.

#### 14.7. Maritime transport in bulk according to IMO instruments

The transport takes place only in approved and appropriate packaging.

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

##### EU regulatory information



## Safety Data Sheet

according to UK REACH Regulation

### TIP TOP REMACOAT A-80 HP POLY

Revision date: 17.12.2024

Product code: 00359-1093

Page 10 of 11

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 75

Directive 2004/42/EC on VOC in  
paints and varnishes: 0 %Information according to Directive  
2012/18/EU (SEVESO III): E2 Hazardous to the Aquatic Environment

#### National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water hazard class (D): 3 - highly hazardous to water

#### 15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

### SECTION 16: Other information

#### Changes

This data sheet contains changes from the previous version in section(s): 1,2,6,7,8,10,11,12,13,14,15,16.

#### Abbreviations and acronyms

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route

RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses

ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure

IMDG = International Maritime Code for Dangerous Goods

IATA/ICAO = International Air Transport Association / International Civil Aviation Organization

MARPOL = International Convention for the Prevention of Pollution from Ships

IBC-Code = International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

REACH = Registration, Evaluation, Authorization and Restriction of Chemicals

CAS = Chemical Abstract Service

EN = European norm

ISO = International Organization for Standardization

DIN = Deutsche Industrie Norm

PBT = Persistent Bioaccumulative and Toxic

vPvB = Very Persistent and very Bio-accumulative

LD = Lethal dose

LC = Lethal concentration

EC = Effect concentration

IC = Median immobilisation concentration or median inhibitory concentration

#### Relevant H and EUH statements (number and full text)

H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H373	May cause damage to organs through prolonged or repeated exposure.

**Safety Data Sheet**

according to UK REACH Regulation

**TIP TOP REMACOAT A-80 HP POLY**

Revision date: 17.12.2024

Product code: 00359-1093

Page 11 of 11

H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

**Further Information**

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product(s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

(n.a. = not applicable; n.d. = not determined)

---

*(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*