

ESKANOL EF HÄRTER

Revision: 29.09.2025

Product code: 00359-1293

Page 2 of 11

P280	Wear protective gloves/protective clothing/eye protection/face protection.
P301+P330+P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER/doctor.

2.3. Other hazards

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605

Vapours may form explosive mixture with air.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Hardener based on aliphatic polyamines

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
100-51-6	Benzyl alcohol			< 45 %
	202-859-9	603-057-00-5	01-2119492630-38	
	Acute Tox. 4, Eye Irrit. 2, Skin Sens. 1B; H302 H319 H317			
38294-64-3	4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with 3-aminomethyl-3,5,5-trimethylcyclohexylamine			< 40 %
	500-101-4		01-2119965165-33	
	Skin Corr. 1B, Eye Dam. 1, Skin Sens. 1, Aquatic Chronic 3; H314 H318 H317 H412			
113930-69-1	4,4'-isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with m-phenylenebis(methylamine)			< 15 %
	500-302-7		01-2119965162-39	
	Skin Corr. 1B, Eye Dam. 1, Skin Sens. 1, Aquatic Chronic 2; H314 H318 H317 H411			
69-72-7	Salicylic acid			< 3 %
	200-712-3	607-732-00-5	01-2119486984-17	
	Repr. 2, Acute Tox. 4, Eye Dam. 1; H361d H302 H318			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
100-51-6	202-859-9	Benzyl alcohol	< 45 %
		oral: ATE 1200 mg/kg	
69-72-7	200-712-3	Salicylic acid	< 3 %
		dermal: LD50 = > 2000 mg/kg; oral: LD50 = 891 mg/kg	

SECTION 4: First aid measures

ESKANOL EF HÄRTER

Revision: 29.09.2025

Product code: 00359-1293

Page 3 of 11

4.1. Description of first aid measures

General information

Remove contaminated soaked clothing immediately.
In the event of persistent symptoms receive medical treatment.

After inhalation

Move to fresh air in case of accidental inhalation of vapours or decomposition products.
In the event of symptoms refer for medical treatment.

After contact with skin

Wash off immediately with soap and plenty of water.
Consult a doctor if skin irritation persists.

After contact with eyes

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.
Seek medical treatment by eye specialist.

After ingestion

Do not induce vomiting.
Rinse mouth.
Never give anything by mouth to an unconscious person.
Summon a doctor immediately.
Induce vomiting only upon the advice of a physician.

4.2. Most important symptoms and effects, both acute and delayed

Harmful if inhaled.
Causes severe skin burns and eye damage.
May cause an allergic skin reaction.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Alcohol-resistant foam, dry chemical, carbon dioxide (CO₂), water-spray.
Fire-extinguishing activities according to surrounding.

Unsuitable extinguishing media

Full water jet.

5.2. Special hazards arising from the substance or mixture

Fire may produce:
Carbon monoxide (CO), carbon dioxide (CO₂) and nitrogen oxides (NO_x).

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective suit.

Additional information

Vapours are heavier than air and spread along ground.
The vapour/air mixture is explosive, even in empty, uncleaned receptacles.
Cool containers at risk with water spray jet.
Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Ensure adequate ventilation.
Remove persons to safety.

ESKANOL EF HÄRTER

Revision: 29.09.2025

Product code: 00359-1293

Page 4 of 11

Keep away sources of ignition.

For non-emergency personnel

Avoid contact with skin, eyes and clothing.
Do not breathe vapours.

For emergency responders

In case of vapour formation use respirator.
Use personal protective clothing.

6.2. Environmental precautions

Do not discharge into the drains/surface waters/groundwater.
Do not discharge into the subsoil/soil.

6.3. Methods and material for containment and cleaning up

For containment

Prevent spread over a wide area (e.g. by containment or oil barriers).

For cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder).
Shovel into suitable container for disposal.
Clean contaminated surface thoroughly.

6.4. Reference to other sections

Observe protective instructions (see Sections 7 and 8).
Information for disposal look up chapter 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Keep container tightly closed.
Use only in thoroughly ventilated areas.
Avoid contact with skin, eyes and clothing.

Advice on protection against fire and explosion

No special protective measures against fire required.

Advice on general occupational hygiene

Do not inhale vapours.
Wash hands before breaks and immediately after handling the product.
When using do not eat, drink or smoke.
Avoid contact with skin, eyes and clothing.
Remove and wash contaminated clothes before re-use.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a dry, cool and well-ventilated place.
Pay attention to anti-explosion rules.
Protect against direct sun radiation.
Recommended storage temperature: 10°C - 30°C

Hints on joint storage

Incompatible with:
Oxidizing agents, Acids and bases.

Further information on storage conditions

Keep away from food, drink and animal feeding stuffs.

7.3. Specific end use(s)

Hardener

SECTION 8: Exposure controls/personal protection

ESKANOL EF HÄRTER

Revision: 29.09.2025

Product code: 00359-1293

Page 5 of 11

8.1. Control parameters**Additional advice on limit values**

No data available

8.2. Exposure controls**Appropriate engineering controls**

Ensure adequate ventilation, especially in confined areas.

Individual protection measures, such as personal protective equipment**Eye/face protection**

Tightly fitting goggles (EN 166).

Eye wash bottle with pure water (EN 15154).

Hand protection

Protective gloves resistant to chemicals made off viton , Minimum coat thickness 0,7 mm, Permeation resistance (wear duration) approx. 30 minutes, i.e. protective glove <Vitoject 890> made by www.kcl.de.

Splash protection: Protective gloves resistant to chemicals made off butyl, Minimum coat thickness 0,7 mm, Permeation resistance (wear duration) approx. 480 minutes, i.e. protective glove <Butoject 898> made by www.kcl.de.

This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.

Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

Pls. find examples in the protective gloves database under: <http://bestglove.com/site/chemrest/>**Skin protection**

Long sleeved clothing (DIN EN ISO 6530)

Respiratory protection

In case of insufficient ventilation wear suitable respiratory equipment (gas filter type A) (EN 14387).

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state:	Liquid
Colour:	Colourless
Odour:	Amine like

Test method**Changes in the physical state**

Melting point/freezing point:	n. d.
Boiling point or initial boiling point and boiling range:	n. d.
Sublimation point:	n.a.
Softening point:	n. d.
Flash point:	94 °C Calculated

Flammability

Solid/liquid:	n.a.
---------------	------

Explosive properties

The product is not explosive.

Lower explosion limits:	n. d.
Upper explosion limits:	n. d.
Auto-ignition temperature:	n. d.

Self-ignition temperature

ESKANOL EF HÄRTER

Revision: 29.09.2025

Product code: 00359-1293

Page 6 of 11

Solid:	n.a.
Gas:	n.a.
Decomposition temperature:	n. d.
pH-Value (at 20 °C):	n. d.
Viscosity / dynamic: (at 23 °C)	280 - 420 mPa·s ISO 2884
Viscosity / kinematic:	n. d.
Flow time:	n. d.
Water solubility: (at 20 °C)	n. d.
Solubility in other solvents n. d.	
Partition coefficient n-octanol/water:	n. d.
Vapour pressure:	n. d.
Density (at 23 °C):	approx. 1,05 g/cm ³ ISO 2811
Bulk density:	n.a.
Relative vapour density:	n. d.

9.2. Other information

Information with regard to physical hazard classes

Sustained combustibility: Sustained combustibility

Oxidizing properties
Not oxidising.

Other safety characteristics

Solvent separation test: n. d.

Solvent content: 0 %

Evaporation rate: n. d.

Further Information

No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

No decomposition if stored and applied as directed.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Reactions with acids, alkalies and oxidising agents.

10.4. Conditions to avoid

To avoid thermal decomposition, do not overheat.

Protect against direct sun radiation.

10.5. Incompatible materials

Oxidizing agents, Acids and bases.

10.6. Hazardous decomposition products

No known hazardous decomposition products.

Fire may produce:

Carbon monoxide (CO), carbon dioxide (CO₂) and nitrogen oxides (NO_x)

ESKANOL EF HÄRTER

Revision: 29.09.2025

Product code: 00359-1293

Page 7 of 11

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Based on available data, the classification criteria are not met.

No toxicological data available.

ATEmix/oral: > 2000 mg/kg

ATEmix/dermal: > 2000 mg/kg

ATEmix/inhalation: > 20 mg/l/4 h (vapour)

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

Irritation and corrosivity

Skin corrosion/irritation: Causes severe skin burns and eye damage.

Serious eye damage/eye irritation: Causes serious eye damage.

Sensitising effects

May cause an allergic skin reaction. (Benzyl alcohol ; 4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with 3-aminomethyl-3,5,5-trimethylcyclohexylamine; 4,4'-isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with m-phenylenebis(methylamine))

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Additional information on tests

Classification in compliance with the assessment procedure specified in the Regulation (EC) no 1272/2008.

11.2. Information on other hazards

Endocrine disrupting properties

No data available

SECTION 12: Ecological information

12.1. Toxicity

Ecological data are not available.

Harmful to aquatic life with long lasting effects.

12.2. Persistence and degradability

Not readily biodegradable.

12.3. Bioaccumulative potential

No data available

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

ESKANOL EF HÄRTER

Revision: 29.09.2025

Product code: 00359-1293

Page 8 of 11

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

Hazard to waters.

Further information

Do not flush into surface water or sanitary sewer system.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Can be incinerated, when in compliance with local regulations.
Where possible recycling is preferred to disposal.

List of Wastes Code - residues/unused products

080411 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); adhesive and sealant sludges containing organic solvents or other hazardous substances; hazardous waste

Contaminated packaging

Contaminated packagings are to be treated like the product itself.
Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.
Packaging that cannot be cleaned should be disposed of like the product.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number:

UN 2735

14.2. UN proper shipping name:

POLYAMINES, LIQUID, CORROSIVE, N.O.S.
(3-Aminomethyl-3,5,5-trimethylcyclohexylamine, Xylylenediamine)

14.3. Transport hazard class(es):

8

14.4. Packing group:

II

Hazard label:

8



Classification code:

C7

Special Provisions:

274

Limited quantity:

1 L / 30 kg

Excepted quantity:

E2

Transport category:

2

Hazard No:

80

Tunnel restriction code:

E

Inland waterways transport (ADN)

14.1. UN number or ID number:

UN 2735

14.2. UN proper shipping name:

POLYAMINES, LIQUID, CORROSIVE, N.O.S.
(3-Aminomethyl-3,5,5-trimethylcyclohexylamine, Xylylenediamine)

14.3. Transport hazard class(es):

8

14.4. Packing group:

II

Hazard label:

8

ESKANOL EF HÄRTER

Revision: 29.09.2025

Product code: 00359-1293

Page 9 of 11



Classification code: C7
 Special Provisions: 274
 Limited quantity: 1 L / 30 kg
 Excepted quantity: E2

Marine transport (IMDG)

14.1. UN number or ID number: UN 2735
14.2. UN proper shipping name: POLYAMINES, LIQUID, CORROSIVE, N.O.S. (Isophorone diamine, xylylendiamine)
14.3. Transport hazard class(es): 8
14.4. Packing group: II
 Hazard label: 8



Marine pollutant: No
 Special Provisions: 274
 Limited quantity: 1 L / 30 kg
 Excepted quantity: E2
 EmS: F-A, S-B
 Segregation group: 18 - alkalis

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 2735
14.2. UN proper shipping name: POLYAMINES, LIQUID, CORROSIVE, N.O.S. (Isophorone diamine, xylylendiamine)
14.3. Transport hazard class(es): 8
14.4. Packing group: II
 Hazard label: 8



Special Provisions: A3 A803
 Limited quantity Passenger: 0.5 L
 Passenger LQ: Y840
 Excepted quantity: E2
 IATA-packing instructions - Passenger: 851
 IATA-max. quantity - Passenger: 1 L
 IATA-packing instructions - Cargo: 855
 IATA-max. quantity - Cargo: 30 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Handle in accordance with good industrial hygiene and safety practice.

14.7. Maritime transport in bulk according to IMO instruments

The transport takes place only in approved and appropriate packaging.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

ESKANOL EF HÄRTER

Revision: 29.09.2025

Product code: 00359-1293

Page 10 of 11

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 75

Directive 2004/42/EC on VOC in paints and varnishes: < 45 %

Information according to Directive 2012/18/EU (SEVESO III): Not subject to 2012/18/EU (SEVESO III)

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water hazard class (D): 2 - obviously hazardous to water

15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 2,9,11,12.

Abbreviations and acronyms

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route
 RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses
 ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure
 IMDG = International Maritime Code for Dangerous Goods
 IATA/ICAO = International Air Transport Association / International Civil Aviation Organization
 MARPOL = International Convention for the Prevention of Pollution from Ships
 IBC-Code = International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk

GHS = Globally Harmonized System of Classification and Labelling of Chemicals
 REACH = Registration, Evaluation, Authorization and Restriction of Chemicals
 CAS = Chemical Abstract Service
 EN = European norm
 ISO = International Organization for Standardization
 DIN = Deutsche Industrie Norm
 PBT = Persistent Bioaccumulative and Toxic
 vPvB = Very Persistent and very Bio-accumulative
 LD = Lethal dose
 LC = Lethal concentration
 EC = Effect concentration
 IC = Median immobilisation concentration or median inhibitory concentration

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Skin Corr. 1B; H314	Calculation method
Eye Dam. 1; H318	Calculation method
Skin Sens. 1; H317	Calculation method
Aquatic Chronic 3; H412	Calculation method

ESKANOL EF HÄRTER

Revision: 29.09.2025

Product code: 00359-1293

Page 11 of 11

Relevant H and EUH statements (number and full text)

H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H361d	Suspected of damaging the unborn child.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Further Information

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product (s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

"(n.a. = not applicable; n.d. = not determined)"

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)