

Safety Data Sheet

according to Regulation (EC) No 1907/2006

TIP TOP PRIMER PR 805

Revision: 25.03.2026

Product code: 00156-0546

Page 1 of 12

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

TIP TOP PRIMER PR 805

Art.-No.

525 2422, 525 2431, 525 2732

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Primer Coat

1.3. Details of the supplier of the safety data sheet

Company name: REMA TIP TOP AG

Street: Gruber Strasse 65

Place: D-85586 Poing

Telephone: +49 (0) 8121 / 707 - 100

Responsible Department: Responsible for the safety data sheet: sds@gbk-ingelheim.de

1.4. Emergency telephone number:

INTERNATIONAL: +49 - (0) 6132 - 84463, GBK GmbH (24h - 7d/w - 365d/a)
Public Poisons Information Line: +353 (0) 1 809 2166 (8am-10pm 7 days a week)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Flam. Liq. 2; H225

Carc. 2; H351

Acute Tox. 4; H332

Skin Irrit. 2; H315

Eye Irrit. 2; H319

STOT SE 3; H335 H336

STOT RE 2; H373

Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling

4-Methylpentan-2-one

Reaction mass of ethylbenzene and xylene

Butanone

Signal word:

Danger

Pictograms:



Hazard statements

H225	Highly flammable liquid and vapour.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

TIP TOP PRIMER PR 805

Revision: 25.03.2026

Product code: 00156-0546

Page 2 of 12

H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H373	May cause damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.

Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P243	Take action to prevent static discharges.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P403+P235	Store in a well-ventilated place. Keep cool.

2.3. Other hazards

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605

Vapours may form explosive mixture with air.

SECTION 3: Composition/information on ingredients**3.2. Mixtures****Chemical characterization**

Preparation with polymers in xylene and 4-methylpentan-2-one

Hazardous components

CAS No	Chemical name	Quantity		
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
108-10-1	4-Methylpentan-2-one			< 50 %
	203-550-1	606-004-00-4	01-2119473980-30	
	Flam. Liq. 2, Carc. 2, Acute Tox. 4, Eye Irrit. 2, STOT SE 3, STOT SE 3; H225 H351 H332 H319 H335 H336 EUH066			
	Reaction mass of ethylbenzene and xylene			< 25 %
	905-588-0		01-2119488216-32	
	Flam. Liq. 3, Acute Tox. 4, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, STOT SE 3, STOT RE 2, Asp. Tox. 1; H226 H332 H312 H315 H319 H335 H373 H304			
78-93-3	Butanone			< 5 %
	201-159-0	606-002-00-3	01-2119457290-43	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066			
1314-13-2	Zinc oxide			< 1 %
	215-222-5	030-013-00-7	01-2119463881-32	
	Aquatic Acute 1, Aquatic Chronic 1; H400 H410			
108-88-3	Toluene			< 1 %
	203-625-9	601-021-00-3	01-2119471310-51	
	Flam. Liq. 2, Repr. 2, Skin Irrit. 2, Eye Irrit. 2, STOT SE 3, STOT RE 2, Asp. Tox. 1, Aquatic Chronic 3; H225 H361d H315 H319 H336 H373 H304 H412			

Full text of H and EUH statements: see section 16.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

TIP TOP PRIMER PR 805

Revision: 25.03.2026

Product code: 00156-0546

Page 3 of 12

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
108-10-1	203-550-1	4-Methylpentan-2-one	< 50 %
		inhalation: ATE 11 mg/l (vapours)	
	905-588-0	Reaction mass of ethylbenzene and xylene	< 25 %
		inhalation: ATE = 11 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: ATE = 1100 mg/kg STOT RE 2; H373: >= 10 - 100	
1314-13-2	215-222-5	Zinc oxide	< 1 %
		Aquatic Acute 1; H400: M=1 Aquatic Chronic 1; H410: M=1	
108-88-3	203-625-9	Toluene	< 1 %
		inhalation: LC50 = 49 mg/l (vapours); dermal: LD50 = 12200 mg/kg	

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove contaminated soaked clothing immediately.

Symptoms of poisoning may not appear for several hours. Keep under medical supervision for at least 48 hours.

In the event of persistent symptoms receive medical treatment.

Take away from danger area and lay down affected person.

After inhalation

Move to fresh air in case of accidental inhalation of vapours.

Seek medical treatment immediately.

After contact with skin

Wash off with soap and plenty of water.

Possible risk of resorption through skin.

If a person feels unwell or symptoms of skin irritation appear, consult a physician.

After contact with eyes

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

Seek medical treatment by eye specialist.

After ingestion

Do not induce vomiting.

Rinse mouth.

Never give anything by mouth to an unconscious person.

Summon a doctor immediately.

Induce vomiting only upon the advice of a physician.

4.2. Most important symptoms and effects, both acute and delayed

Harmful if inhaled.

Causes skin irritation.

Causes serious eye irritation.

May cause respiratory irritation.

May cause drowsiness or dizziness.

Suspected of causing cancer.

May cause damage to organs through prolonged or repeated exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptoms.

SECTION 5: Firefighting measures

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

TIP TOP PRIMER PR 805

Revision: 25.03.2026

Product code: 00156-0546

Page 4 of 12

5.1. Extinguishing media**Suitable extinguishing media**Foam, carbon dioxide (CO₂), dry chemical, water-spray.**Unsuitable extinguishing media**

Full water jet.

5.2. Special hazards arising from the substance or mixture

Fire may produce:

carbon monoxide and carbon dioxide

Hydrogen chloride (HCl)

5.3. Advice for firefighters

Use breathing apparatus with independent air supply.

Protective suit.

Additional information

Vapours are heavier than air and spread along ground.

The vapour/air mixture is explosive, even in empty, uncleaned receptacles.

Cool containers at risk with water spray jet.

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures****General advice**

Ensure adequate ventilation.

Remove persons to safety.

For non-emergency personnel

Do not breathe vapours.

Avoid contact with skin, eyes and clothing.

For emergency responders

In case of vapour formation use respirator.

Use personal protective clothing.

6.2. Environmental precautions

Do not discharge into the drains/surface waters/groundwater.

Clean contaminated surface thoroughly.

6.3. Methods and material for containment and cleaning up**For containment**

Prevent spread over a wide area (e.g. by containment or oil barriers).

For cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder).

Shovel into suitable container for disposal.

6.4. Reference to other sections

Observe protective instructions (see Sections 7 and 8).

Informations for disposal look up chapter 13.

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

Do not wear contact lenses when handling the product.

Keep container tightly closed.

Vapours are heavier than air and spread along ground.

Keep a good ventilation and air-exhaust at the place of work.

Avoid contact with skin, eyes and clothing.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

TIP TOP PRIMER PR 805

Revision: 25.03.2026

Product code: 00156-0546

Page 5 of 12

Advice on protection against fire and explosion

Keep away from heat and sources of ignition.

Do not smoke.

Take precautionary measures against static discharges.

Pay attention to anti-explosion protection rules: In case of an explosive atmosphere use only explosion-proof equipment.

Advice on general occupational hygiene

Do not inhale vapours.

Wash hands before breaks and immediately after handling the product.

When using do not eat, drink or smoke.

Avoid contact with skin, eyes and clothing.

Remove and wash contaminated clothes before re-use.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a dry, cool and well-ventilated place.

Pay attention to anti-explosion rules.

Hints on joint storage

Incompatible with oxidizing agents.

Further information on storage conditions

Keep away from food, drink and animal feeding stuffs.

7.3. Specific end use(s)

Primer Coat

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

CAS No	Substance	ppm	mg/m ³	fib/cm ³	Category	Origin
100-41-4	Ethylbenzene	100	442		TWA (8 h)	
		200	884		STEL (15 min)	
78-93-3	Methyl ethyl ketone (MEK) (Butan-2-one)	200	600		TWA (8 h)	
		300	900		STEL (15 min)	
108-10-1	Methyl isobutyl ketone (MIBK)	20	83		TWA (8 h)	
		50	208		STEL (15 min)	
13463-67-7	Titanium dioxide, total inhalable dust	-	10		TWA (8 h)	
108-88-3	Toluene	50	192		TWA (8 h)	
		100	384		STEL (15 min)	
1330-20-7	Xylene, mixed isomers	50	221		TWA (8 h)	
		100	442		STEL (15 min)	
1314-13-2	Zinc oxide, fume (Respirable Fraction)	-	2		TWA (8 h)	
		-	10		STEL (15 min)	

Safety Data Sheet

according to Regulation (EC) No 1907/2006

TIP TOP PRIMER PR 805

Revision: 25.03.2026

Product code: 00156-0546

Page 6 of 12

Biological limit values

CAS No	Substance	Parameter	Value	Test material	Sampling time
108-10-1	Methyl isobutyl ketone (MIBK; 4-methylpentan-2-one)	MIBK	1 mg/L	Urine	End of shift
78-93-3	Butan-2-one	Butan-2-one	70 µmol/L	Urine	Post shift
108-88-3	Toluene	Toluene	0.03 mg/L	Urine	End of shift
100-41-4	Ethyl benzene	Mandelic acid and phenylglyoxylic acid	0.7 g/g	Creatinine	End of shift at end of workweek

8.2. Exposure controls

Appropriate engineering controls

Ensure adequate ventilation, especially in confined areas.

Individual protection measures, such as personal protective equipment

Eye/face protection

Tightly fitting goggles (EN 166).
Eye wash bottle with pure water (EN 15154).

Hand protection

Splash protection:
Protective gloves resistant to chemicals made off butyl, Minimum coat thickness 0,7 mm, Permeation resistance (wear duration) > 240 minutes, i.e. protective glove <Butoject 898> made by www.kcl.de.
This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.
Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

Skin protection

Solvent-resistant apron (EN 467).

Respiratory protection

In case of insufficient ventilation wear suitable respiratory equipment (gas filter type A) (EN 14387).

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	Grey
Odour:	Aromatic

Test method

Changes in the physical state

Melting point/freezing point:	n. d.
Boiling point or initial boiling point and boiling range:	n. d.
Sublimation point:	n.a.
Softening point:	n. d.
Pour point:	n. d.
Flash point:	15 °C

Flammability

Solid/liquid:	n.a.
---------------	------

Explosive properties

The product is considered non-explosive; nevertheless explosive vapour/air mixture can be generated.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

TIP TOP PRIMER PR 805

Revision: 25.03.2026

Product code: 00156-0546

Page 7 of 12

Lower explosion limits:	1,4 vol. % (*)
Upper explosion limits:	7,5 vol. % (*)
Auto-ignition temperature:	n. d.
Self-ignition temperature	
Solid:	n.a.
Gas:	n.a.
Decomposition temperature:	n. d.
pH-Value:	n. d.
Viscosity / dynamic:	10 - 300 mPa·s
Viscosity / kinematic: (at 40 °C)	> 20,5 mm ² /s
Flow time:	n. d.
Water solubility: (at 20 °C)	Immiscible
Solubility in other solvents	
n. d.	
Partition coefficient n-octanol/water:	n. d.
Vapour pressure: (at 20 °C)	n. d.
Density (at 20 °C):	0,87 - 0,92 g/cm ³
Bulk density:	n.a.
Relative vapour density:	n. d.

9.2. Other information**Information with regard to physical hazard classes**

Sustained combustibility: Sustained combustibility

Oxidizing properties
Not oxidising.**Other safety characteristics**

Solvent separation test: n. d.

Solvent content: < 75 %

Evaporation rate: n. d.

Further Information

(*) 4-Methylpentan-2-one

SECTION 10: Stability and reactivity**10.1. Reactivity**

No decomposition if stored and applied as directed.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Reactions with oxidising agents.

10.4. Conditions to avoidTo avoid thermal decomposition, do not overheat.
Vapour/air mixtures are explosive at intensive warming.
Heating can release vapours which can be ignited.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

TIP TOP PRIMER PR 805

Revision: 25.03.2026

Product code: 00156-0546

Page 8 of 12

10.5. Incompatible materials

Strong oxidizing agents

10.6. Hazardous decomposition products

No hazardous decomposition products known.

Fire may produce:

Carbon monoxide and carbon dioxide

Hydrogen chloride (HCl)

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Harmful if inhaled.

No toxicological data available.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg

Irritation and corrosivity

Skin corrosion/irritation: Causes skin irritation.

Serious eye damage/eye irritation: Causes serious eye irritation.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Suspected of causing cancer. (4-Methylpentan-2-one)

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

May cause respiratory irritation. (4-Methylpentan-2-one; Reaction mass of ethylbenzene and xylene)

May cause drowsiness or dizziness. (4-Methylpentan-2-one)

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure. (Reaction mass of ethylbenzene and xylene)

Aspiration hazard

Based on available data, the classification criteria are not met.

Practical experience

Classification in compliance with the assessment procedure specified in the Regulation (EC) no 1272/2008.

11.2. Information on other hazards

Endocrine disrupting properties

No data available

Other information

Inhalation of vapours is irritating to the respiratory system, may cause throat pain and cough.

Repeated exposure may cause skin dryness or cracking.

Possible risk of resorption through skin.

Inhalation of high vapour concentration may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

Inhalation of vapours is irritating to the respiratory system, may cause throat pain and cough.

May cause irritation of the mucous membranes.

SECTION 12: Ecological information

12.1. Toxicity

Ecological data are not available.

Harmful to aquatic life with long lasting effects.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

TIP TOP PRIMER PR 805

Revision: 25.03.2026

Product code: 00156-0546

Page 9 of 12

Zinc oxide
EC50/Selenastrum capricornutum/72 h = 0,17 mg/l
4-Methylpentan-2-one
LC50/Pimephales promelas/96 h = 505 - 540 mg/l
EC50/Daphnia magna/48 h = 170 mg/l
EC50/Selenastrum capricornutum/72 h = 170 mg/l
Toluene
LC50/Carassius Auratus/96 h = 13 mg/l
EC50/algae/72 h = 12,5 mg/l [OECD 201]
Ethyl benzene
ErC50/algae/96 h = 3,6 mg/l

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential

No data available

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

Hazard to waters.

Further information

Do not flush into surface water or sanitary sewer system.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Where possible recycling is preferred to disposal.
Can be incinerated, when in compliance with local regulations.

List of Wastes Code - residues/unused products

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances; hazardous waste

Contaminated packaging

Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.
Packaging that cannot be cleaned should be disposed of like the product.
Empty containers should be taken for local recycling, recovery or waste disposal.

SECTION 14: Transport information

Land transport (ADR/RID)

<u>14.1. UN number or ID number:</u>	UN 1263
<u>14.2. UN proper shipping name:</u>	Paint
<u>14.3. Transport hazard class(es):</u>	3
<u>14.4. Packing group:</u>	II
Hazard label:	3

Safety Data Sheet

according to Regulation (EC) No 1907/2006

TIP TOP PRIMER PR 805

Revision: 25.03.2026

Product code: 00156-0546

Page 10 of 12



Classification code: F1
 Limited quantity: 5 L / 30 kg
 Excepted quantity: E2
 Transport category: 2
 Hazard No: 33
 Tunnel restriction code: D/E

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 1263
14.2. UN proper shipping name: Paint
14.3. Transport hazard class(es): 3
14.4. Packing group: II
 Hazard label: 3



Classification code: F1
 Limited quantity: 5 L / 30 kg
 Excepted quantity: E2

Marine transport (IMDG)

14.1. UN number or ID number: UN 1263
14.2. UN proper shipping name: Paint
14.3. Transport hazard class(es): 3
14.4. Packing group: II
 Hazard label: 3



Marine pollutant: No
 Limited quantity: 5 L / 30 kg
 Excepted quantity: E2
 EmS: F-E, S-E

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1263
14.2. UN proper shipping name: Paint
14.3. Transport hazard class(es): 3
14.4. Packing group: II
 Hazard label: 3



Limited quantity Passenger: 1 L
 Passenger LQ: Y341
 Excepted quantity: E2
 IATA-packing instructions - Passenger: 353
 IATA-max. quantity - Passenger: 5 L
 IATA-packing instructions - Cargo: 364
 IATA-max. quantity - Cargo: 60 L

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

TIP TOP PRIMER PR 805

Revision: 25.03.2026

Product code: 00156-0546

Page 11 of 12

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Handle in accordance with good industrial hygiene and safety practice.

14.7. Maritime transport in bulk according to IMO instruments

The transport takes place only in approved and appropriate packaging.

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 48, Entry 75

Directive 2004/42/EC on VOC in
paints and varnishes: < 75%Information according to Directive
2012/18/EU (SEVESO III): P5c FLAMMABLE LIQUIDS**National regulatory information**

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water hazard class (D): 2 - obviously hazardous to water

15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

SECTION 16: Other information**Changes**

This data sheet contains changes from the previous version in section(s): 1,2,4,9,11,12,15.

Abbreviations and acronyms

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route

RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses

ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure

IMDG = International Maritime Code for Dangerous Goods

IATA/ICAO = International Air Transport Association / International Civil Aviation Organization

MARPOL = International Convention for the Prevention of Pollution from Ships

IBC-Code = International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

REACH = Registration, Evaluation, Authorization and Restriction of Chemicals

CAS = Chemical Abstract Service

EN = European norm

ISO = International Organization for Standardization

DIN = Deutsche Industrie Norm

PBT = Persistent Bioaccumulative and Toxic

vPvB = Very Persistent and very Bio-accumulative

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

TIP TOP PRIMER PR 805

Revision: 25.03.2026

Product code: 00156-0546

Page 12 of 12

LD = Lethal dose
LC = Lethal concentration
EC = Effect concentration
IC = Median immobilisation concentration or median inhibitory concentration

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Carc. 2; H351	Calculation method
Acute Tox. 4; H332	Calculation method
Skin Irrit. 2; H315	Calculation method
Eye Irrit. 2; H319	Calculation method
STOT SE 3; H335	Calculation method
STOT SE 3; H336	Calculation method
STOT RE 2; H373	Calculation method
Aquatic Chronic 3; H412	Calculation method

Relevant H and EUH statements (number and full text)

H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H312 Harmful in contact with skin.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H351 Suspected of causing cancer.
H361d Suspected of damaging the unborn child.
H373 May cause damage to organs through prolonged or repeated exposure.
H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.
EUH066 Repeated exposure may cause skin dryness or cracking.

Further Information

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product (s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

"(n.a. = not applicable; n.d. = not determined)"

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)