

Safety Data Sheet

according to 29 CFR 1910.1200(g)

TIP TOP CAMPLAST CEMENT

Revision date: 09/25/2025

Product code: 00156-0045

Page 1 of 10

1. Identification

Product identifier

TIP TOP CAMPLAST CEMENT

Art.-No.

514 9229, 514 9230, 552 2208, 552 2209, 552 2215, 552 2246, 552 3001, 552 3128, 552 3190, 552 3197, 552 3198, 552 3199, 552 3207, 552 3208, 552 4000, 552 4196, 552 4200, 552 4206, 552 4270, 5096

Recommended use of the chemical and restrictions on use

Use of the substance/mixture

Adhesive

Details of the supplier of the safety data sheet

Company name: REMA TIP TOP / North America Inc.
Street: 1500 Industrial Blvd
Place: Madison, GA 30650, USA
Telephone: +1 800 225 7362,
Internet: www.rematiptop.com
Responsible Department: Responsible for the safety data sheet: sds@gbk-ingelheim.de
Emergency phone number: (USA domestic) 1 800 535 5053 or international (001) 352 323 3500
Infotrac/GBK GmbH-ID: 93591

2. Hazard(s) identification

Classification of the chemical

29 CFR Part 1910.1200

Flammable liquids: Flam. Liq. 2
Serious eye damage/eye irritation: Eye Irrit. 2A
Specific target organ toxicity single exposure: STOT SE 3 (narcotic effects)

Label elements

29 CFR Part 1910.1200

Signal word: Danger**Pictograms:**

Hazard statements

Highly flammable liquid and vapor
Causes serious eye irritation
May cause drowsiness or dizziness

Precautionary statements

Keep out of reach of children.
Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
Keep container tightly closed.
Wear protective gloves/protective clothing/eye protection/face protection.
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
If inhaled: Remove person to fresh air and keep comfortable for breathing.
Store in a well-ventilated place. Keep cool.
Dispose of contents/container to in accordance with local and national regulations.

Hazards not otherwise classified

**Safety Data Sheet**

according to 29 CFR 1910.1200(g)

TIP TOP CAMPLAST CEMENT

Revision date: 09/25/2025

Product code: 00156-0045

Page 2 of 10

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

Vapours may form explosive mixture with air.

3. Composition/information on ingredients**Mixtures****Chemical characterization**

Preparation in butanone

Hazardous components

CAS No	Components	Quantity
78-93-3	Butanone	83.87 %

4. First-aid measures**Description of first aid measures****General information**

Remove contaminated soaked clothing immediately.
If you feel unwell, seek medical advice.

After inhalation

Move to fresh air in case of accidental inhalation of vapours or decomposition products.
Refer for medical treatment.

After contact with skin

Wash off with soap and plenty of water.
Consult a doctor if skin irritation persists.

After contact with eyes

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.
Seek medical treatment by eye specialist.

After ingestion

Do not induce vomiting.
Rinse out mouth and give plenty of water to drink.
Never give anything by mouth to an unconscious person.
Summon a doctor immediately.
The decision whether to induce vomiting or not is to be taken by a physician.

Most important symptoms and effects, both acute and delayed

Causes serious eye irritation.
May cause drowsiness or dizziness.
Repeated exposure may cause skin dryness or cracking.

OSHA Hazard Communication: This material is considered hazardous by the OSHA Hazard Communication Standard 29CFR 1910.1200.

Indication of any immediate medical attention and special treatment needed

Treat symptoms.

5. Fire-fighting measures**Extinguishing media****Suitable extinguishing media**

Alcohol-resistant foam, dry chemical, carbon dioxide (CO₂), water-spray.

Unsuitable extinguishing media

Full water jet.



Safety Data Sheet

according to 29 CFR 1910.1200(g)

TIP TOP CAMPLAST CEMENT

Revision date: 09/25/2025

Product code: 00156-0045

Page 3 of 10

Specific hazards arising from the chemical

Fire may produce:
carbon monoxide and carbon dioxide

Special protective equipment and precautions for fire-fighters

Use breathing apparatus with independent air supply.
Protective suit.

Additional information

Vapours are heavier than air and spread along ground.
The vapour/air mixture is explosive, even in empty, uncleaned receptacles.
Cool containers at risk with water spray jet.
Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

General advice

Use only explosion-proof equipment.
Ensure adequate ventilation.
Keep away sources of ignition.
Keep away noninvolved persons.

For non-emergency personnel

Do not breathe vapours.
Avoid contact with skin, eyes and clothing.

For emergency responders

In case of vapour formation use respirator.
Use personal protective clothing.

Environmental precautions

Do not discharge into the drains/surface waters/groundwater.

Methods and material for containment and cleaning up

For containment

Prevent spread over a wide area (e.g. by containment or oil barriers).

For cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder).
Shovel into suitable container for disposal.

Reference to other sections

Observe protective instructions (see Sections 7 and 8).
Information for disposal look up chapter 13.

7. Handling and storage

Precautions for safe handling

Advice on safe handling

Keep container tightly closed.
When using do not eat, drink or smoke.
Use only in thoroughly ventilated areas.
Avoid contact with skin, eyes and clothing.

Advice on protection against fire and explosion

Keep away from heat and sources of ignition.
Do not smoke.
Take precautionary measures against static discharges.
Use only explosion-proof equipment.

**Safety Data Sheet**

according to 29 CFR 1910.1200(g)

TIP TOP CAMPLAST CEMENT

Revision date: 09/25/2025

Product code: 00156-0045

Page 4 of 10

Advice on general occupational hygiene

- Avoid contact with eyes and skin.
- Wash hands before breaks and immediately after handling the product.
- When using do not eat, drink or smoke.
- Remove and wash contaminated clothes before re-use.

Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

- Keep container tightly closed in a dry, cool and well-ventilated place.

Hints on joint storage

- Incompatible with oxidizing agents.

Further information on storage conditions

- Keep away from food, drink and animal feeding stuffs.

8. Exposure controls/personal protection**Control parameters****Exposure limits**

CAS No	Substance	ppm	mg/m ³	f/cc	Category	Origin
78-93-3	2-Butanone (Methyl ethyl ketone)	200	590		TWA (8 h)	PEL
78-93-3	2-Butanone	200	590		TWA (8 h)	REL
		300	885		STEL (15 min)	REL
78-93-3	Methyl ethyl ketone	75			TWA (8 h)	ACGIH-2024
		150			STEL (15 min)	ACGIH-2024

Biological Exposure Indices (BEI-ACGIH)

CAS No	Substance	Determinant	Value	Test material	Sampling time
78-93-3	METHYL ETHYL KETONE	Methyl ethyl ketone	2 mg/L	urine	End of shift

Exposure controls**Appropriate engineering controls**

- Ensure adequate ventilation, especially in confined areas.

Individual protection measures, such as personal protective equipment**Eye/face protection**

- Tightly fitting goggles.
- Eye wash bottle with pure water.

Hand protection

- Protective gloves resistant to chemicals made of butyl, Minimum coat thickness 0,7 mm, Permeation resistance (wear duration) > 240 minutes, i.e. protective glove <Butoject 898> made by www.kcl.de. This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions. Requirements can vary as a function of the use. Therefore, it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves. Protective gloves resistant to chemicals made off butyl, Minimum coat thickness 0.7 mm, Permeation resistance (wear duration) > 30 minutes, i.e. protective glove <Butoject 898> made by www.kcl.de.

Skin protection

- Long sleeved clothing.

Respiratory protection

- In case of insufficient ventilation wear suitable respiratory equipment (gas filter type A).

**Safety Data Sheet**

according to 29 CFR 1910.1200(g)

TIP TOP CAMPLAST CEMENT

Revision date: 09/25/2025

Product code: 00156-0045

Page 5 of 10

9. Physical and chemical properties**Information on basic physical and chemical properties**

Physical state:	Liquid
Color:	Yellow
Odor:	Like ketone

Test method**Changes in the physical state**

Melting point/freezing point:	n.d.
Boiling point or initial boiling point and boiling range:	approx. 80 °C
Sublimation point:	n.a.
Softening point:	n.d.
Flash point:	- 7 °C DIN EN ISO 3679

Flammability

Solid/liquid:	n.a.
---------------	------

Explosive properties

The product is considered non-explosive; nevertheless explosive vapour/air mixture can be generated.

Lower explosion limits:	1,8 vol. %
Upper explosion limits:	11,5 vol. %
Auto-ignition temperature:	505 °C

Self-ignition temperature

Solid:	n.a.
Gas:	n.a.

Decomposition temperature:	n.d.
----------------------------	------

Viscosity / dynamic:	n.d.
----------------------	------

Viscosity / kinematic:	n.d.
------------------------	------

Flow time:	n.d.
------------	------

Water solubility: (at 20 °C)	350 g/L
---------------------------------	---------

Solubility in other solvents

n.d.

Partition coefficient n-octanol/water:	n.d.
--	------

Vapor pressure: (at 20 °C)	105 hPa
-------------------------------	---------

Density (at 20 °C):	0,86 g/cm ³
---------------------	------------------------

Bulk density:	n.a.
---------------	------

Relative vapour density:	n.d.
--------------------------	------

Other information**Information with regard to physical hazard classes**

Sustained combustibility:	Sustained combustibility
---------------------------	--------------------------

Oxidizing properties

Not oxidising.

Other safety characteristics

Solvent separation test:	0 %
--------------------------	-----

**Safety Data Sheet**

according to 29 CFR 1910.1200(g)

TIP TOP CAMPLAST CEMENT

Revision date: 09/25/2025

Product code: 00156-0045

Page 6 of 10

Solvent content: < 90 %
Evaporation rate: n.d.

Further Information

No data available

10. Stability and reactivity**Reactivity**

No decomposition if stored and applied as directed.

Chemical stability

Stability: Stable

Stable under normal conditions.

Possibility of hazardous reactions

Hazardous reactions: Will not occur

Reactions with oxidizing agents.

Conditions to avoid

Vapour/air mixtures are explosive at intensive warming.

Heating can release vapours which can be ignited.

Incompatible materials

Oxidizing agents

Hazardous decomposition products

No hazardous decomposition products known.

Fire may produce:

Carbon monoxide and carbon dioxide

11. Toxicological information**Route(s) of Entry**

Skin and eye contact and ingestion.

Information on toxicological effects**Acute toxicity**

Based on available data, the classification criteria are not met.

No toxicological data available.

Butanone

LD50/oral/rat: 3300 mg/kg

LD50/dermal/rabbit: 6400 - 8000 mg/kg

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

Irritation and corrosivity

Serious eye damage/eye irritation: Causes serious eye irritation

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Sensitizing effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

Specific target organ toxicity (STOT) - single exposure

May cause drowsiness or dizziness (Butanone)

**Safety Data Sheet**

according to 29 CFR 1910.1200(g)

TIP TOP CAMPLAST CEMENT

Revision date: 09/25/2025

Product code: 00156-0045

Page 7 of 10

Specific target organ toxicity (STOT) - repeated exposure

Based on available data, the classification criteria are not met.

Carcinogenicity (OSHA): No ingredient of this mixture is listed.

Carcinogenicity (IARC): No ingredient of this mixture is listed.

Carcinogenicity (NTP): No ingredient of this mixture is listed.

Aspiration hazard

Based on available data, the classification criteria are not met.

Additional information on tests

This product is classified in accordance with the GHS regulations.

Information on other hazards**Endocrine disrupting properties**

No data available

Other information

Concentration above the admissible concentration at the workplace may cause dizziness, headache and inebriation.

Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea.

12. Ecological information**Ecotoxicity**

Ecological data are not available.

Butanone

LC50/Pimephales promelas/96 h = 3220 mg/l

EC50/Daphnia magna/48 h = 5091 mg/l

Persistence and degradability

No data available

Butanone

Readily biodegradable (to OECD criteria)

Bioaccumulative potential

No data available

Mobility in soil

No data available

Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

Other adverse effects

Slightly water hazardous.

Further information

Ecological injuries are not known or expected under normal use.

Do not flush into surface water or sanitary sewer system.

13. Disposal considerations**Waste treatment methods****Disposal recommendations**

Can be disposed of as a solid waste or burned in a suitable installation subject to local regulations.

Where possible recycling is preferred to disposal.

Contaminated packaging

Empty containers should be taken for local recycling, recovery or waste disposal.

Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.

Safety Data Sheet

according to 29 CFR 1910.1200(g)

TIP TOP CAMPLAST CEMENT

Revision date: 09/25/2025

Product code: 00156-0045

Page 8 of 10

Packaging that cannot be cleaned should be disposed of like the product.

14. Transport information

U.S. DOT 49 CFR 172.101

UN number or ID number: UN 1133
Proper shipping name: Adhesives
Transport hazard class(es): 3
Packing group: II
Hazard label: 3



Marine transport (IMDG)

UN number or ID number: UN 1133
UN proper shipping name: Adhesives
Transport hazard class(es): 3
Packing group: II
Hazard label: 3



Marine pollutant: No
Limited quantity: 5 L / 30 kg
Excepted quantity: E2
EmS: F-E, S-D
Segregation group: alkalis

Air transport (ICAO-TI/IATA-DGR)

UN number or ID number: UN 1133
UN proper shipping name: Adhesives
Transport hazard class(es): 3
Packing group: II
Hazard label: 3



Limited quantity Passenger: 1 L
Passenger LQ: Y341
Excepted quantity: E2
IATA-packing instructions - Passenger: 353
IATA-max. quantity - Passenger: 5 L
IATA-packing instructions - Cargo: 364
IATA-max. quantity - Cargo: 60 L

Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

Special precautions for user

Handle in accordance with good industrial hygiene and safety practice.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

The transport takes place only in approved and appropriate packaging.

**Safety Data Sheet**

according to 29 CFR 1910.1200(g)

TIP TOP CAMPLAST CEMENT

Revision date: 09/25/2025

Product code: 00156-0045

Page 9 of 10

15. Regulatory information**U.S. Regulations****National Inventory TSCA**

All of the components are listed on the TSCA inventory.

National regulatory information

SARA Section 304 CERCLA:

Methyl ethyl ketone (78-93-3): Reportable quantity = 5,000 (2270) lbs. (kg)

SARA Section 311/312 Hazards:

Methyl ethyl ketone (78-93-3): Fire hazard, Immediate (acute) health hazard

Clean Air Act Section 112(b):

Methyl ethyl ketone (78-93-3)

State Regulations**Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65, State of California)**

This product can not expose you to chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.

16. Other information**Hazardous Materials Identification System (HMIS)**

Health: 1

Flammability: 2

Physical Hazard: 0

NFPA Hazard Ratings

Health: 1

Flammability: 2

Reactivity: 0

Unique Hazard:

**Changes**

Revision date: 25.09.2025

Revision No: 2,9

This data sheet contains changes from the previous version in section(s): 2,6,8,9,10,11,14.

Abbreviations and acronyms

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route

RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses

ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure

IMDG = International Maritime Code for Dangerous Goods

IATA/ICAO = International Air Transport Association / International Civil Aviation Organization

MARPOL = International Convention for the Prevention of Pollution from Ships

IBC-Code = International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

REACH = Registration, Evaluation, Authorization and Restriction of Chemicals

CAS = Chemical Abstract Service

EN = European norm

ISO = International Organization for Standardization

DIN = Deutsche Industrie Norm

PBT = Persistent Bioaccumulative and Toxic

vPvB = Very Persistent and very Bio-accumulative

**Safety Data Sheet**

according to 29 CFR 1910.1200(g)

TIP TOP CAMPLAST CEMENT

Revision date: 09/25/2025

Product code: 00156-0045

Page 10 of 10

LD = Lethal dose

LC = Lethal concentration

EC = Effect concentration

IC = Median immobilisation concentration or median inhibitory concentration

Other data

The information in this document is based on the present state of knowledge and is applicable to the product with regard to appropriate safety precautions.

The information describes exclusively the safety requirements for the product (s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

(n.a. = not applicable; n.d. = not determined)

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)