

## Safety Data Sheet

according to 29 CFR 1910.1200(g)

### TIP TOP PRIMER PR 805

Revision date: 03/25/2026

Product code: 00156-0546

Page 1 of 11

## 1. Identification

### Product identifier

TIP TOP PRIMER PR 805

### Art.-No.

525 2422, 525 2431, 525 2732

### Recommended use of the chemical and restrictions on use

#### Use of the substance/mixture

Primer Coat

### Details of the supplier of the safety data sheet

Company name: REMA TIP TOP / North America Inc.  
Street: 1500 Industrial Blvd  
Place: Madison, GA 30650, USA  
Telephone: +1 800 225 7362,  
Internet: www.rematiptop.com  
Responsible Department: Responsible for the safety data sheet: sds@gbk-ingelheim.de  
Emergency phone number: (USA domestic) 1 800 535 5053 or international (001) 352 323 3500  
Infotrac/GBK GmbH-ID: 93591

## 2. Hazard(s) identification

### Classification of the chemical

#### 29 CFR Part 1910.1200

Flammable liquids: Category 2  
Carcinogenicity: Category 2  
Reproductive toxicity: Category 2  
Acute toxicity: Category 4 (inhalation)  
Skin corrosion/irritation: Category 2  
Serious eye damage/eye irritation: Category 2A  
Specific target organ toxicity single exposure: Category 3 (narcotic effects) (respiratory tract irritation)  
Specific target organ toxicity repeated or prolonged exposure: Category 2  
Hazardous to the aquatic environment: Aquatic Chronic 3

### Label elements

#### 29 CFR Part 1910.1200

**Signal word:** Danger

**Pictograms:**



### Hazard statements

Highly flammable liquid and vapor  
Causes skin irritation and serious eye irritation  
Harmful if inhaled  
May cause respiratory irritation  
May cause drowsiness or dizziness  
Suspected of causing cancer  
Suspected of damaging the unborn child  
May cause damage to organs through prolonged or repeated exposure  
Harmful to aquatic life with long lasting effects

**Safety Data Sheet**

according to 29 CFR 1910.1200(g)

**TIP TOP PRIMER PR 805**

Revision date: 03/25/2026

Product code: 00156-0546

Page 2 of 11

**Precautionary statements**

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
Take precautionary measures against static discharge.  
Wear protective gloves/protective clothing/eye protection/face protection.  
If exposed or concerned: Get medical advice/attention.  
Store in a well-ventilated place. Keep cool.

**Hazards not otherwise classified**

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.  
Vapours may form explosive mixture with air.

**3. Composition/information on ingredients****Mixtures****Chemical characterization**

Preparation with polymers in xylene and 4-methylpentan-2-one

**Hazardous components**

CAS No	Components	Quantity
108-10-1	4-Methylpentan-2-one	< 50 %
	Reaction mass of ethylbenzene and xylene	< 25 %
78-93-3	Butanone	< 5 %
108-88-3	Toluene	< 1 %

**4. First-aid measures****Description of first aid measures****General information**

Remove contaminated soaked clothing immediately.  
Symptoms of poisoning may not appear for several hours. Keep under medical supervision for at least 48 hours.  
In the event of persistent symptoms receive medical treatment.  
Take away from danger area and lay down affected person.

**After inhalation**

Move to fresh air in case of accidental inhalation of vapours.  
Seek medical treatment immediately.

**After contact with skin**

Wash off with soap and plenty of water.  
Possible risk of resorption through skin.  
If a person feels unwell or symptoms of skin irritation appear, consult a physician.

**After contact with eyes**

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.  
Remove contact lenses, if present and easy to do. Continue rinsing.  
Seek medical treatment by eye specialist.

**After ingestion**

Do not induce vomiting.  
Rinse mouth.  
Never give anything by mouth to an unconscious person.  
Summon a doctor immediately.  
Induce vomiting only upon the advice of a physician.

**Most important symptoms and effects, both acute and delayed**

Harmful if inhaled.



## Safety Data Sheet

according to 29 CFR 1910.1200(g)

### TIP TOP PRIMER PR 805

Revision date: 03/25/2026

Product code: 00156-0546

Page 3 of 11

Causes skin irritation.  
Causes serious eye irritation.  
May cause respiratory irritation.  
May cause drowsiness or dizziness.  
Suspected of causing cancer.  
May cause damage to organs through prolonged or repeated exposure.  
Suspected of damaging the unborn child.

#### **Indication of any immediate medical attention and special treatment needed**

Treat symptoms.

## 5. Fire-fighting measures

### **Extinguishing media**

#### **Suitable extinguishing media**

Foam, carbon dioxide (CO<sub>2</sub>), dry chemical, water-spray.

#### **Unsuitable extinguishing media**

Full water jet.

### **Specific hazards arising from the chemical**

Fire may produce:  
carbon monoxide and carbon dioxide  
Hydrogen chloride (HCl)

### **Special protective equipment and precautions for fire-fighters**

Use breathing apparatus with independent air supply.  
Protective suit.

### **Additional information**

Vapours are heavier than air and spread along ground.  
The vapour/air mixture is explosive, even in empty, uncleaned receptacles.  
Cool containers at risk with water spray jet.  
Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

## 6. Accidental release measures

### **Personal precautions, protective equipment and emergency procedures**

#### **General advice**

Ensure adequate ventilation.  
Remove persons to safety.

#### **For non-emergency personnel**

Do not breathe vapours.  
Avoid contact with skin, eyes and clothing.

#### **For emergency responders**

In case of vapour formation use respirator.  
Use personal protective clothing.

### **Environmental precautions**

Do not discharge into the drains/surface waters/groundwater.  
Clean contaminated surface thoroughly.

### **Methods and material for containment and cleaning up**

#### **For containment**

Prevent spread over a wide area (e.g. by containment or oil barriers).

#### **For cleaning up**

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder).  
Shovel into suitable container for disposal.



## Safety Data Sheet

according to 29 CFR 1910.1200(g)

### TIP TOP PRIMER PR 805

Revision date: 03/25/2026

Product code: 00156-0546

Page 4 of 11

#### Reference to other sections

Observe protective instructions (see Sections 7 and 8).  
Information for disposal look up chapter 13.

## 7. Handling and storage

#### Precautions for safe handling

##### **Advice on safe handling**

Do not wear contact lenses when handling the product.  
Keep container tightly closed.  
Vapours are heavier than air and spread along ground.  
Keep a good ventilation and air-exhaust at the place of work.  
Avoid contact with skin, eyes and clothing.

##### **Advice on protection against fire and explosion**

Keep away from heat and sources of ignition.  
Do not smoke.  
Take precautionary measures against static discharges.  
Pay attention to anti-explosion protection rules: In case of an explosive atmosphere use only explosion-proof equipment.

##### **Advice on general occupational hygiene**

Do not inhale vapours.  
Wash hands before breaks and immediately after handling the product.  
When using do not eat, drink or smoke.  
Avoid contact with skin, eyes and clothing.  
Remove and wash contaminated clothes before re-use.

#### Conditions for safe storage, including any incompatibilities

##### **Requirements for storage rooms and vessels**

Keep container tightly closed in a dry, cool and well-ventilated place.  
Pay attention to anti-explosion rules.

##### **Hints on joint storage**

Incompatible with oxidizing agents.

##### **Further information on storage conditions**

Keep away from food, drink and animal feeding stuffs.

## 8. Exposure controls/personal protection

#### Control parameters

**Safety Data Sheet**

according to 29 CFR 1910.1200(g)

**TIP TOP PRIMER PR 805**

Revision date: 03/25/2026

Product code: 00156-0546

Page 5 of 11

**Exposure limits**

CAS No	Substance	ppm	mg/m <sup>3</sup>	f/cc	Category	Origin
78-93-3	2-Butanone (Methyl ethyl ketone)	200	590		TWA (8 h)	REL
78-93-3	2-Butanone	200	590		TWA (8 h)	REL
		300	885		STEL (15 min)	REL
100-41-4	Ethyl benzene	100	435		TWA (8 h)	REL
		100	435		TWA (8 h)	REL
		125	545		STEL (15 min)	REL
100-41-4	Ethyl benzene	20	-		TWA (8 h)	ACGIH-2025
108-10-1	Hexone (Methyl isobutyl ketone)	100	410		TWA (8 h)	REL
108-10-1	Hexone	50	205		TWA (8 h)	REL
		75	300		STEL (15 min)	REL
78-93-3	Methyl ethyl ketone	75			TWA (8 h)	ACGIH-2025
		150			STEL (15 min)	ACGIH-2025
112926-00-8	Silica, amorphous, precipitated and gel	706	(Z-3)		TWA (8 h)	REL
		mp/m <sup>3</sup>				
13463-67-7	Titanium dioxide Total dust	-	15		TWA (8 h)	REL
13463-67-7	Titanium dioxide: Finescale particles (Respirable particulate matter)	-	2.5		TWA (8 h)	ACGIH-2025
13463-67-7	Titanium dioxide				as low as possible	REL
108-88-3	Toluene	200	-		TWA (8 h)	REL
		C 300	-		Ceiling	REL
		500	-		Peak (10 min)	REL
108-88-3	Toluene	100	375		TWA (8 h)	REL
		150	560		STEL (15 min)	REL
108-88-3	Toluene	20	-		TWA (8 h)	ACGIH-2025
-	Wood dusts (inhalable fraction): All other species/All other wood dusts		1		TWA (8 h)	ACGIH-2025
1330-20-7	Xylene: mixed isomers	20			TWA (8 h)	ACGIH-2025
1330-20-7	Xylenes (o-,m-,p-isomers)	100	435		TWA (8 h)	REL

**Biological Exposure Indices (BEI-ACGIH)**

CAS No	Substance	Determinant	Value	Test material	Sampling time
108-10-1	METHYL ISOBUTYL KETONE	Methyl isobutyl ketone	1 mg/L	urine	End of shift
78-93-3	METHYL ETHYL KETONE	Methyl ethyl ketone	2 mg/L	urine	End of shift
108-88-3	TOLUENE	Toluene	0.02 mg/L	blood	Prior to last shift of workweek
100-41-4	Ethyl benzene	Sum of mandelic acid and phenylglyoxylic acid (creatinine)	0.15 g/g	urine	End of shift

**Exposure controls****Appropriate engineering controls**

Ensure adequate ventilation, especially in confined areas.

**Individual protection measures, such as personal protective equipment**

**Safety Data Sheet**

according to 29 CFR 1910.1200(g)

**TIP TOP PRIMER PR 805**

Revision date: 03/25/2026

Product code: 00156-0546

Page 6 of 11

**Eye/face protection**

Tightly fitting goggles.  
Eye wash bottle with pure water.

**Hand protection**

Splash protection:  
Protective gloves resistant to chemicals made of butyl, Minimum coat thickness 0,7 mm, Permeation resistance (wear duration) > 240 minutes, i.e. protective glove <Butoject 898> made by www.kcl.de.  
This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.  
Requirements can vary as a function of the use. Therefore, it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

**Skin protection**

Solvent-resistant apron.

**Respiratory protection**

In case of insufficient ventilation wear suitable respiratory equipment (gas filter type A).

**9. Physical and chemical properties****Information on basic physical and chemical properties**

Physical state:	Liquid
Color:	Grey
Odor:	Aromatic

**Test method****Changes in the physical state**

Melting point/freezing point:	n.d.
Boiling point or initial boiling point and boiling range:	n.d.
Sublimation point:	n.a.
Softening point:	n.d.
Pour point:	n.d.
Flash point:	15 °C

**Flammability**

Solid/liquid:	n.a.
---------------	------

**Explosive properties**

The product is considered non-explosive; nevertheless explosive vapour/air mixture can be generated.

Lower explosion limits:	1,4 vol. % (*)
Upper explosion limits:	7,5 vol. % (*)
Auto-ignition temperature:	n.d.

**Self-ignition temperature**

Solid:	n.a.
Gas:	n.a.
Decomposition temperature:	n.d.
pH-Value:	n.d.
Viscosity / dynamic:	10 - 300 mPa·s
Viscosity / kinematic: (at 40 °C)	> 20,5 mm <sup>2</sup> /s
Flow time:	n.d.

**Safety Data Sheet**

according to 29 CFR 1910.1200(g)

**TIP TOP PRIMER PR 805**

Revision date: 03/25/2026

Product code: 00156-0546

Page 7 of 11

Water solubility: Immiscible  
(at 20 °C)

**Solubility in other solvents**

n.d.

Partition coefficient n-octanol/water: n.d.

Vapor pressure: n.d.  
(at 20 °C)

Density (at 20 °C): 0,87 - 0,92 g/cm<sup>3</sup>

Bulk density: n.a.

Relative vapour density: n.d.

**Other information****Information with regard to physical hazard classes**

Sustained combustibility: Sustained combustibility

Oxidizing properties

Not oxidising.

**Other safety characteristics**

Solvent separation test: n.d.

Solvent content: < 75 %

Evaporation rate: n.d.

**Further Information**

(\*) 4-Methylpentan-2-one

**10. Stability and reactivity****Reactivity**

No decomposition if stored and applied as directed.

**Chemical stability**

Stable under normal conditions.

**Possibility of hazardous reactions**

Reactions with oxidizing agents.

**Conditions to avoid**

To avoid thermal decomposition, do not overheat.

Vapour/air mixtures are explosive at intensive warming.

Heating can release vapours which can be ignited.

**Incompatible materials**

Strong oxidizing agents

**Hazardous decomposition products**

No hazardous decomposition products known.

Fire may produce:

Carbon monoxide and carbon dioxide

Hydrogen chloride (HCl)

**11. Toxicological information****Information on toxicological effects****Acute toxicity**

Harmful if inhaled

No toxicological data available.

**Safety Data Sheet**

according to 29 CFR 1910.1200(g)

**TIP TOP PRIMER PR 805**

Revision date: 03/25/2026

Product code: 00156-0546

Page 8 of 11

**ATEmix calculated**

ATE (oral) &gt; 2000 mg/kg; ATE (dermal) &gt; 2000 mg/kg

**Irritation and corrosivity**

Skin corrosion/irritation: Causes skin irritation

Serious eye damage/eye irritation: Causes serious eye irritation

**Sensitizing effects**

Based on available data, the classification criteria are not met.

**Carcinogenic/mutagenic/toxic effects for reproduction**

Suspected of causing cancer (4-Methylpentan-2-one)

Suspected of damaging the unborn child (Toluene)

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

**Specific target organ toxicity (STOT) - single exposure**

May cause respiratory irritation (4-Methylpentan-2-one; Reaction mass of ethylbenzene and xylene)

May cause drowsiness or dizziness (4-Methylpentan-2-one)

**Specific target organ toxicity (STOT) - repeated exposure**

May cause damage to organs through prolonged or repeated exposure (Reaction mass of ethylbenzene and xylene)

Carcinogenicity (IARC): Methyl isobutyl ketone (CAS 108-10-1) is listed in group 2B. Titanium dioxide (CAS 13463-67-7) is listed in group 2B. Toluene (CAS 108-88-3) is listed in group 3.

**Aspiration hazard**

Based on available data, the classification criteria are not met.

**Practical experience**

This product is classified in accordance with the GHS regulations.

**Information on other hazards****Endocrine disrupting properties**

No data available

**Other information**

Inhalation of vapours is irritating to the respiratory system, may cause throat pain and cough.

Repeated exposure may cause skin dryness or cracking.

Possible risk of resorption through skin.

Inhalation of high vapour concentration may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

Inhalation of vapours is irritating to the respiratory system, may cause throat pain and cough.

May cause irritation of the mucous membranes.

**12. Ecological information****Ecotoxicity**

Ecological data are not available.

Harmful to aquatic life with long lasting effects.

Zinc oxide

EC50/Selenastrum capricornutum/72 h = 0,17 mg/l

4-Methylpentan-2-one

LC50/Pimephales promelas/96 h = 505 - 540 mg/l

EC50/Daphnia magna/48 h = 170 mg/l

EC50/Selenastrum capricornutum/72 h = 170 mg/l

Toluene

LC50/Carassius Auratus/96 h = 13 mg/l

EC50/algae/72 h = 12,5 mg/l [OECD 201]

Ethyl benzene

ErC50/algae/96 h = 3,6 mg/l

**Persistence and degradability**

**Safety Data Sheet**

according to 29 CFR 1910.1200(g)

**TIP TOP PRIMER PR 805**

Revision date: 03/25/2026

Product code: 00156-0546

Page 9 of 11

No data available

**Bioaccumulative potential**

No data available

**Mobility in soil**

No data available

**Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

**Other adverse effects**

Hazardous water pollutant.

**Further information**

Do not flush into surface water or sanitary sewer system.

**13. Disposal considerations****Waste treatment methods****Disposal recommendations**

Where possible recycling is preferred to disposal.  
Can be incinerated, when in compliance with local regulations.

**Contaminated packaging**

Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.  
Packaging that cannot be cleaned should be disposed of like the product.  
Empty containers should be taken for local recycling, recovery or waste disposal.

**14. Transport information****U.S. DOT 49 CFR 172.101**

<b><u>UN number or ID number:</u></b>	UN 1263
<b><u>Proper shipping name:</u></b>	PAINT
<b><u>Transport hazard class(es):</u></b>	3
<b><u>Packing group:</u></b>	II
Hazard label:	3

**Marine transport (IMDG)**

<b><u>UN number or ID number:</u></b>	UN 1263
<b><u>UN proper shipping name:</u></b>	Paint
<b><u>Transport hazard class(es):</u></b>	3
<b><u>Packing group:</u></b>	II
Hazard label:	3



Marine pollutant:	No
Limited quantity:	5 L / 30 kg
Excepted quantity:	E2
EmS:	F-E, S-E

**Air transport (ICAO-TI/IATA-DGR)**

<b><u>UN number or ID number:</u></b>	UN 1263
---------------------------------------	---------

**Safety Data Sheet**

according to 29 CFR 1910.1200(g)

**TIP TOP PRIMER PR 805**

Revision date: 03/25/2026

Product code: 00156-0546

Page 10 of 11

**UN proper shipping name:** Paint  
**Transport hazard class(es):** 3  
**Packing group:** II  
Hazard label: 3



Limited quantity Passenger: 1 L  
Passenger LQ: Y341  
Excepted quantity: E2  
IATA-packing instructions - Passenger: 353  
IATA-max. quantity - Passenger: 5 L  
IATA-packing instructions - Cargo: 364  
IATA-max. quantity - Cargo: 60 L

**Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: No

**Special precautions for user**

Handle in accordance with good industrial hygiene and safety practice.

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

The transport takes place only in approved and appropriate packaging.

**15. Regulatory information****U.S. Regulations****National Inventory TSCA**

All of the components are listed on the TSCA inventory.

**National regulatory information**

SARA Section 304 CERCLA:

Methyl isobutyl ketone (108-10-1): Reportable quantity = 5,000 (2270) lbs. (kg)

Xylene (mixed isomers) (1330-20-7): Reportable quantity = 100 (45.4) lbs. (kg)

Methyl ethyl ketone (78-93-3): Reportable quantity = 5,000 (2270) lbs. (kg)

Toluene (108-88-3): Reportable quantity = 1,000 (454) lbs. (kg)

Ethylbenzene (100-41-4): Reportable quantity = 1,000 (454) lbs. (kg)

SARA Section 311/312 Hazards:

Methyl isobutyl ketone (108-10-1): Fire hazard, Delayed (chronic) health hazard, Immediate (acute) health hazard

Xylene (mixed isomers) (-): Fire hazard, Immediate (acute) health hazard, Delayed (chronic) health hazard

Methyl ethyl ketone (78-93-3): Fire hazard, Immediate (acute) health hazard

Toluene (108-88-3): Fire hazard, Immediate (acute) health hazard, Delayed (chronic) health hazard

SARA Section 313 Toxic release inventory:

Methyl isobutyl ketone (108-10-1): De minimis limit = 1.0 %, Reportable threshold = Standard

Xylene (mixed isomers) (1330-20-7): De minimis limit = 1.0 %, Reportable threshold = Standard

Toluene (108-88-3): De minimis limit = 1.0 %, Reportable threshold = Standard

Ethylbenzene (100-41-4): De minimis limit = 0.1 %, Reportable threshold = Standard

Clean Air Act Section 112(b):

Methyl isobutyl ketone (108-10-1), Xylene (mixed isomers) (1330-20-7), Methyl ethyl ketone (78-93-3),

Toluene (108-88-3), Ethylbenzene (100-41-4)

**State Regulations****Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65, State of California)**

WARNING: This product can expose you to chemicals including Methyl isobutyl ketone (MIBK) (cancer, developmental); Carbon black (airborne, unbound particles of respirable size) (cancer); Toluene (developmental), which are known to the State of California to cause cancer, birth defects or other reproductive

**Safety Data Sheet**

according to 29 CFR 1910.1200(g)

**TIP TOP PRIMER PR 805**

Revision date: 03/25/2026

Product code: 00156-0546

Page 11 of 11

harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).**16. Other information****Hazardous Materials Identification System (HMIS)**

Health: \*1  
Flammability: 3  
Physical Hazard: 0

**NFPA Hazard Ratings**

Health: 1  
Flammability: 3  
Reactivity: 0  
Unique Hazard:

**Changes**

Revision date: 25.03.2026  
Revision No: 1,1

This data sheet contains changes from the previous version in section(s): 1,2,4,9,11,12.

**Abbreviations and acronyms**

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route  
RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses  
ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure  
IMDG = International Maritime Code for Dangerous Goods  
IATA/ICAO = International Air Transport Association / International Civil Aviation Organization  
MARPOL = International Convention for the Prevention of Pollution from Ships  
IBC-Code = International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk

GHS = Globally Harmonized System of Classification and Labelling of Chemicals  
REACH = Registration, Evaluation, Authorization and Restriction of Chemicals  
CAS = Chemical Abstract Service  
EN = European norm  
ISO = International Organization for Standardization  
DIN = Deutsche Industrie Norm  
PBT = Persistent Bioaccumulative and Toxic  
vPvB = Very Persistent and very Bio-accumulative  
LD = Lethal dose  
LC = Lethal concentration  
EC = Effect concentration  
IC = Median immobilisation concentration or median inhibitory concentration

**Other data**

The information in this document is based on the present state of knowledge and is applicable to the product with regard to appropriate safety precautions.  
The information describes exclusively the safety requirements for the product (s) and is based on the present level of our knowledge.  
The delivery specifications are contained in the corresponding product sheet.  
This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.  
(n.a. = not applicable; n.d. = not determined)

*(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*